Laboratorijsko postrojenje zglobne veze noseće konstrukcije hodnog stroja bagera

Milomir Gašić^{1*}, Goran Marković¹, Mile Savković¹, Nebojša Zdravković¹

¹Univerzitet u Kragujevcu, Fakultet za mašinstvo i građevinarstvo u Kraljevu

Predstavljeno laboratorijsko postrojenje obuhvata formiranje nove koncepcije veze okretnog i neokretnog dela mašina transportne i građevinske mehanizacije. Nova koncepcija veze ide u pravcu obezbeđenja bolje prilagodljivosti stazi po kojoj se mašina kreće i poboljšanju funkcije posrednih elemenata izvedenih u obliku ležajeva velikih prečnika (tipa Rothe Erde) uz povećanje pouzdanosti u radu i brzini izvođenja radnih operacija. Veze okretnih i neokretnih konstrukcija mašina transportne i građevinske mehanizacije su se razvijale pod uticajem različitih radnih i konstruktivnih zahteva. Međutim, dosadašnja konceptijska rešenja (izvedena u obliku "X" i "H" tipa) ne obezbeđuju pouzdan i dugotrajan rad posrednih elemenata (ležajeva velikih prečnika) ugrađenih između okretnog i neokretnog dela. Kao problem pred pronalazak postavlja se zahtev kako konstrukcijski obezbediti rasterećenje i pouzdan rad posrednog elementa (ležajeva velikih prečnika) ugrađenog između okretnog i neokretnog dela noseće konstrukcije bagera. Za razliku od postojećih rešenja sa krutom vezom, razvijeno novo rešenje bazira se na zglobnoj vezi u cilju torzionog rasterećenja noseće konstrukcije hodnog stroja bagera. Rešenje je tako koncipirano da se, osim kod bagera, može primeniti i na druge mašine građevinske i transportne mehanizacije.

Ključne riječi: laboratorijsko postrojenje, radijalno-aksijalni ležaj, torziona krutost, noseći ram, deplanacija

1. UVOD

Opšte je poznato da nije moguće ostvariti potpuni kontakt između staze i hodnog stroja bagera. Problem ostvarivanja kontakta može biti, gotovo po pravilu usled neravnina na podlozi ili pak ređe grešaka nastalih u toku izrade. Kao posledica toga, u toku eksploatacije dolazi do pojave odizanja ili spuštanja nekog od oslonaca mašine, odnosno preraspodele vertikalnih reakcija u osloncima a samim tim i deformacija noseće konstrukcije [1, 2, 3]. Ova pojava ima za posledicu činjenicu da noseći ramovi izvedenih rešenja radijalno-aksijalnih ležajeva ne mogu u potpunosti da obezbede potrebnu krutost oslone površine za vezu ležaja a samim time i normalno funkcionisanje veze okretnog i neokretnog dela kod takvih mašina (slika 1).

Slika 1. Elementi veze okretnog i neokretnog dela posredstvom ležajeva velikih prečnika [4]

Polazeći od široke primene ovakve vrste oslanjanja, problema koji se javljaju pri prenošenju opterećenja sa okretnih na neokretne delove nosećih konstrukcija mašina građevinske i transportne mehanizacije, analiza i istraživanje u cilju povećanja veka trajanja i sigurnosti u radu navedenih mašina se nameće kao imperativ. Vremenom su se rešenja veze usavršavala, tako što je ugrađen međuelement - cilindrični nosač, koji ima za cilj smanjenje deplanacije oslone površine radijalno-aksijalnog ležaja velikog prečnika [4].

Normalno funkcionisanje mašina građevinske i transportne mehanizacije, sa okretnim i neokretnim delom zavisi od uticajnih parametara na veličinu pritisaka u osloncima. Drugim rečima rezultati istraživanja prenošenja opterećenja sa okretnog dela na vezu sa neokretnim delom, treba da definišu uticajne parametre od čijih vrednosti zavisi pravilnost funkcionisanja navedene veze. Generalno, izvedena rešenja nosećih konstrukcija mašina građevinske i transportne mehanizacije su takva da deformacije uglavnom prima oslona konstrukcija ležaja velikih prečnika (oslona ploča, nosači za koje je ploča vezana i kruti prsten).

Slika 2. Zona dejstva rezultante pri oslanjanju u četiri i tri tačke

Statički određena šema oslanjanja u tri tačke se uglavnom primenjuje kod rudarskih mašina visoke proizvodnosti, savremenih portalnih kranova sa horizontalnim premeštanjem tereta i nekih stubnih dizalica. U svim ostalim slučajevima primenjuje se oslanjanje u četiri tačke. Razlog veće primene statički neodređene šeme oslanjanja u četiri tačke leži u tome, što se rezultanta vertikalnih sila može raspodeliti u široj zoni, nego pri oslanjanju u tri tačke sa istom širinom oslanjanja. Ovo se očigledno vidi i na uporednoj šemi mašina sa sakretnim delom (slika 2) [5]. Pri oslanjanju u četiri tačke, sile u osloncima zavise od stanja oslone površine (neravnine i deformacije) kao i od konstruktivnog izvođenja i elastičnosti hodnih delova mašina.

Slika 3. Zona dejstva rezultante pri oslanjanju u četiri i tri tačke

Dakle, u slučaju da se pojave deformacije podloge ili pak greške u izradi i montaži šina, osloni pravougaonik se može podeliti na dva trougla (slika 3). Ukoliko rezultanta prolazi kroz jedan od dva trougla, npr. $\triangle ABC$, dolazi do odvajanja od podloge ili šine suprotnog oslonca D, neopterećenog trougla $\triangle ACD$. Daljim okretanjem gornjeg dela mašine, rezultanta se pomera i dolazi do prevrtanja mašine oko AC, pa je u tom slučaju oslanjanje preko $\triangle ACD$, odnosno oslonac B se podiže od podloge ili šine.

Iz svega ovog proizilazi da je neophodno eliminisati takav neželjeni efekat, odnosno dovesti do ravnomernog oslanjanja na sve tačkove. Analiza ovog problema sa uticajem prethodno navedenih pojava je obimna, jer zahteva i prethodno uvođenje parametara pokretnih delova (hodnog stroja) i staze po kojoj se mašina kreće. Ocena i uticaj neravnina staze često su vezani za pojedine poteškoće, te se koriste približne metode proračuna [6]. Saglasno jednačinama ravnoteže i uz pretpostavku da se $\triangle ABC$ javlja kao noseći (slika 3), sile u osloncima F_A i F_C imaju maksimalne vrednosti za položaj strele u pravcu dijagonale AC:

$$F_{A\max} = \frac{F_{nd} + F_0}{2} + F_0 \frac{e}{\sqrt{r^2 + s^2}} \quad \dots\dots(1)$$

dok će za položaj strele u pravcu normalnom na AC sila u osloncu F_B imati maksimalnu vrednost:

$$F_{B\max} = F_0 \frac{e}{rs} \sqrt{r^2 + s^2} \quad \dots\dots(2)$$

Bolju i detaljniju analizu izvršio je Herrnbrod [16], a zatim tako dobijene eksperimentalne rezultate uporedio sa rezultatima približnih metoda. Naime na taj način je ukazao na jednostavno formiranje dijagrama promene F_A/F_0 u polarnim koordinatama u funkciji ugla okretanja strele φ oko tačke okretanja O, pri čemu je sila F_A prikazana u obliku :

$$F_A = c + a \sin \varphi + b \cos \varphi = r_1 + r_2 \quad \dots\dots(3)$$

ili grafički u vidu dve kružnice sa centrom u O. Maksimalna vrednost sile F_A je pri položaju strele u pravcu normalnom na dijagonalu BD. Na grafiku (slika 4) date su krive promene opterećenja dobijene različitim metodama, kao i za slučajeve oslanjanja u tri tačke.

Slika 4. Polarni dijagram promene opterećenja u osloncima u funkciji ugla okretanja
a- sila F_A (Montagnon); b- sila F_A (Andre); c1- sila F_A pri oslanjanju u tri tačke ($\triangle ACD$); c2- sila F_A pri oslanjanju u tri tačke ($\triangle ABC$); d- sila F_B pri oslanjanju u tri tačke ($\triangle ABC$);

U daljoj eksploataciji, a u cilju obezbeđivanja potrebne krutosti oslone površine usavršavana su postojeća rešenja sa krutom vezom cilindričnog nosača tj. konstrukcije nosača ležaja i podužnih nosača guseničnog sklopa. U cilju poboljšanja rešenja proizvođači bagera su vršili optimizaciju geometrije poprečnog preseka konstrukcije nosača ležaja, kao i promenu odnosa njegove savojne i torzione krutosti [7, 8, 9, 10].

I pored optimizacije odnosa geometrijskih veličina elemenata noseće strukture i ugradnje cilindričnog nosača, kao posrednog elementa između ležaja i nosećeg rama problem nije u potpunosti rešen odnosno oslona površina radialno-aksijalnih ležajeva i dalje nema potrebnu krutost. Ovaj problem je razlog za pronalaženje novog rešenja koje će omogućiti praćenje neravnina u toku kretanja bagera čime će se ujedno vršiti rasterećenje konstrukcije [11, 12, 13]. Pored pažljivog pretraživanja dostupne patentne dokumentacije i sagledavanjem rešenja svih relevantnih svetskih proizvođača bagera nije pronađeno nijedno rešenje sa zglobovima koje će omogućiti praćenje neravnina u toku kretanja bagera.

2. KONCEPT LABORATORIJSKOG POSTROJENJA ZGLOBNE VEZE

Torziono rasterećenje noseće konstrukcije donjeg stroja bagera, koje u velikoj meri rešava problem deplanacije oslone površine radijalno-aksijalnog ležaja, bazirano je na konceptu novog načina oslanjanja hodnog stroja. Formiranjem teorijskog proračunskog modela noseće konstrukcije ležaja, sproveden je određeni stepen redukcije uticajnih parametara i uspostavljene su teorijske zavisnosti odgovarajućih geometrijskih karakteristika noseće konstrukcije. Tako je, bez narušavanja opštosti razmatranog problema stvorena baza za istraživanje i razvoj nove koncepcije veze okretne i neokretne konstrukcije. Potvrda definisanih teorijskih zavisnosti od značaja za kvalitet veze, izvršena je eksperimentalnom verifikacijom na fizičkom modelu noseće konstrukcije bagera [14, 15].

Univerzalni element zglobne veze za torziono rasterećenje noseće konstrukcije hodnog stroja bagera sastoji se od glavnog centralnog i dva pomoćna zgloba (slika 5). Zglobovi su postavljeni na jedan nosač gusenice. Može se postaviti na levi ili desni po izboru. Centralni zglob je postavljen u središnjem delu sandučastog nosača gusenice i omogućava prijem vertikalnog opterećenja. Montira se ubacivanjem sa bočne strane sandučastog nosača gusenice. Vertikalno oslanjanje na sandučasti nosač gusenice ostvaruje se preko jednog para svornjaka (gornji i donji) koji su spojeni sa prstenom zavarenim za gornju, odnosno donju ploču sandučastog nosača gusenice. Centralni zglob omogućava obrtanje sandučastog nosača u vertikalnoj ravni - u oba smera, odnosno, omogućava maksimalno prilagođavanje nepravilnostima terena. Ovo obrtanje dovodi do torzionog rasterećenja noseće konstrukcije donjeg stroja bagera, što rešava problem deplanacije oslone površi radijalno-aksijalnog ležaja.

Pomoćni zglobovi omogućavaju obrtanje sandučastog nosača u vertikalnoj ravni - u oba smera do zadatog ugla a preko njih je ujedno i ostvareno vođenje u vertikalnoj ravni.

Zadavanje ugla obrtanja definiše se položajem postavljenih graničnika. Istovremeno, navedenim elementima se sprečava okretanje sandučastog nosača oko vertikalne ose (u horizontalnoj ravni) prilikom promene pravca kretanja bagera.

Novost se ogleda u podizanju kvaliteta veze okretnog i neokretnog dela mašina građevinske i transportne mehanizacije povezanih sa radijalno-aksijalnim ležajevima velikih prečnika [16, 17]. Takođe, predstavljeno postrojenje ima i sledeće prednosti u odnosu na postojeća tehnička rešenja:

- sprečavanje pojave deplanacije oslone površine za vezu ležaja,
- povećanje pouzdanosti i veka trajanja radijalno-aksijalnog ležaja,
- povećanje pouzdanosti i veka trajanja konstrukcije nosača radijalno-aksijalnog ležaja i
- poboljšanje efikasnosti u radu bagera i drugih mašina građevinske i transportne mehanizacije.

2.1 Detaljan opis tehničkog rešenja zglobne veze za torziono rasterećenje

Noseća konstrukcija hodnog stroja se sastoji iz centralnog zavarenog nosača 1, čiji je sastavni element osloni prsten za vezu sa radijalno-aksijalnim ležajem 2. Za centralni nosač 1 je sa jedne strane zavaren fiksni sandučasti nosač gusenica 3, dok je sa druge strane, posredstvom oslone ploče i centralnog zgloba, ostvarena demontažna veza sa drugim nosačem gusenica 4, koji je okretan u vertikalnoj ravni. Konstrukciono rešenje centralnog zgloba, kojim se postiže prilagodljivost noseće strukture hodnog stroja neravninama terena, prikazano je presekom na slici 5.

Sandučasti nosač gusenica, koji se sastoji od gornjeg (1) i donjeg (2) pojasnog lima i spoljnog (3) i unutrašnjeg (4) rebra, je istovremeno okretan oko svoje horizontalne i vertikalne ose.

Slika. 5 Izometrijski pogled i poprečni presek noseće konstrukcije hodnog stroja bagera sa univerzalnim elementom zglobne veze [16]

Univerzalni element zglobne veze za toziona rasterećenje noseće konstrukcije hodnog stroja bagera, sastoji se od centralnog zgloba (5), koji čini glavčina (20), smeštena u centralnom delu, sa čije gornje i donje strane se oslanjaju svornjaci (12), preko ležajeva (19), a koja se preko dva ležaja (32), oslanja na centralni svornjak (26), koji je okretan oko horizontalne ose (23). Na taj način omogućeno je zakretanje okretnog guseničnog nosača (4) u odnosu na noseću ploču (24), koja je oslonjena na centralni svornjak (26) preko radijalne površine (28), pri čemu su noseća ploča (24) i centralni svornjak (26) spojeni pomoću zavrtnjeva (29). Glavčina (20), preko svornjaka (12) i ležajevima (13) je spojena sa prstenima (11), koji su zavareni za gornji pojasni lim (7) i donji pojasni lim (8) i tako čini celinu sa okretnim guseničnim nosačem (4).

Slika 6. Svornjak

Slika 7. Centralni svornjak

Slika 8. Glavčina

Slika 9. Noseća ploča

U sklopu pomoćnog zgloba (6) (slika 10), nalazi se osovinica (47), zavarena za unutrašnje (10) i spoljašnje rebro (9), i na taj način omogućava njeno kretanje po žljebu (46), noseće ploče (24), ograničeno u prostoru. Ograničenje definišu zub ploče (48) i graničnik (49), Priteznom pločicom (51) uz pomoć navrtke (52), omogućena je ograničena rotacija okretnog guseničnog nosača (4) oko noseće ploče (24).

Slika 10. Pomoćni zglob [15]

Slika 11. Poprečni presek pomoćnog zgloba

Slika 12. Osovinica

Slika 14. Centralni i pomoćni zglob laboratorijskog postrojenja zglobne veze [17]

2.2 Izvedeno tehničko rešenje zglobne veze za torziono rasterećenje

Novo rešenje zglobne veze za torziono rasterećenje bi znatno podiglo kvalitet veze okretnog i neokretnog dela mašina transportne i građevinske mehanizacije povezanih sa radijalno-aksijalnim ležajevima velikih prečnika [16]. Drugim rečima, ovakvo konceptijsko rešenje sprečava pojavu deplanacije oslone površine za vezu ležaja čime se znatno povećava njegova pouzdanost, vek trajanja konstrukcije kao i efikasnost u radu. Takođe proizvođači ležajeva velikih prečnika bi mogli da definišu nove uslove ugradnje, garantujući pri tome duži vek trajanja pri čemu ukoliko potencijalni korisnici budu prepoznali sve prednosti ovih rezultata, moguće je i korišćenje ovog rešenja i u serijskoj proizvodnji.

Slika 13. Laboratorijsko postrojenje zglobne veze [17]

3. ZAKLJUČAK

Posebna pažnja u okviru ovog rada usmerena je predstavljanju rezultata razvoja i usavršavanja okretnih i neokretnih veza mašina građevinske i transportne mehanizacije tj. ispravnog funkcionisanja veze okretnog i neokretnog dela preko radijalno-aksijalnog ležaja velikih prečnika.

Istraživanje i razvoj novog konceptijskog rešenja veze okretne i neokretne konstrukcije mašina bazirano je na analizi torziona krutosti različitih varijantnih rešenja i formiranje teorijskog proračunskog modela noseće konstrukcije ležaja. Na osnovu teorijske zavisnosti odgovarajućih geometrijskih karakteristika noseće konstrukcije i uporedne analize veličina pomeranja karakterističnih tačaka oslonih površina određen je uticaj ugradnje cilindričnog nosača na smanjenje deplanacije i pomeranja tačaka oslone površine za vezu radijalno-aksijalnog ležaja. Ustanovljeno je da ugrađenim cilindričnim nosačem nije moguće uvek ostvariti pomeranja koja su manja od dozvoljenih, a delimično se i smanjuje stabilnost bagera pri radu.

Razvijeno rešenje sprečava pojavu deplanacije oslone površine za vezu ležaja čime se znatno povećava njegova pouzdanost, vek trajanja konstrukcije kao i efikasnost u radu.

Laka montaža sklopljenih elemenata ležišta i povećana stabilnost cele konstrukcije uz sopstvene granične parametre, omogućavaju prednost u odnosu na druge načine oslanjanja, a samim tim i opravdanu dalju analizu i usavršavanje novog rešenja.

Opravdanost analize i istraživanja u cilju povećanja veka trajanja i sigurnosti u radu navedenih mašina je utoliko veća ukoliko se imaju uvidu i problemi pri prenošenju opterećenja sa okretnih na neokretne delove nosećih konstrukcija mašina građevinske i transportne mehanizacije.

4. ZAHVALNOST

Ovaj rad je rezultat projekta broj TR35038 koji je finansiran od strane Ministarstva prosvete, nauke i tehnološkog razvoja Republike Srbije.

LITERATURA

- [1] Jevtić, D., Gašić, M.: The influence of relation between elements geometric dimensions of a dredger supporting structure and the connection with the rotating platform, International conference on engineering design, IECD, Dubrovnik, 1990, pp. 23-43.
- [2] Gašić, M., Marković, G., Savković, M.: Prilog razvoju novog rešenja veze okretnog i neokretnog dela mašina građevinske i transportne mehanizacije, IMK 14 Istraživanje i razvoj, 2005, (20-21), 1-2/2005, str. 71-75.
- [3] Gašić, M., Savković M., Marković G., Zdravković, N.: Analiza metoda proračuna prstenova portalnog kрана i bagera guseničara, IMK-14 – Istraživanje i razvoj, (30-31) 1-2/2009, str. 37-41.
- [4] Milomir Gašić, Mile Savković, Goran Marković, Nebojša Zdravković: Geometric Identification of Carryng Frame of Radial-axial Bearing at Hydraulic Excavators, IMK14 - Reasearch&Developement in Heavy Machinery, Vol. 20, No 2, 47-53, 2014.
- [5] Scheffler M., Pajer G., Kurt F.: Grundlagen der Fördertechnik, VEB Verlag Technik, Berlin 1964.
- [6] Herrnbrodt H.: Über die Raddrücke von fahrbaren Drehkranen, Fördertechnik 33, (1940) 21-26.
- [7] Amasorrain, J.I., Sagartzazu, X., Damian, J.: Load distribution in a four contact-point slewing bearing, Mechanism and Machine Theory, 2003, Vol 38, No. 4, pp. 399-412.
- [8] Zupan, S., Prebil, I.: Carrying angle and carrying capacity of a large single row ball bearings as a function of geometry parametars of rolling contact and the supporting structure stiffness, Mechanism and Machine Theory, 2001, Vol 36, No. 4, pp. 399-412.
- [9] Smolnicki, T. Rusinski, E. (2007). Superelement-Based Modeling of Load Distribution in Large-Size Slewing Bearings. Journal of Mmechanical Design, vol no. 129, p. 459-463.
- [10] Kania, L. (2006). Modeling of rollers in calculation of slewing bearing with the use of finite elements, Mechanism and Machine Theory. vol. no. 41, pp.1359-1376.
- [11] Gašić, M., Karamarković, V., Savković, M., Marković, G.: Research and development of new solution to the connection of excavator carrying construction, International Conference -Heavy Machinery HM 2002, Kraljevo, 2002. pp. A3÷A5.
- [12] Janošević, D.: Izbor aksijalnog ležaja pogona obrtne platforme hidrauličkih bagera, IMK 14 Istraživanje i razvoj, 2003, Vol. 16, 26-27, str. 143-149.
- [13] Gašić M., Savković M., Marković G., Zdravković N.: Research and development of carrying structure of radial – axial bearing of construction and transport mechanization machines, KOD 2010 - The 6th International Symposium, pp.41-48, Palić, 2010.
- [14] Gašić M., Savković M., Marković G., Zdravković N.: Analysis of Carrying Structure Influential Parameters on Bond Function of Revolving and Non-Revolving Parts, 11th International Conference Research and Development in Mechanical Industry - RaDMI 2011, Volume 1, pp. 167-173, Soko Banja, 2011,
- [15] Milomir Gašić, Mile Savković, Goran Marković, Nebojša Zdravković: Geometric Identification of Carryng Frame of Radial-axial Bearing at Hydraulic Excavators, IMK14 - Reasearch&Developement in Heavy Machinery, Vol. 20, No 2, 47-53, 2014.
- [16] Gašić, M., Savković, M., Marković G., Zdravković N.: Zglobna veza za torziona rasterećenje konstrukcije hodnog stroja bagera, Fakultet za mašinstvo i građevinarstvo u Kraljevu, IMK 14. oktobar u restruktuiranju-Kruševac, Prototip, 2014.
- [17] Gašić, M., Savković, M., Marković G., Zdravković N.: Laboratorijsko postrojenje za torziona rasterećenje konstrukcije hodnog stroja bagera, Fakultet za mašinstvo i građevinarstvo u Kraljevu, tehničko rešenje, 2015.
- [18] http://www.rotheerde.com/download/info/Rothe_Erd e_GWL_D.pdf

Laboratory Model of the Joint Connection in the Carrying Structure of the Excavator Undercarriage

Milomir Gašić^{1*}, Goran Marković¹, Mile Savković¹, Nebojša Zdravković¹

¹University of Kragujevac, Faculty of Mechanical and Civil Engineering in Kraljevo

The laboratory model presented in this paper covers the formation of a new concept of connection between the revolving and non-revolving parts of transportation and earth-moving machinery. The new concept of connection is oriented toward providing better adaptability to the path along which the machine is moving and improvement of the function of indirect elements made in the form of large diameter bearings (type Rothe Erde) with the increased reliability in operation and speed of operations. The connections between revolving and non-revolving structures of transportation and earth-moving machinery have developed under the influence of different operation and structural requirements. However, the conceptual solutions so far (realized in the shape of "X" and "H" types) do not provide reliable and long operation of indirect elements (large diameter bearings) inserted between the revolving and non-revolving parts. The problem set for the model is a requirement how to structurally provide relief and reliable operation of the indirect element (large diameter bearings) inserted between the revolving and non-revolving parts of the excavator carrying structure. Unlike the existing solutions with a rigid connection, the new solution is based on the joint connection for the purpose of torsional relief of the carrying structure of the excavator undercarriage. The solution is conceived in such a way that, in addition to excavators, it can be applied to other transportation and earth-moving machinery.

Keywords: laboratory model, radial-axial bearing, torsional stiffness, underframe, deplanation

1. INTRODUCTION

It is widely known that it is not possible to realize a full contact between the path and the excavator undercarriage. The problem of realizing contacts can occur, almost as a rule, due to terrain roughness or, more rarely, faults made during manufacturing. As a consequence, during exploitation there occurs lifting or lowering of a machine support, i.e. redistribution of vertical reactions at the supports, which leads to deformations of the carrying structure [1, 2, 3]. The consequence of this phenomenon is the fact that the underframes of the existing solutions of radial-axial bearings cannot completely provide the necessary rigidity of the support surface for the bearing connection and, therefore, normal functioning of the connection between the revolving and non-revolving parts in such machines (Figure 1).

Figure 1. Elements of connections between the revolving and non-revolving parts by means of large diameter bearings [4]

Starting from a wide application of such a type of support and the problems which appear in transferring loads from revolving to non-revolving parts of the carrying structures of transportation and earth-moving machinery, the analysis and research for the purpose of increasing the life and safe operation of the mentioned machinery are imposed as an imperative. The solutions of the connection have been improved in the course of time by inserting a mid-element – cylindrical carrier, for the purpose of reducing deplanation of the support surface of the large diameter radial-axial bearing [4].

Normal functioning of transportation and earth-moving machinery, with revolving and non-revolving parts, depends on the parameters influencing the value of pressure at the supports. In other words, the results of research into the transfer of loads from the revolving part to the connection with the non-revolving part should define the parameters influencing the proper functioning of the mentioned connection.

Figure 2. Zone of action of the resultant with the support at four and three points

Generally, the existing solutions of the carrying structures of transportation and earth-moving machinery are such that deformations are mostly received by the support structure of large diameter bearings (support plate, carriers to which the plate is connected and the rigid ring).

The statically determined scheme of support at three points is mainly applied in high-productivity mining machines, modern portal cranes with horizontal displacement of loads and some jib cranes. The support at four points is applied in all other cases. The reason for larger application of the statically indefinite scheme of support at four points lies in the fact that the resultant of vertical forces can be distributed in a wider zone than with the support at three points with the same width of support. This is obviously seen in a comparative scheme of machines with a revolving part (Figure 2) [5]. With the support at four points, the forces at the supports depend on the state of the support surface (roughness and deformations) as well as on the structural solution and elasticity of the undercarriage of machines.

Figure 3. Zone of action of the resultant with the support at four and three points

So, if deformations of the base or faults in manufacturing and mounting of tracks occur, the support rectangle can be divided into two triangles (Fig. 3). If the resultant passes through one of the two triangles, e.g. $\triangle ABC$, the opposite support D, of the unloaded triangle $\triangle ACD$, detaches from the base or the track. By further rotation of the upper part of the machine, the resultant moves and the machine overturns around AC, and in that case the support is accomplished through $\triangle ACD$, i.e. the support B detaches from the base or the track.

All this shows that it is necessary to eliminate such an undesired effect, i.e. achieve uniform support on all wheels. The analysis of this problem with the influence of the previously stated phenomena is comprehensive because it also requires the introduction of parameters of the revolving parts (undercarriage) and the path along which the machine moves. The evaluation and influence of roughness of the path are often connected with certain difficulties, so that approximate methods of calculation are used [6]. In accordance with the equilibrium equations and with the assumption that $\triangle ABC$ appears as the carrying one (Fig. 3), the forces at the supports F_A and F_C will have maximum values for the position of the boom in the direction of the diagonal AC:

$$F_{A \max} = \frac{F_{nd} + F_0}{2} + F_0 \frac{e}{\sqrt{r^2 + s^2}} \quad \text{.....(1)}$$

whereas for the boom position in the direction normal to AC, the force at the support FB will have the maximum value:

$$F_{B \max} = F_0 \frac{e}{rs} \sqrt{r^2 + s^2} \quad \text{.....(2)}$$

A better and more detailed analysis was performed by Herrnbrodt [16], and then he compared the obtained experimental results with the results of approximate methods. Namely, in that way he pointed to simple formation of the diagram F_A/F_0 in polar coordinates as a function of the angle of rotation of the boom ϕ around the point of rotation O, where the force F_A is presented in the form:

$$F_A = c + a \sin \phi + b \cos \phi = r_1 + r_2 \quad \text{.....(3)}$$

or graphically in the form of two circle lines with the centre at O. The maximum value of the force F_A is at the boom position in the direction normal to the diagonal BD. The graph (Fig. 4) shows the curves of change of loads obtained by the different methods, as well as for the cases of support at three points.

Figure 4. Polar diagram of the change of loads at the supports as a function of the angle of rotation
a- force F_A according to Montagnon; b- force F_A according to Andre; c₁-force F_A with the support at three points ($\triangle ACD$); c₂-force F_A with the support at three points ($\triangle ABC$); d-force F_B with the support at three points ($\triangle ABC$);

In further exploitation, and for the purpose of providing the necessary rigidity of the support surface, the existing solutions with the rigid connection of the cylindrical carrier, i.e. the bearing support structure and the longitudinal carriers of the caterpillar assembly have been improved. In order to improve the solutions, the manufacturers of excavators have performed optimization of the geometry of the cross section of the bearing support structure and changed the relationship between its bending and torsional stiffness [7, 8, 9, 10].

Despite the optimization of the relationship between geometrical values of the carrying structure elements and installation of a cylindrical carrier, as an indirect element between the bearing and the underframe, the problem has not been entirely solved, i.e. the support surface of radial-axial bearings still do not have the necessary rigidity. This problem is the reason for finding a new solution that will allow tracking of roughness while the excavator is moving, which will at the same time relieve the structure [11, 12, 13].

In spite of careful searching through the available patent documentation and considering solutions made by all relevant world manufacturers of excavators, no solution with a joint which will allow tracking of roughness while the excavator is moving has been found.

2. CONCEPT OF THE LABORATORY MODEL OF THE JOINT CONNECTION

Torsional relief of the carrying structure of the excavator undercarriage, which significantly solves the problem of deplanation of the support surface of the radial-axial bearing, is based on the concept of the new way of support of the undercarriage. Formation of the theoretical calculation method for the carrying structure of the bearing allowed a certain degree of reduction of influential parameters and establishing of theoretical dependencies of the corresponding geometrical characteristics of the carrying structure. Without disturbing the generality of the considered problem, it resulted in the creation of a database for research and development of a new concept of connection between the revolving and non-revolving structures. Verification of the defined theoretical dependencies significant for the quality of connection was done experimentally, on a physical model of the excavator carrying structure [14, 15].

The universal element of the joint connection for torsional relief of the carrying structure of the excavator undercarriage consists of the main central joint and two auxiliary joints (Figure 5). The joints are placed on one caterpillar carrier. They can be installed either on the left one or the right one.

The central joint is placed in the central part of the box girder of the caterpillar and it allows the reception of vertical load. It is installed from the lateral side of the box girder of the caterpillar. Vertical support on the box girder of the caterpillar is realized through a pair of bolts (upper and lower) which are connected to a ring welded to the upper or lower plate of the box girder of the caterpillar. The central joint allows rotation of the box girder in the vertical plane – in both directions, that is, it allows maximum adjustment to terrain roughness. This rotation leads to torsional relief of the carrying structure of the excavator undercarriage, which solves the problem of deplanation of the support surface of the radial-axial bearing.

The auxiliary joints allow rotation of the box girder in the vertical plane – in both directions up to the prescribed angle as well as guidance in the vertical plane.

Prescribing of the angle of rotation is defined by the position of the installed limiters. Simultaneously, the mentioned elements prevent the rotation of the box girder around the vertical axis (in the horizontal plane) during the change of direction of motion of the excavator.

The novelty is seen in the increased quality of the connection between revolving and non-revolving parts of transportation and earth-moving machinery which are connected to radial-axial large diameter bearings [16, 17]. Also, the presented model has the following advantages over the existing technical solutions:

- prevention of the appearance of deplanation of the support surface for the bearing connection,
- increased reliability and life of the radial-axial bearing,
- increased reliability and life of the radial-axial bearing support structure, and
- improved efficiency in the operation of excavators and other transportation and earth-moving machinery.

2.1 Detailed description of the technical solution of the joint connection for torsional relief

The carrying structure of the undercarriage consists of the central welded carrier 1, whose constituent element is the support ring for the connection with the radial-axial bearing 2. As for the central carrier 1, on one end it has a welded fixed box girder of the caterpillars 3, while on the other end the support plate and the central joint serve for the removable connection with the other carrier of the caterpillars 4, which rotates in the vertical plane.

The structural solution of the central joint, which accomplishes the adaptability of the carrying structure of the undercarriage to terrain roughness, is shown by the cross section in Figure 5.

The box girder of the caterpillars, which consists of the upper (1) and lower (2) web plate and the external (3) and internal (4) webs, can simultaneously rotate around its horizontal and vertical axes.

The universal element of the joint connection for torsional relief of the carrying structure of the excavator undercarriage consists of the central joint (5) made of a hub (20), which is placed in the central part.

On its upper and lower sides, it provides support to the bolts (12), through the bearings (19), and by means of two bearings (32) it leans on the central bolt (26), which can rotate around its horizontal axis (23). It thus allows turning of the rotary caterpillar carrier (4) in relation to the carrying plate (24), which is supported on the central bolt (26) by means of the radial surface (28), where the carrying plate (24) and the central bolt (26) are joined by the screws (29).

The hub (20) is connected, through the bolt (12) and the bearings (13), with the rings (11), which are welded to the upper web plate (7) and the lower web plate (8) and thus make a whole with the rotary caterpillar carrier (4).

Figure 5. Isometric view and the cross section of the carrying structure of the excavator undercarriage with the universal element of the joint connection [16]

Figure 6. Bolt

Figure 8. Hub

Figure 7. Central bolt

Figure 9. Carrying plate

Within the assembly of the auxiliary joint (6) (Figure 10), there is a pin (47) welded to the inner (10) and outer webs (9), which thus allows its motion along the groove (46) of the carrying plate (24), restricted in the space. The restriction is defined by the tooth of the plate (48) and the limiter (49). The pressure plate (51), together with the nut (52), allows restricted rotation of the rotary caterpillar carrier (4) around the carrying plate (24).

Figure 10. Auxiliary joint [15]

Figure 11. Cross section of the auxiliary joint

Figure 12. Pin

2.2 Realized technical solution of the joint connection for torsional relief

The new solution of the joint connection for torsional relief would considerably increase the quality of connection between the revolving and non-revolving parts of transportation and earth-moving machinery connected by radial-axial large diameter bearings [16].

In other words, such a conceptual solution prevents the occurrence of deplanation of the support surface for the bearing connection, which considerably increases its reliability, life of the structure and efficiency in operation. Also, the manufacturers of large diameter bearings could define new conditions of installation, guaranteeing a longer life, when, if potential users recognize all advantages of these results, it will be possible to use this solution in serial production.

Figure 13. Laboratory installation of the joint connection [17]

Figure 14. Central and auxiliary joints of the laboratory model of the joint connection [17]

3.CONCLUSION

Special attention within this paper is directed toward the presentation of results of development and improvement of revolving and non-revolving connections in transportation and earth-moving machinery, i.e. proper functioning of the connection between the revolving and non-revolving parts by the large diameter radial-axial bearing.

Research and development of the new conceptual solution of the connection between the revolving and non-revolving structures of machines is based on the analysis of torsional stiffness of various variant solutions and formation of the theoretical calculation model of the bearing support structure. The influence of installation of the cylindrical carrier on the reduction of deplanation and displacements of points of the support surface for the connection of the radial-axial bearing has been defined based on the theoretical dependency of the corresponding geometrical characteristics of the carrying structure and the comparative analysis of the values of displacements of characteristic points of the support surfaces. It has been established that the installed cylindrical carrier does not always produce displacements which are smaller than the allowed ones, and the stability of the excavator in operation is partly reduced, too.

The solution developed prevents the appearance of deplanation of the support surface for the bearing connection, which considerably increases its reliability, the life of the structure and the efficiency in operation.

Easy mounting of the assembled elements of the bearing and the increased stability of the whole structure with its own boundary parameters provide an advantage over the other manners of support and, therefore, justify further analysis and improvement of the new solution.

Justification of analysis and research for the purpose of increasing the life of the mentioned machines and their safety in operation is even greater if the problems of transferring loads from revolving and non-revolving parts of carrying structures of transportation and earth-moving machinery are taken into account.

ACKNOWLEDGEMENT

This paper is the result of the project number TR35038 financed by the Ministry of Education, Science and Technological Development of the Republic of Serbia.

REFERENCES

- [1] Jevtić, D., Gašić, M.: The influence of relation between elements geometric dimensions of a dredger supporting structure and the connection with the rotating platform, International Conference on Engineering Design, IECD, Dubrovnik, 1990, pp. 23-43.
- [2] Gašić, M., Marković, G., Savković, M.: Prilog razvoju novog rešenja veze okretnog i neokretnog dela mašina građevinske i transportne mehanizacije, IMK 14 Istraživanje i razvoj, 2005, (20-21), 1-2/2005, str. 71-75.
- [3] Gašić, M., Savković M., Marković G., Zdravković, N.: Analiza metoda proračuna prstenova portalnog kрана i bagera guseničara, IMK-14 – Istraživanje i razvoj, (30-31) 1-2/2009, str. 37-41.
- [4] Milomir Gašić, Mile Savković, Goran Marković, Nebojša Zdravković: Geometric Identification of Carryng Frame of Radial-Axial Bearing at Hydraulic Excavators, IMK14 - Reasearch&Developement in Heavy Machinery, Vol. 20, No 2, 47-53, 2014.
- [5] Scheffler M., Pajer G., Kurt F.: Grundlagen der Fördertechnik, VEB Verlag Technik, Berlin 1964.
- [6] Herrnbrodt H.: Über die Raddrucke von fahrbaren Drehkränen, Fördertechnik 33, (1940) 21-26.
- [7] Amasorrain, J.I., Sagartzazu, X., Damian, J.: Load distribution in a four contact-point slewing bearing, Mechanism and Machine Theory, 2003, Vol 38, No. 4, pp. 399-412.
- [8] Zupan, S., Prebil, I.: Carrying angle and carrying capacity of a large single row ball bearings as a function of geometry parameters of rolling contact and the supporting structure stiffness, Mechanism and Machine Theory, 2001, Vol 36, No. 4, pp. 399-412.
- [9] Smolnicki, T. Rusinski, E. (2007). Superelement-Based Modeling of Load Distribution in Large-Size Slewing Bearings. Journal of Mmechanical Design, vol no. 129, p. 459-463.
- [10] Kania, L. (2006). Modeling of rollers in calculation of slewing bearing with the use of finite elements, Mechanism and Machine Theory. vol. no. 41, pp. 1359-1376.
- [11] Gašić, M., Karamarković, V., Savković, M., Marković, G.: Research and development of new solution to the connection of excavator carrying construction, International Conference -Heavy Machinery HM 2002, Kraljevo, 2002. pp. A3÷A5.
- [12] Janošević, D.: Izbor aksijalnog ležaja pogona obrtne platforme hidrauličkih bagera, IMK 14 Istraživanje i razvoj, 2003, Vol. 16, 26-27, str. 143-149.
- [13] Gašić M., Savković M., Marković G., Zdravković N.: Research and development of carrying structure of radial – axial bearing of construction and transport mechanization machines, KOD 2010 - The 6th International Symposium, pp. 41-48, Palić, 2010.
- [14] Gašić M., Savković M., Marković G., Zdravković N.: Analysis of Carrying Structure Influential Parameters on Bond Function of Revolving and Non-Revolving Parts, 11th International Conference Research and Development in Mechanical Industry - RaDMI 2011, Volume 1, pp. 167-173, Soko Banja, 2011,
- [15] Milomir Gašić, Mile Savković, Goran Marković, Nebojša Zdravković: Geometric Identification of Carryng Frame of Radial-axial Bearing at Hydraulic Excavators, IMK14 - Reasearch&Developement in Heavy Machinery, Vol. 20, No 2, 47-53, 2014.
- [16] Gašić, M., Savković, M., Marković G., Zdravković N.: Zglobna veza za torziona rasterećenje konstrukcije hodnog stroja bagera, Fakultet za mašinstvo i građevinarstvo u Kraljevu, IMK 14. oktobar u restruktuiranju-Kruševac, Prototip, 2014.
- [17] Gašić, M., Savković, M., Marković G., Zdravković N.: Laboratorijsko postrojenje za torziona rasterećenje konstrukcije hodnog stroja bagera, Fakultet za mašinstvo i građevinarstvo u Kraljevu, tehničko rešenje, 2015.
- [18] http://www.rotheerde.com/download/info/Rothe_Erd e_GWL_D.pdf