Pregled dinamičkih i matematičkih modela portalnih obrtnih dizalica

Goran Bošković^{1*}, Goran Marković¹, Mile Savković¹, Nebojša Zdravković¹

¹Fakultet za mašinstvo i građevinarstvo, Univerzitet u Kragujevcu, Kraljevo (Srbija)

Ovaj rad predstavlja pregled dosadašnjih istraživanja u oblasti dinamike obrtnih dizalica. Akcenat je stavljen na portalne obrtne dizalice ali zbog nedostatka literature iz ove oblasti u obzir su uzeti i tipovi dizalica čiji se dinamički i matematički modeli mogu primeniti na pomenuti tip dizalica. Na kraju rada dat je i predlog daljih istraživanja.

Ključne reči: Portalna obrtna dizalica, Dinamički model, Matematički model

1. UVOD

Ubrzani razvoj vodenog saobraćaja (morski i rečni), kao i povećani promet robe, usloveli su razvoj novih rešenja dizaličnih mašina za manipulaciju u lukama i pristaništima. Najčešće korišćeni tip dizalica za operacije utovara-istovara u lukama i pristaništima su portalne dizalice (okretne i neokretne). Obrtne portalne dizalice predstavljaju dizaličnu mašinu sastavljenu iz obrtne platforme sa strelom koja se može okretati za 360° i noseće konstrukcije koja se može kretati pravolinijski po šinama. Portalnu dizalicu čine i odgovarajući mehanizmi: mehanizam za kretanje dizalice, mehanizam za podizanje i spuštanje tereta sa pripadajućim užetnim sistemom, mehanizam za promenu dohvata strele i mehanizam za obrtanje platforme [1-3].

Jedna od opštih podela portalnih dizalica prikazana je na Sl.1. Ovaj tip dizalica se koristi za transport komadnog i rasutog tereta. Detaljne karakteristike jedne portalne okretne

dizalice (nosivost dizalice, dimenzije, brzine kretanja i ubrzanje) prikazane su u radu [4]. Prilikom operacija sa dizalicom, javljaju se česta ubrzavanja i usporjenja (kočenja) mehanizama što prouzrokuje različite dinamičke efekte [5]. Prilikom projektovanja i proračuna performansi i konstrukcije ovih dizalica, pored statičkih opterećenja, javljaju se i dinamička opterećenja koja se manifestuju u obliku promene brzine mehanizma za dizanje i spuštanje, inercijalnih sila usled kretanja tereta iz stanja mirovanja, pojava oscilovanja (klačenja) tereta usled obrtnog kretanja platforme i uticaja sile vetra. Navedeni dinamički efekti u značajnoj meri utiču na samu noseću konstrukciju dizalice i samog rukovaoca dizalice i predstavljaju bitne faktore za adekvatan proračun i optimizaciju poprečnih preseka elemenata noseće konstrukcije. Treba napomenuti da se u toku rada sa dizalicom mogu pojaviti rezonantna stanja koja teže oštećenju elemenata - havariji.

Slika 1. Opšta podela portalnih obrtnih dizalica

2. DINAMIČKI I MATEMATIČKI MODELI OBRTNIH DIZALICA

U ovom poglavlju biće predstavljeni i opisani dinamički i matematički modeli portalnih obrtnih dizalica. U nedostatku literature iz pomenute oblasti, u razmatranje će biti uzete i dizalice sličnih konstrukcija čiji se matematički modeli mogu primeniti ili prilagoditi konkretnom rešenju konstrukcije dizalice.

U radovima [6,7] istraživani su parametri koji utiču na dinamičko ponašanje konstrukcije portalne obrtne dizalice velikog kapaciteta prilikom kretanja kao i kod pojave klačenja tereta. Formiran je prostorni dinamički model koji omogućava utvrđivanje pomenutih parametara Sl.2. Korišćenjem metode konačnih elemenata kao i modalne analize određeno je dinamičko ponašanje prostorne konstrukcije dizalice koje zavisi od promene ugla rotacije strele dizalice.

Jednačine koje opisuju kretanje dizalice predstavljene su u obliku:

$$\ddot{\theta}(t) + \omega_l^2 \sin \theta(t) = -\frac{1}{L_r} \ddot{x}(t) \cos \varphi, \quad (1)$$

$$\ddot{\psi}(t) + \omega^2 \sin \psi(t) = -\frac{1}{L_r} \ddot{x}(t) \sin \varphi, \quad (2)$$

$$J\ddot{\phi}(t) = T, \quad (3)$$

gde je: θ ugao oscilovanja tereta u podužnom pravcu, ψ ugao oscilovanja tereta u poprečnom pravcu, φ ugao rotacije strele, x pravolinijsko kretanje strele i ω kružna frekvencija oscilovanja tereta.

Pomoću Laplasove transformacije i Hevisajdove funkcije sa linearnim polinomom, određeni su zakoni promene oscilovanja tereta. Ovi zakoni su od velikog značaja jer nekontrolisano oscilovanje tereta može izazvati havariju same konstrukcije dizalice. Takođe su određena i maksimalna pomeranja karakteristične 4 tačke noseće konstrukcije. Određivanjem velikog broja parametara koji utiču na dinamičko ponašanje dizalice stvorena je i mogućnost za optimizaciju elemenata noseće konstrukcije dizalice.

Slika 2. Dinamički model dizalice [6]

U radu [8] je proučavana dinamička stabilnost portalne obrtne dizalice. Formiran je konačno-elementni (ravanski) model dizalice Sl.3, pomoću kojeg je analizirano

dinamičko ponašanje dizalica sa ciljem određivanja osetljivost delova dizalica kod velikih amplituda oscilacija i dugog perioda usporenja. Elastični oslonci dizalice su modelirani kao opruge, tako da predstavljaju elastičnost podloge. U radu su razmatrani uticaji inercijalnih sila prilikom kretanja elemenata konstrukcije kao i uticaj oscilovanja (klačenja) tereta.

Jednačine koje predstavljaju teorijsku osnovu i opisuju diskretnu dinamičku konstrukciju napisane su u obliku:

$$[M] \cdot \{\ddot{q}\} + [B] \cdot \{\dot{q}\} + [K] \cdot \{q\} = \{R(t)\} \quad (4)$$

gde je: $[M]$ matrica koeficijenata inercije, $[B]$ matrica prigušenja, $[K]$ matrica krutosti konstrukcije, $[R]$ vektor generalisanih opterećenja i $\{q\}$ su generalisane koordinate u čvorovima konstrukcije.

Dobijanjem dinamički osetljivih pozicija elemenata konstrukcije dizalice omogućeno je rešavanje projektantskih problema izbora materijala, poznavanja brzina pri radu i geometrijskih karakteristika dizalice. Izvršena je i uporedna analiza rezultata dobijenih metodom konačnih elemenata i eksperimentalnim putem.

Slika 3. Dinamički model dizalice za analizu konačnim elementima u 12 karakterističnih pozicija [8]

U radu [9] prikazan je višemaseni model okretne dizalice Sl. 4 pomoću kojeg je razmatrano obrtno kretanje dizalice koje proizvodi i prostorno oscilovanje korisnog tereta. U radu su razmatrani sledeći uticaji: otpor vazduha, trenje u glavnom ležaju, prigušenje i elastičnost noseće konstrukcije obrtne dizalice.

Matematički model dizalice predstavljen je Lagranžovim jednačinama druge vrste u kojima figuriše 10 nezavisnih generalisanih koordinata u sledećem obliku:

$$\frac{d}{dt} \left[\frac{\partial T}{\partial \dot{q}_j} \right] - \frac{\partial T}{\partial q_j} + \frac{\partial V}{\partial q_j} = Q_j', \quad j = 1, \dots, s. \quad (5)$$

gde su: T ukupna kinetička energija sistema, Q_j' nekonzervativne generalisane sile, V potencijalna energija sistema i q_j su nezavisne generalisane koordinate.

Ovaj matematički model takođe uzima u obzir i nelinearno kretanje korisnog tereta za veće uglove nagiba i nema nikakvog ograničenja za male uglove klaćenja tereta. Za verifikaciju dobijenih numeričkih rezultata korišćen je umanjeni laboratorijski model okretne dizalice gde je regulacija ulazne brzine obrtanja kontrolisana pomoću frekventnog regulatora. Simulacije su izvršene pomoću opsega težina korisnog tereta ($m_Q = 20 \div 50 \text{ kg}$), radijusa tačke vešanja tereta ($R_0 = 1 \div 2 \text{ m}$) kao i različitih dužina užeta o koje je okačen teret ($L_0 = 0,5 \div 2 \text{ m}$).

Slika 4. Višemaseni model obrtne dizalice [9]

Grafičkim putem, pomoću 16 dijagrama dat je uporedni prikaz rezultata numeričke simulacije zasnovane na matematičkom modelu i rezultata dobijenih merenjem na laboratorijskom modelu dizalice. Na osnovu datih dijagrama može se zaključiti da je došlo do dobrog poklapanja rezultata simulacije i rezultata dobijenih eksperimentalnim putem.

U radu [10] prikazano je dinamičko modeliranje i kontrola kretanja obrtne dizalice korišćenjem samo horizontalnog kretanja strele dizalice. Sa aspekta energetske efikasnosti (uštede energije) dizalice korisnije je koristiti samo horizontalno kretanje strele, gde se pored uštede energije smanjuju i troškovi ugradnje različitih senzora i kontrolera za merenje klaćenja tereta.

Dinamički model prikazan na Sl.5 uključuje samo značajne izraze za centrifugalnu i Koriolisovu silu. Ovaj jednostavni dinamički model obrtne dizalice omogućava analitičko rešavanje diferencijalnih jednačina izvedenih za prikazani model napisanih u sledećem obliku:

$$l(1 + \theta_1^2) \ddot{\theta}_1 + l\theta_1 \ddot{\theta}_2 - l\theta_2 \ddot{\theta}_4 + l\theta_1 \dot{\theta}_1^2 + l\theta_1 \dot{\theta}_2^2 - 2l\dot{\theta}_2 \dot{\theta}_4 - (l\theta_1 + L \sin \theta_3) \ddot{\theta}_4 + g\theta_1 = 0 \quad (6)$$

$$l\theta_1 \ddot{\theta}_2 + l(1 + \theta_2^2) \ddot{\theta}_2 - l\theta_2 \ddot{\theta}_4 + l\theta_2 \dot{\theta}_1^2 + l\theta_2 \dot{\theta}_2^2 + 2l\dot{\theta}_1 \dot{\theta}_4 + (l\theta_1 + L \sin \theta_3) \ddot{\theta}_4 + g\theta_2 = 0 \quad (7)$$

gde su: θ_1 i θ_2 su uglovi klaćenja tereta u ravni vertikalnog kretanja strele i tangencijalni pravac horizontalnog kretanja strele, θ_3 i θ_4 označavaju horizontalne i vertikalne uglove strele, respektivno, a L i l predstavljaju dužine strele i užeta.

Numeričkim rešavanjem algebarskih jednačina može se dobiti trajektorija S-krive koja obuhvata ukidanje zaostalih vibracija bez merenja istih, korišćenjem samo horizontalnog kretanja strele dizalice. Pomoću laboratorijskog modela dizalice izvršena je verifikacija rezultata dobijenih numeričkom simulacijom i eksperimentalnih rezultata dobijenih na umanjenom modelu dizalice.

Uočeno je dobro poklapanje rezultata i utvrđeno da se istim laboratorijskim modelom osim dobijanja trajektorije može dobiti i vreme usporenja dizalice u realnom vremenu što je jedna od ideja za buduća istraživanja.

Slika 5. Šematski prikaz modela obrtne dizalice [10]

U radu [11] predstavljen je dinamički model toranjske (građevinske) dizalice Sl.6 gde se duž obrtne strele dizalice kreću kolica sa okačenim teretom. Dizalica se može modelirati kao sistem koji se sastoji od konzolnog nosača pričvršćenog za obrtni kruti stub i kolica na koja je okačen teret u vidu klatna i koja se kreću duž konzole. Konzolni nosač je modeliran pomoću Ojler-Bernulijeve teorije pod pretpostavkom da se obrtne inercijalne i smičuće deformacije mogu odbaciti.

Koristan teret je modeliran kao klatno SI.7 na čijem kraju se nalazi koncentrisana masa koja je okačena jednim krajem na lako neistegljivo uže a drugim prikačena na kolica koja se kreću duž obrtne strele bez trenja i takođe su predstavljena (modelirana) kao koncentrisana masa.

Slika 6. Konfiguracija elastične strele sa pokretnim opterećenjem [11]

Kretanje obrtne strele opisano je uz pomoć spregnutih jednačina u ravni i van ravni konzole dok su jednačine kretanja korisnog tereta izvedene na osnovu Hamiltonovog principa. U radu su date i napomene u vidu smernica za rešavanje jednačina.

Slika 7. Uglovi oscilovanja tereta [11]

Rad [12] se bavi istraživanjem dinamičkog ponašanja hidraulične obrtne dizalice sa slobodno okačenim teretom koji osciluje tokom obrtanja i podizanja i spuštanja strele dizalice Sl.8. U cilju uprošćenja procedure pomenuta dva kretanja su razmatrana pojedinačno. Dizalica predstavlja kinematski lanac od 3 člana sa rotirajućim zglobovima. Pomoću dva stepena slobode opisano je podizanje i spuštanje tereta dok je sa još jednim dodatnim opisano obrtanje strele dizalice. Za formiranje matematičkog modela dizalice, korišćen je Njutn-Ojlerov algoritam na osnovu kojeg su formirane diferencijalne jednačine drugog reda za problem napredne dinamike.

$$-M(q)\ddot{q}-H(q,\dot{q})+G(q)+\tau(t)=0 \quad (8)$$

gde su: q , $\dot{q}$, $\ddot{q}$ vektori položaja, brzine i ugaonog ubrzanja zglobova; $M(q)$ matrica masa sastavljena od elemenata koji definišu ubrzanje $\ddot{q}$ za svaki zglob, $H(q, \dot{q})$ matrica sastavljena od elemenata koji definišu ubrzanje $\ddot{q}$ za svaki element, $G(q)$ težinski uslovi i $\tau(t)$ je vektor obrtnog momenta za svaki zglob.

Na osnovu simulacije koja bazira na pomenutim jednačinama, određeni su uglovi podizanja i spuštanja strele, hidraulični pritisak u sistemu kao i sile u zglobovima. Postignuto je i dobro poklapanje rezultata dobijenih simulacijom i rezultata dobijenih eksperimentalnim putem.

Slika 8. Denavit-Hartenbergovi parametri za slučaj oscilovanja tereta [12]

Rad [13] razmatra kretanje korisnog tereta predstavljenog klatnom kao i dinamički odziv konstrukcije građevinske toranjske dizalice na Sl.9. Dizalica je modelirana primenom metode konačnih elemenata dok su jednačine kretanja tereta opisane Lagranžovim jednačinama druge vrste uključujući disipativnu funkciju.

Izvršena je analiza dinamike realnog modela dizalice korišćenjem predloženog pristupa i numeričkih metoda za rešavanje jednačina kretanja sistema. Utvrđeno je da dinamički faktori pojačanja rastu sa porastom početnog ugla oscilovanja tereta čije su promene kod kretanja u ravni nelinearne.

Slika 9. Šema geometrije konstrukcije toranjske dizalice sa teretom u vidu klatna [13]

Rad [14] se bavi dinamičkim ponašanjem mobilne građevinske dizalice ne samo sa aspekta noseće konstrukcije i spoljašnjih opterećenja već i pogonskog i kontrolnog sistema SI.10. Razvijena je nova metoda za dinamički proračun mobilnih dizalica koja je zasnovana na sistemu sa više krutih tela koji je spregnut da pogonskim sistemom. Na taj način na osnovu integrisanog modela mogu se odrediti dinamičko ponašanje dizalice, kretanje konstrukcije dizalice kao i dinamičko ponašanje pogonskog sistema.

Kretanje celokupnog sistema je opisano pomoću Lagranžovih jednačina druge vrste. Numerička simulacija sistema sprovedena je uz pomoć ulaznih parametara, zahtevane brzine obrtanja i kontrolnih parametara. Pomoću nove metode mogu se razmatrati razni parametri sistema, a neki od njih su: pritisak ulja, izlazni moment na motoru, protok ulja, kontrola stabilnosti i mnogi drugi parametri značajni za projektovanje dizalice.

Slika 10. Dinamički model dizalice sa koordinatnim sistemom [14]

U radu [15] razmatran je uticaj elastičnosti oslonaca na dinamiku obrtne dizalice SI.11. Matematički model koji se sastoji od četiri kruta tela formiran je korišćenjem Lagranžovih jednačina drugog reda koje su numerički rešene pomoću Njumarkove metode integracije. U cilju dobijanja zahtevane trajektorije i stabilizacije konačne pozicije tereta na kraju kretanja primenjena je dinamička optimizaciona metoda.

Rezultati numeričke simulacije su upoređeni sa rezultatima iz programskog paketa MSC.ADAMS, a takođe i sa rezultatima koji su dobijeni eksperimentalnim putem. Rezultati dinamičke optimizacije mogu se koristiti u cilju formiranja neuronske mreže koja omogućava da pogonske funkcije dizalice budu definisane u realnom vremenu.

Slika 11. Dinamički model dizalice [15]

U radu [16] predstavljena je metoda smanjenja oscilovanja tereta korišćenjem namotavanja i odmotavanja užeta za podizanje. Teret je modeliran kao koncentrisana masa, uža je modelirano kao kruta veza, a sklop predstavlja sferno klatno okačeno na vrh strele. Korišćenjem dvodimenzionalnih i trodimenzionalnih modela opisano je kretanje tereta. Rezultati numeričkih simulacija pokazuju da se promenom dužine užeta može smanjiti klaćenje (oscilovanje) tereta zbog skoro rezonantne pobude.

Lagranžova funkcija koja predstavlja ukupnu energiju sistema može se napisati u sledećem obliku:

$$L = T - V = \frac{1}{2} m \left((\dot{x}_a + \dot{\xi})^2 + (\dot{y}_a + \dot{\zeta})^2 + \dot{z}^2 \right) - mgz \quad (9)$$

gde su: T kinetička energija sistema, V potencijalna energija sistema, dok su (ξ, η, ζ) koordinate položaja tereta u koordinatnom sistemu vezanom za vrh strele na SI.12. Utvrđeno je da se adekvatnim izborom brzina namotavanja i odmotavanja užeta može postići značajno smanjenje oscilovanje tereta.

Slika 12. Koordinatni sistem dizalice [16]

3. ZAKLJUČAK

U radu je dat prikaz matematičkih i dinamičkih modela obrtnih dizalica sa akcentom na portalne obrtne dizalice. Kroz analizu postojećih istraživanja, obrađene su portalne obrtne dizalice, građevinske toranjske dizalice, mobilne građevinske dizalice i hidraulične teleskopske dizalice.

Svi prethodno pomenuti radovi predstavljaju dobru osnovu za dalja istraživanja u oblasti dinamike dizalica koja treba usmeriti na opisivanje sistema pomoću preciznijeg dinamičkog modela koji uzima u obzir veći broj koncentrisanih masa. Pored toga, u budućim istraživanjima treba uzeti u obzir i elastičnost segmenata konstrukcije koja utiče na dalji proračun i dobijene rezultate. Takođe, dalja proučavanja treba usmeriti ka korišćenju savremenih optimizacionih algoritama kojima se može doći do optimalnih vrednosti konstrukcionih parametara dizalica.

4. ZAHVALNOST

Ovaj rad je rezultat projekta broj TR35038 koji je finansiran od strane Ministarstva prosvete, nauke i tehnološkog razvoja Republike Srbije.

5. LITERATURA

- [1] Ostrić D, Tošić S.: "DIZALICE", Mašinski fakultet, Beograd, 2005.
- [2] А. Ланг, И. Мазовер, В. Майзель, "ПОРТАЛЬНЫЕ КРАНЫ – расчёт и конструирование", Государственное научно-техническое издательствомашиностроительной литературы, Москва-Ленинград, 1962.
- [3] Georgijević M.: "DINAMIKA DIZALICA - eksperimentalna i modelska analiza", Zadužbina Andejević, Beograd, 1996.
- [4] B. Visocnik, S. Kravanja: "Slewing Port Jib Cranes", Promet- Traffic- Traffico, Vol.14, 2002, No.5, 251-257
- [5] Rade Vasiljevic, Radovan Bulatovic, Mile Savkovic: "The Approaches to the Mathematical-mechanical Modeling Supporting Construction", IMK-14 – Research & Development in Heavy Machinery, Vol.19, No.1, 2012, EN29-38
- [6] Rade Vasiljević, Milomir Gašić: "The Dynamic Model of the Boom Portal Cranes", IMK-14 – Research & Development in Heavy Machinery, Vol.21, No.4, 2015, EN125-130
- [7] Rade Vasiljević, Milomir Gašić, Mile Savković: "Parameters Influencing the Dynamic Behaviour of the Carrying Structure of a Type H Portal Crane", Strojniški vestnik - Journal of Mechanical Engineering 62(2016)10, 591-602
- [8] Miomir Jovanović, Goran Radoičić, Predrag Milić, "Dynamic Sensitivity Research of Portal-Rotating Cranes", XIX International Conference on "Material Handling, Constructions and Logistics - MHCL 09", Beograd, 15-16 Oktobar 2009, pp. 61-66
- [9] Ivica Marinović, Denijal Sprečić, Boris Jerman, "A Slewing Crane Payload Dynamics", Tehnički vjesnik, Vol.19, No.4, 2002, 907-916.
- [10] Naoki Uchiyama, Huimin Ouyang, Shigenori Sano, "Simple rotary crane dynamics modeling and open-loop control for residual load sway suppression by only horizontal boom motion", Mechatronics, Vol.23, 2013, 1223-1236.
- [11] Wenqing Zang, Zhiyi Zhang, Rongzeng Shen, "Modeling of system dynamics of a slewing flexible beam with moving payload pendulum", Mechanics Research Communications, Vol.34, 2007, 260-266.
- [12] Bozhidar GRIGOROV, Rosen MITREV, "Dynamic behavior of a hydraulic crane operating a freely suspended payload", Journal of Zhejiang University-SCIENCE A (Applied Physics & Engineering), In press, 2016, 22-35.
- [13] F. Ju, Y.S. Choo, F.S. Cui, "Dynamic response of tower crane induced by the pendulum motion of the payload", International Journal of Solids and Structures, Vol.43, 2006, 376-389.
- [14] Guangfu Sun, Michael Kleeberger, "Dynamic responses of hydraulic mobile crane with consideration of the drive system", Mechanism and Machine Theory, Vol.38, No.12, 2003, 1489-1508.
- [15] Andrzej Urbas, Marek Szczotka, Stanislaw Wojciech, "THE INFLUENCE OF FLEXIBILITY OF THE SUPPORT ON DYNAMIC BEHAVIOR OF A CRANE", International Journal of Bifurcation and Chaos, Vol.21, No.10, 2011, 2963-2974.
- [16] E. M. Abdel-Rahman, A. H. Nayfeh, "endulation Reduction in Boom Cranes Using Cable Length Manipulation", Nonlinear Dynamics, Vol.27, 2002, 255-269.

Review of the Dynamic and Mathematical Models of Portal Slewing Cranes

Goran Boskovic^{1*}, Goran Markovic¹, Mile Savkovic¹, Nebojsa Zdravkovic¹

¹ Faculty of Mechanical and Civil Engineering in Kraljevo, University of Kragujevac, Kraljevo (Serbia)

This paper presents an overview of previous research in the field of slewing crane dynamics. Emphasis is placed on the gantry slewing cranes but due to the lack of literature in this field into consideration were taken types of cranes whose dynamic and mathematical models can be applied to the aforementioned type of crane. The plan of further research is given at the end of the paper.

Keywords: Portal slewing crane, Dynamic model, Mathematical model

1. INTRODUCTION

The rapid development of water transport (sea and river), as well as the increased traffic of goods, caused the development of new solutions of crane machines for manipulation in ports and docks. The most commonly used type of cranes for operations of loading and unloading in ports and harbours is portal cranes (slewing and non-slewing). Slewing portal cranes represents crane machine composed of revolving platform with boom which can rotate for 360 degrees and carrying structure that can move in a straight line along the rails. Slewing portal crane is also composed of appropriate mechanisms: mechanism for crane movement, mechanism for raising and lowering the load associated with corresponding rope system, mechanism for changing the reach of the boom and mechanism for the rotation of platform [1-3].

One of the general classification of portal slewing cranes is shown in Fig.1. This type of cranes is used for transport of

piece and bulk cargo. Detailed characteristics of a slewing portal crane (Load capacity, dimensions, speed and acceleration) are shown in the paper [4]. During the operation with crane, acceleration and deceleration (braking) mechanisms occurs frequently what causes different dynamic effects [5]. During the design and performances and construction of this cranes, in addition to static loads, dynamic loads also appear which are manifest in the form of changes of speed of the mechanism for lifting and lowering, inertial forces due to the movement of load from the state of immobility, the occurrence of oscillation (swinging) of the payload due to the rotary motion of platform and the impact of the wind force. Listed dynamic effects significantly influencing on the crane carrying structure and the crane operator, and represent essential factors for an adequate calculation and optimization of cross-sections of the carrying structure elements.

Figure 1: General classification slewing portal cranes

2. THE DYNAMIC AND MATHEMATICAL MODELS OF SLEWING CRANES

In this chapter the dynamic and mathematical models of portal slewing cranes will be presented and described. In the lacking of literature in the aforementioned field, in consideration will be taken cranes of similar construction whose mathematical and dynamical models can be applied or adjusted to concrete solutions of crane structures.

In papers [6,7] are studied the parameters that influence the dynamic behavior of the structure of slewing portal cranes of large capacity during movement as well for the occurrence of swaying load. Spatial dynamical model on Fig.2 that allows the determination of the parameters mentioned above is formed. Using the finite element method and also modal analysis, the dynamic behavior of the spatial structure of the crane that depends on changing the angle of rotation of the crane boom is determined.

The equations that describe the movement of the crane are presented in the form of:

$$\ddot{\theta}(t) + \omega_l^2 \sin \theta(t) = -\frac{1}{L_r} \ddot{x}(t) \cos \phi, \quad (1)$$

$$\ddot{\psi}(t) + \omega^2 \sin \psi(t) = -\frac{1}{L_r} \ddot{x}(t) \sin \phi, \quad (2)$$

$$J\ddot{\phi}(t) = T \quad (3)$$

where: θ is angle of oscillation of payload in the longitudinal direction, ψ is angle of oscillation of payload in the transverse direction, ϕ angle of the boom rotation, x rectilinear motion of the boom and ω circular frequency of oscillation of the load.

Using Laplace transformation and Heaviside functions with linear polynomial, the laws of changes of payload oscillation are determined. These laws are of great importance because uncontrolled oscillations of payload can cause the breakdown of the crane structure. Also, the maximal displacements of characteristic 4 points of the support structure are determined. By determining the large number of parameters that influence on the dynamic behavior of the crane, the possibility to optimize the elements of the support structure of the crane, is created.

Figure 2: Dynamic model of the crane [6]

In the paper [8] the dynamic stability of portal slewing cranes is studied. The finite-element (plane) model of the crane is formed Fig.3, by which the dynamic behavior of the crane was analyzed with the aim of determining the sensitivity of the crane parts for large amplitudes of oscillations and a long period of deceleration. Elastic supports of the crane are modeled as springs, to represent the elasticity of the base. The influence of inertial forces during movement of structural elements and the influence of oscillations (swinging) of the payload are considered in this paper.

The equations that represent the theoretical basis and describe discrete dynamical structure are written in the form:

$$[M] \cdot \{\ddot{q}\} + [B] \cdot \{\dot{q}\} + [K] \cdot \{q\} = \{R(t)\} \quad (4)$$

where: $[M]$ is the inertia coefficients matrix, $[B]$ is the dumping matrix, $[K]$ is the structure stiffness matrix, $\{R\}$ is the generalized loads vector and $\{q\}$ are generalized coordinated in the structure nodes.

By obtaining the dynamically sensitive positions of the crane elements solving the problem of selection of the design material is enabled, knowing the speed of during operation and geometric characteristics of the crane. Comparative analysis of the results obtained by the finite element method and results obtained by the experiment is presented.

Figure 3: Dynamic model of the crane for finite element analysis with 12 characteristic positions [8]

In the paper [9] the multi-mass model of the slewing crane is presented, by which the rotary motion of the crane is considered and which produce as well spatial oscillations of the payload.

The following impacts are considered in this paper: air resistance, friction in the main bearing, damping and elasticity of the support structure of the slewing crane.

The mathematical model of the crane is presented with the Lagrange equations of the second kind in which figure 10 independent generalized coordinates in the following form:

$$\frac{d}{dt} \left[\frac{\partial T}{\partial \dot{q}_j} \right] - \frac{\partial T}{\partial q_j} + \frac{\partial V}{\partial q_j} = Q_j, \quad j = 1, \dots, s. \quad (5)$$

where: T is the total kinetic energy of the system, Q_j are generalized non-conservative forces, V is the potential energy of the system and q_j are independent generalized coordinates.

This mathematical model also takes into account the non-linear movement of the payload for higher angles of inclination and there is no limit for small swinging angles of the payload. For the verification of obtained numerical results scaled laboratory model of slewing crane is used where the regulation of the input speed of rotation is controlled by a frequency converter. The simulations were carried out using a weight ranges of the payload ($m_0 = 20 \div 50 \text{ kg}$), radius of load pivot point ($R_0 = 1 \div 2 \text{ m}$) and as well different lengths of rope that hanging the payload ($L_0 = 0,5 \div 2 \text{ m}$).

Figure 4: Multi-mass model of the slewing crane [9]

Graphically, using 16 diagrams comparison of results of numerical simulation based on a mathematical model and measurement results on a laboratory model of the crane is given. Based on the given diagrams it can be concluded that there is a good overlap of the simulation results and the results obtained by experiment.

In the paper [10] dynamical modeling and control of slewing crane rotation using only horizontal movement of crane boom is presented. From the aspect of energy efficiency (energy savings) of the crane, it is more useful to use only horizontal movement of boom, where except where in addition to energy savings also reduce the costs of installing different sensors and controllers for measuring the swinging load. Dynamic model shown on Fig.5 includes only significant terms of the centrifugal and Coriolis force. This simple dynamic model of the rotating crane provides analytical solving of differential equations derived for the presented model written in the following form:

$$l(1 + \theta_1^2) \ddot{\theta}_1 + l\theta_1\theta_2\ddot{\theta}_2 - l\theta_2\ddot{\theta}_4 + l\theta_1\dot{\theta}_1^2 + l\theta_1\dot{\theta}_2^2 - 2l\dot{\theta}_2\dot{\theta}_4 - (l\theta_1 + L\sin\theta_3)\ddot{\theta}_4 + g\theta_1 = 0 \quad (6)$$

$$l\theta_1\theta_2\ddot{\theta}_1 + l(1 + \theta_2^2) \ddot{\theta}_2 - l\theta_2\ddot{\theta}_4 + l\theta_2\dot{\theta}_1^2 + l\theta_2\dot{\theta}_2^2 + 2l\dot{\theta}_1\dot{\theta}_4 + (l\theta_1 + L\sin\theta_3)\ddot{\theta}_4 + g\theta_2 = 0 \quad (7)$$

where: θ_1 and θ_2 are angles of swinging of the payload in the plane of vertical motion of the boom and the tangential direction of the horizontal movement of the boom, θ_3 and θ_4 indicate the horizontal and vertical angles of boom, respectively, and a L and l represent the lengths of boom and rope.

Using numerical solving of algebraic equations trajectory of S-curve can be obtained, which includes the elimination of residual vibrations without measuring them, using only the horizontal movement of the crane boom. Using a laboratory model of the crane, the verification of results obtained by numerical simulation and experimental results from scaled model of the crane was carried out.

Good agreement between the results is observed and found that with the same laboratory model except obtaining trajectories can obtain time of deceleration of the crane in the real time, which is one of the ideas for future research.

Figure 5: Schematic of slewing crane model [10]

In the paper [11], a dynamic model tower (construction) crane Fig.6 is presented, where along the rotating crane boom, trolley with hanging payload is moving.

The crane can be modeled as a system consisting of cantilever beam attached to the rigid rotating pillar and trolley on which is hanged the payload in the form of a pendulum and which are moving along the console. Cantilever beam is modeled using Euler-Bernoulli theory assuming that the revolving inertial and shear deformations can be discarded. The payload is modeled as pendulum Fig.7, on which end is located a concentrated mass and which is hung at one end to the massless inextensible cable and the second attached on trolley which are moving frictionless along the rotating boom and also are represented as concentrated mass.

Figure 6: Configuration of the elastic boom with moving load [11]

Movement of rotating boom is described with the help of coupled equations in plane and out of the console plane, while the equations of motion of the payload are derived from the Hamilton's principle. In the paper are given notes in the form of of guidelines for solving equations.

Figure 7: The angles of the payload oscillations [11]

The paper [12] deals with research of dynamic behavior of hydraulic slewing crane with free hanging load which is oscillating during rotation and raising and lowering the crane boom Fig.8. For the purpose of simplification of the mentioned procedure two movements are discussed individually. Crane represents the kinematic chain of 3 members with rotating joints. With two degrees of freedom raising and lowering of the load is described while with an additional degree the rotation of the crane is described.

For the formation of mathematical model of the crane, the Newton-Euler algorithm on the basis of which formed the second order differential equation problem for forward dynamics is used.

$$-M(q)\ddot{q}-H(q,\dot{q})+G(q)+\tau(t)=0 \quad (8)$$

where: q , $\dot{q}$, $\ddot{q}$ are vectors of position, speed and angular acceleration of joints, $M(q)$ is mass matrix composed of elements which describe acceleration $\ddot{q}$ for every element, $G(q)$ weight terms and $\tau(t)$ is vector of torque for every joint.

Based on the simulation, which is based on the aforementioned equations, angles of raising and lowering of the boom are determined, hydraulic system pressure and also forces in the joints, a good match between the results obtained by the simulation and the results obtained by experiment is achieved.

Figure 8: Denavit- Hartenberg parameters in case of oscillation of the load [12]

The paper [13] considers the movement of the payload represented by the pendulum and the dynamic response of the structure of construction tower crane on Fig.9. Crane is modeled using finite element method while equations of the payload movement are described using Lagrange equations of second kinds, including the dissipative function.

The analysis of dynamics of the real crane model using the proposed approach and the numerical methods for solving the equations of motion of the system is performed. It was found that the dynamic amplification factors increase with increasing initial angle of oscillation of the payload whose changes when moving in the plane are non-linear.

Figure 9: Scheme geometry construction of the tower cranes with a load in the form of a pendulum [13]

The paper [14] deals with the dynamic behavior of mobile construction crane not only from the aspect of the support structure and external loads, also in terms of the drive and control system Fig.10. A new method for dynamic analysis of mobile cranes, which is based on a system with more rigid bodies which is coupled to a drive system is developed. In this way, on the basis of the integrated model dynamic behavior of the crane, motion of the crane construction and dynamic behavior of the drive system can be determined.

The movement of the entire system is described with using the Lagrange equation of second kind. Numerical simulation of the system was carried out with the assistance of input parameters, the required speed of rotation and the control parameters. Using the new method various parameters of the system can be considered, and some of them are: oil pressure, output torque of the engine, the oil flow, stability control, and many other parameters which are important for the design of the crane.

Figure 10: Dynamic model of the crane with coordinate system [14]

The paper [15] examined the effect of supports elasticity of slewing crane dynamics Fig.11. The mathematical model that consists of four rigid bodies is constructed using Lagrange equations of the second order which are numerically solved using the Newmark integration method. In order to obtain the required trajectory and the stabilization of the final positions of the payload, at the end of the motion dynamic optimization method is applied.

The results of numerical simulations were compared with the results from the software package MSC.ADAMS, and also with the results obtained by experiment. The results of dynamic optimization can be used in order to form a neural network which allows that the crane drive functions are defined in real time.

Figure 11: Dynamic model of the crane [15]

The paper [16] presents a method of reducing the payload oscillations by using of winding and unwinding of cable for lifting. The payload is modeled as a concentrated mass, the rope is modeled as a rigid connection and assembly represents the spherical pendulum hanging on the tip of the boom. Using two-dimensional and three-dimensional models, the movement of the payload is described. The results of numerical simulations show that with change of rope, length swinging (oscillation) of the payload can be reduced because of the near resonant excitation.

Lagrangian function which represents the total energy of the system can be written in the following form:

$$L = T - V = \frac{1}{2} m \left((\dot{x}_a + \dot{\xi})^2 + (\dot{y}_a + \dot{\zeta})^2 + \dot{z}^2 \right) - mgz \quad (9)$$

where: T is kinetic energy of the system, V potential energy of the system, while (ξ, η, ζ) are the coordinates of the load position in the coordinate system attached to the boom tip, shown on Fig.12. It was found that the appropriate selection of the winding and unwinding speed of the cable, a significant reduction in the oscillation of the payload can be achieved.

Figure 12: Coordinate system of the crane [16]

3. CONCLUSION

The paper presents the mathematical and dynamic models of slewing cranes with a focus on craft portal cranes. Through the analysis of existing research, slewing portal cranes, construction tower cranes, mobile construction cranes and hydraulic telescopic cranes are discussed in this paper.

All aforementioned papers represent a good basis for further research in the field of crane dynamics, which should focus on describing a system using precise dynamic model that takes into account the larger number of concentrated masses. Apart from that, in future researches should be taken into account the elasticity of the segments of the construction which affects the future budget and the results obtained. In addition, in future researches the elasticity of the segments of the structure that affects the further calculation and obtained results, should be taken in to the account.

Also, further studies should be directed towards the use of modern optimization algorithms that can be used to reach optimal values of structural parameters of cranes.

4. ACKNOWLEDGEMENT

This paper is the result of a project number TR35038, which is funded by the Ministry of Education, Science and Technological Development of Republic of Serbia.

5. REFERENCES

- [1] Ostrić D, Tošić S.: “DIZALICE”, Mašinski fakultet, Beograd, 2005.
- [2] А. Ланг, И. Мазовер, В. Майзель, “ПОРТАЛЬНЫЕ КРАНЫ – расчёт и конструирование”, Государственное научно-техническое издательствомашинириельной литературы, Москва-Ленинград, 1962.
- [3] Georgijević M.: “DINAMIKA DIZALICA - eksperimentalna i modelska analiza”, Zadužbina Andejević, Beograd, 1996.
- [4] B. Visocnik, S. Kravanja: “Slewing Port Jib Cranes”, Promet- Traffic- Traffico, Vol.14, 2002, No.5, 251-257
- [5] Rade Vasiljevic, Radovan Bulatovic, Mile Savkovic: “The Approaches to the Mathematical-mechanical Modeling Supporting Construction”, IMK-14 – Research & Development in Heavy Machinery, Vol.19, No.1, 2012, EN29-38
- [6] Rade Vasiljević , Milomir Gašić: “The Dynamic Model of the Boom Portal Cranes”, IMK-14 – Research & Development in Heavy Machinery, Vol.21, No.4, 2015, EN125-130
- [7] Rade Vasiljević, Milomir Gašić, Mile Savković: “Parameters Influencing the Dynamic Behaviour of the Carrying Structure of a Type H Portal Crane”, Strojniški vestnik - Journal of Mechanical Engineering 62(2016)10, 591-602
- [8] Miomir Jovanović, Goran Radoičić, Predrag Milić, “Dynamic Sensitivity Research of Portal-Rotating Cranes”, XIX International Conference on "Material Handling, Constructions and Logistics - MHCL 09", Beograd, 15-16 Oktobar 2009, pp. 61-66
- [9] Ivica Marinović, Denijal Sprečić, Boris Jerman, “A Slewing Crane Payload Dynamics”, Tehnički vjesnik, Vol.19, No.4, 2002, 907-916.
- [10] Naoki Uchiyama, Huimin Ouyang, Shigenori Sano, “Simple rotary crane dynamics modeling and open-loop control for residual load sway suppression by only horizontal boom motion”, Mechatronics, Vol.23, 2013, 1223-1236.
- [11] Wenqing Zang, Zhiyi Zhang, Rongzeng Shen, “Modeling of system dynamics of a slewing flexible beam with moving payload pendulum”, Mechanics Research Communications, Vol.34, 2007, 260-266.
- [12] Bozhidar GRIGOROV, Rosen MITREV, “Dynamic behavior of a hydraulic crane operating a freely suspended payload”, Journal of Zhejiang University-SCIENCE A (Applied Physics & Engineering), In press, 2016, 22-35.
- [13] F. Ju, Y.S. Choo, F.S. Cui, “Dynamic response of tower crane induced by the pendulum motion of the payload”, International Journal of Solids and Structures, Vol.43, 2006, 376-389.
- [14] Guangfu Sun, Michael Kleeberger, “Dynamic responses of hydraulic mobile crane with consideration of the drive system”, Mechanism and Machine Theory, Vol.38, No.12, 2003, 1489-1508.
- [15] Andrzej Urbas, Marek Szczotka, Stanislaw Wojciech, “THE INFLUENCE OF FLEXIBILITY OF THE SUPPORT ON DYNAMIC BEHAVIOR OF A CRANE”, International Journal of Bifurcation and Chaos, Vol.21, No.10, 2011, 2963-2974.
- [16] E. M. Abdel-Rahman, A. H. Nayfeh, “endulation Reduction in Boom Cranes Using Cable Length Manipulation”, Nonlinear Dynamics, Vol.27, 2002, 255-269.