Osnove eksperimentalnog određivanja sila u kontaktu točak-šina primenom instrumentalizovanih osovinskih sklopova

Milan Bižić*, Dragan Petrović

¹Fakultet za mašinstvo i građevinarstvo u Kraljevu, Univerzitet u Kragujevcu, Srbija

Sile u kontaktu točak-šina predstavljaju glavne uticajne parametre i pokazatelje kvaliteta dinamičkog ponašanja železničkih vozila. Njihovo tačno određivanje ima veliki praktični značaj u procesima razvoja i ispitivanja železničkih vozila. Iskustva pokazuju da je najbolji način za određivanje ovih sila eksperimentalno ispitivanje odnosno merenje koje može biti stacionarno (sistemi na koloseku) i kontinualno (sistemi na vozilu). Kada se radi o mernim sistemima na vozilu, čija upotreba je obavezna u mnogim slučajevima sertifikacije i atestiranja železničkih vozila prema međunarodnim standardima, ne postoji univerzalno tehničko rešenje. Kao posledica toga, danas postoji veliki broj rešenja ovakvih mernih sistema koji su uglavnom zasnovani na primeni instrumentalizovanih osovinskih sklopova. Cilj ovog rada je da analizira najznačajnije metode i definiše osnove merenja sila u kontaktu točak-šina i položaja tačke kontakta primenom instrumentalizovanih osovinskih sklopova. Rezultati rada mogu biti veoma značajan izvor informacija za naučnike i inženjere, imajući u vidu nedostatak literature i naučnih publikacija u ovoj oblasti.

Ključne reči: Sile u kontaktu točak-šina, Instrumentalizovani osovinski sklop, Eksperiment, Železnička vozila.

0. UVOD

Mehanizam nastanka iskliznuća je usko povezan sa silama u kontaktu točak-šina koje izazivaju vibracije, habanje, termičke pojave, buku, zamor, otkaze i druge neželjene efekte u eksploataciji železničkih vozila. Poseban značaj ima vertikalna sila Q i bočna sila Y čiji je odnos Y/Q ključan za ocenu sigurnosti protiv iskliznuća (Sl. 1).

Sl. 1: Sile u kontaktu točak-šina

Iznalaženje načina za što tačnije i pozudnjanje analitičko i eksperimentalno određivanje ovih sila predstavlja jedan od najvažnijih zadataka u dinamici železničkih vozila [1–4]. Analitički pristup zasnovan je na odgovarajućim modelima kontakta točak-šina i numeričkom rešavanju formiranih jednačina [5]. Međutim, najpouzdaniji pristup podrazumeva eksperimentalna ispitivanja ili merenja koja mogu biti realizovana sa strane koloseka i sa strane vozila. Merni sistemi sa strane koloseka su obično bazirani na merenju deformacija šine [6, 7]. Nasuprot tome, merni sistemi sa strane vozila (instrumentalizovani osovinski sklopovi) obično se zasnivaju na merenju deformacija točka [8]. Instrumentalizovani osovinski sklopovi su opremljeni senzorima, najčešće mernim trakama, i postavljaju se na železničko vozilo koje se ispituje (Sl. 2). Njihova primena je obavezna u mnogim slučajevima prilikom sertifikacije i

atestiranja železničkih vozila u skladu sa međunarodnim standardima UIC 518 i EN14363 [9, 10].

Sl. 2: Instrumentalizovani osovinski sklop

Osnovni cilj pri razvoju instrumentalizovanih osovinskih sklopova je postizanje što veće tačnosti merenja. Step en ispunjenja ovog cilja zavisi od uspešnosti rešavanja više međusobno spregnutih problema vezanih za lokacije mernih traka, metod inverzne identifikacije, način kalibracije, itd. [11–14]. Tokom godina mnogi istraživači su se bavili rešavanjem ovih problema koji su još aktuelni u naučnoj i stručnoj javnosti. Veoma je značajno naglasiti da danas ne postoji univerzalan metod za merenje sila u kontaktu točak-šina primenom instrumentalizovanih osovinskih sklopova. Iako pomenuti međunarodni standardi propisuju primenu instrumentalizovanih osovinskih sklopova u pojedinim fazama sertifikacije železničkih vozila, oni ne definišu tehničko rešenje i potrebnu tačnost mernog sistema. Zbog toga danas postoji mnoštvo različitih pristupa i metoda, pri čemu svaki od njih ima određene prednosti i nedostatke u poređenju sa ostalima [15]. U tom smislu, osnovni cilj ovog rada je da analizira najznačajnije metode i definiše osnove merenja sila u kontaktu točak-šina i položaja tačke kontakta primenom instrumentalizovanih osovinskih sklopova.

1. METODE MERENJA SILA U KONTAKTU TOČAK-ŠINA

Sve metode eksperimentalnog određivanja sila u kontaktu točak-šina zasnovane su na dva pristupa: merenja sa strane koloseka i merenja sa strane vozila. Oba pristupa proizilaze iz činjenice da je ove sile nemoguće meriti

direktno na mestu njihove egzistencije u kontaktu točka i šine. Rešavanje problema zasniva se na činjenici da pomenute sile tokom kretanja izazivaju deformacije struktura koje se nalaze u njihovoj neposrednoj blizini. Merenjem deformacija tih struktura (elemenata koloseka ili vozila), sile u kontaktu točak-šina mogu se određivati na indirektnan način.

Merenje sa strane koloseka obično bazira na primeni stacionarnih mernih stanica koje se postavljaju na određena mesta duž koloseka. One se opremljene senzorima, obično mernim trakama, koje su postavljene na elemente koloseka (obično šine), koje mere deformacije tokom prolaska voza. Prve korake u uvođenju sistema merenja sa strane koloseka napravio je ORE (Office for Research and Experiments), kasnije ERRI (European Rail Research Institute). U izveštaju publikovanom 1970. godine ORE je identifikovao ključne probleme i dao generalne smernice za njihovo rešavanje, ali bez definisanja jedinstvene merne metode [16]. Od tada su razvijena različita tehnička rešenja ovakvih mernih sistema. Većina njih je zasnovana na merenju deformacija šine primenom mernih traka [6, 7]. Određivanje lokacija mernih traka je obično bazirano na MKE (metod konačnih elemenata) analizi deformacija šine. Ključni problem je pronalaženje lokacija sa najvećom osetljivošću na dejstvo Q i Y sile, uz minimalno mešanje njihovog uticaja u izlaznim mernim signalima. Kalibracija mernog sistema može biti zasnovana na MKE rezultatima ili može biti realizovana pomoću specijalne opreme u realnim uslovima. Osnovna prednost metode merenja sa strane koloseka je da se merenje može realizovati za svaki voz koji prolazi kroz stacionarnu mernu stanicu. Njen osnovni nedostatak je da ne omogućava kontinualno merenje tokom kretanja voza. Merenje se realizuje samo na diskretnim mestima odnosno u tačkama na liniji koje su procenjene kao kritične sa aspekta kvaliteta dinamičkog ponašanja železničkih vozila. Međutim, u procesu sertifikacije železničkih vozila u skladu sa pomenutim međunarodnim standardima zahteva se primena kontinualnog merenja parametara dinamičkog ponašanja tokom kretanja po koloseku. Zbog toga je primena mernih sistema sa strane koloseka ograničena na oblast nadzora železničkih vozila koja su već u eksploataciji.

Merenje sila u kontaktu točak-šina sa strane vozila obično su zasnovana na primeni instrumentalizovanih osovinskih sklopova. Oni su opremljeni senzorima (najčešće mernim trakama) koji mere deformacije tokom kretanja ispitivanog vozila na bazi kojih se indirektno određuju sile u kontaktu točak-šina. Generalno, sva tehnička rešenja instrumentalizovanih osovinskih sklopova baziraju na dva pristupa: merenje preko osovine i merenje preko točka. Prva rešenja merenja preko osovine pojavila su se početkom sedamdesetih godina 20. veka. Iako su u međuvremenu značajno unapređena, njihova glavna karakteristika zasniva se na merenju momenata savijanja i uvijanja u određenim presecima osovine [17–19]. Rešenje prikazano na slici 3 bazira na merenju momenata savijanja i uvijanja u šest različitih preseka osovine. Na taj način moguće je odrediti približne vrednosti šest sila u kontaktu točak-šina. Momenti se mere pomoću mernih traka koje su povezane u odgovarajuće konfiguracije Vitstonovih mostova. Prednosti ovakvih rešenja leže u relativno jednostavnom mernom sistemu, kao i u mogućnosti

zamene točkova instrumentalizovanog osovinskog sklopa. Mnogo su značajniji njihovi nedostaci koji se primarno ogledaju u nemogućnosti kompenzovanja greške merenja koja nastaje pri promeni položaja tačke kontakta. Merenje preko osovine je dugo korišćeno na Nemačkim železnicama ali su ga, zbog navedenih nedostataka, zamenila savremenija rešenja.

Sl. 3: Instrumentalizovani osovinski sklop zasnovan na merenju preko osovine [19]

Prva konkretna rešenja merenja preko točka instrumentalizovanog osovinskog sklopa pojavila su se tokom pedesetih godina 20. veka. Tada se pojavljuje poznata metoda Olsona (Olson) i Džonsona (Johnsson) [20]. Od tada do danas razvijen je veliki broj tehničkih rešenja merenja preko točka instrumentalizovanog osovinskog sklopa [21]. Sva rešenja baziraju na dva pristupa: merenje preko točka sa paocima i merenje preko standardnog monoblok točka. Najveći doprinos razvoju instrumentalizovanih osovinskih sklopova sa točkovima sa paocima dale su Britanske železnice tokom sedamdesetih i osamdesetih godina 20. veka [22–24]. Rešenja su bazirana na merenju deformacija primenom mernih traka postavljenih na određena osetljiva mesta na paocima (Sl. 4). Merne trake su u određenim konfiguracijama povezane u Vitstonove mostove sa ciljem postizanja najveće moguće osetljivosti i tačnosti merenja. Prednost ove metode je bolja osetljivost na uticaj Q sile usled veće elastičnosti točka u vertikalnom pravcu. Osnovni nedostatak je veoma složena i skupa izrada paoka koja zahteva visoku tačnost. Ovaj metod se danas retko koristi, iako je dugo korišćen u Velikoj Britaniji i Švajcarskoj.

Sl. 4: Instrumentalizovani osovinski sklop zasnovan na točkovima sa paocima [23]

Instrumentalizovani osovinski sklopovi sa merenjem preko standardnih monoblok točkova pojavili su se tokom pedesetih godina 20. veka. Nakon pojave metode Olsona i Džonsona razvoj ovakvih instrumentalizovanih osovinskih sklopova išao je uzlaznom putanjom uz povećanje osetljivosti i tačnosti merenja [25–27].

Osamdesetih godina 20. veka u ovoj oblasti značajni koraci napravljeni su na prostoru bivše Jugoslavije. Tada je profesor Relja Jovanović sa saradnicima razvio instrumentalizovani osovinski sklop baziran na primeni mernih traka postavljenih na standardne monoblok točkove [28]. Merenje sila u kontaktu točak-šina pomoću instrumentalizovanih osovinskih sklopova sa standardnim monoblok točkovima je metoda koja se danas najviše koristi u ovoj oblasti [29–34].

Ključna prednost merenja sa strane vozila sastoji se u činjenici da omogućava kontinualno merenje. Glavni nedostatak ogleda se u tome što je merni sistem vezan samo za jedan osovinski sklop. Pošto se konstrukcije osovinskih sklopova za različite tipove železničkih vozila mogu značajno razlikovati, instrumentalizovani osovinski sklopovi moraju biti prilagođeni specifičnim tipovima vozila ili obrtnih postolja. To uzrokuje visoke troškove njihovog razvoja i izrade.

2. FORMULACIJA PROBLEMA KONTINUALNOG MERENJA SILA U KONTAKTU TOČAK-ŠINA I POLOŽAJA TAČKE KONTAKTA

Osnovni problem merenja sila u kontaktu točak-šina leži u činjenici da je ove sile nemoguće meriti direktno u kontaktnoj površini između točka i šine. Kao rezultat toga, ove sile se određuju indirektno na osnovu merenja deformacija struktura koje se nalaze u neposrednoj blizini kontaktne površine. Kod mernih sistema sa strane vozila, merenja se obično realizuju preko točka kao elementa železničkih vozila koji je izložen najvećim opterećenjima usled uticaja navedenih sila. Merenje deformacija točka primenom mernih traka omogućava indirektno određivanje sila u kontaktu točak-šina po određenom algoritmu. Osnovni problem kod svih indirektnih metoda proizilazi iz činjenice da deformacije točka nisu izazvane samo uticajem bočne i vertikalne sile koje se mere, već na njih u isto vreme utiče veliki broj drugih parametara. Uzimanje u obzir i pravilno sagledavanje uticaja ovih parametara je od ključnog značaja za razvoj visoko kvalitetne metode za eksperimentalno određivanje sila u kontaktu točak-šina i postizanje visoke tačnosti merenja.

Na deformacije točka tokom kretanja utiču sledeće sile u kontaktu točak-šina: vertikalna sila Q , bočna sila Y i podužna sila X . Pored toga, na date deformacije utiču i: položaj tačke kontakta y_{cp} , habanje profila točka w , ugaona brzina točka ω i temperaturno polje T .

Zavisnost deformacija točka u tački j od pomenutih parametara može se izraziti na sledeći način [8]:

$$\varepsilon_j = f(Q, Y, X, y_{cp}, w, \omega, T) \quad (1)$$

Prema tome, na osnovu deformacija točka odnosno signala sa Vitstonovih mostova, koji su pomešani usled uticaj svih navedenih parametara, potrebno je indirektno određivati vrednosti nepoznatih parametara Q , Y i y_{cp} . Ovaj problem pripada grupi problema inverzne identifikacije i može se šematski predstaviti kao što je prikazano na slici 5.

Usled velike krutosti točka, deformacije koje se registruju mernim trakama imaju veoma male vrednosti, naročito pri dejstvu Q sile. Tu postoji veoma značajan problem kako dobiti najveće moguće vrednosti signala sa Vitstonovih mostova i povećati odnos signal-šum. Imajući u vidu da su deformacije promenljive duž tela točka, veoma je značajno određivanje lokacija ili radijalnih rastojanja sa najvećom osetljivošću na uticaje parametara koji se mere. Postavljanje mernih traka na takve lokacije obezbeđuje veću osetljivost mernog sistema odnosno veće vrednosti izlaznih signala sa Vitstonovih mostova. Ako su merne trake postavljene na lokacije sa nedovoljnom osetljivošću dobijaće se male vrednosti izlaznih signala, što će dovesti do velikog odnosa signal-šum i velike greške merenja. Pored toga, značajni problemi odnose se na određivanje optimalnog rasporeda, broja i načina povezivanja mernih traka, takođe u cilju dobijanja najvećih mogućih vrednosti izlaznih signala ili u cilju kompenzovanja uticaja pojedinih parametara iz izraza (1). Dakle, osnovni preduslov za dobijanje visoke tačnosti merenja je interaktivno i kvalitetno rešavanje formulisanih problema, kao i problema razvoja algoritma inverzne identifikacije.

3. PRINCIPI REŠAVANJA FORMULISANIH PROBLEMA

Rešavanje formulisanih problema treba da bude zasnovano na MKE modelu točka osovinskog sklopa koji je izabran kao platforma za razvoj instrumentalizovanog osovinskog sklopa. Ključni zadatak modela je da obezbedi tačno određivanje naponsko-deformacionih stanja točka pri dejstvu parametara definisanih izrazom (1). Na taj način se omogućava identifikacija uticaja datih parametara na deformacije točka odnosno signale sa Vitstonovih mostova, što je od ključnog značaja za kvalitetno rešavanje problema i dobijanje visoke tačnosti merenja. Model treba da omogući identifikaciju optimalnih lokacija mernih traka, kao i njihovog optimalnog rasporeda, broja i načina povezivanja. Pored toga, treba da omogući testiranje i verifikaciju razvijenog algoritma inverzne identifikacije.

Sl. 5: Problem inverzne identifikacije pri merenju sila u kontaktu točak-šina i položaja tačke kontakta

Na taj način se omogućava značajno smanjenje troškova razvoja instrumentalizovanog osovinskog sklopa.

Primer naponsko-deformacionih stanja točka dobijenih MKE proračunom prikazan je na slici 6.

Sl. 6: Primer naponsko-deformacionih stanja točka dobijenih MKE proračunom [8]

Od svih parametara definisanih izrazom (1) može se zanemariti samo uticaj podužne sile X . Instrumentalizovani osovinski sklopovi primarno su namenjeni za ispitivanja vučenih vizila kod kojih ova sila nema značajne vrednosti, a njeno merenje ne zahteva se u procesu sertifikacije prema pomenutim međunarodnim standardima. Veoma je značajno napomenuti da standardi ne zahtevaju ni merenje položaja tačke kontakta u procesu sertifikacije železničkih vozila. Međutim, ovaj parametar ima određenog uticaja na deformacije točka i mora se uzeti u obzir u cilju dobijanja visoke tačnosti merenja sila Q i Y . Uticaj parametra w manifestuje se promenom profila točka tokom eksploatacije instrumentalizovanog osovinskog sklopa. U cilju dobijanja visoke tačnosti merenja, uticaj ovog parametra mora se uzeti u obzir u samom algoritmu inverzne identifikacije [8]. Na taj način, signal sa

Vitstonovog mosta koji je postavljen na određenom radijalnom rastojanju postaje sledeća funkcija:

$$S_m = f(Q, Y, y_{cp}) \quad (2)$$

Prema tome, na osnovu izlaznih signala sa Vitstonovih mostova treba određivati tri nepoznata parametra Q , Y i y_{cp} . Imajući u vidu da svaka merna traka registruje relativnu deformaciju ε i da se točak nalazi u zoni elastičnosti, prema Hukovom zakonu postojaće linearna relacija između napona odnosno sile u kontaktu točak-šina i registrovane deformacije. Isto važi i za Vitstonov most koji se sastoji od više mernih traka. Pošto je relacija između registrovane deformacije svake individualne merne trake i zadate sile linearna, veza između signala sa Vitstonovog mosta i zadate sile u kontaktu točak-šina biće takođe linearna. Prema tome, zavisnost signala S_m od Q sile i Y sile u izrazu (2) je linearna. Međutim, glavni problem proizilazi iz činjenice da je, usled složene nelinearne geometrije profila točka, zavisnost signala S_m od promene položaja tačke kontakta y_{cp} nelinearna. Ova nelinearna relacija može se transformisati u linearnu uvođenjem momenta M od sila Q i Y u odnosu na nominalnu tačku kontakta (Sl. 7).

Sl. 7: Moment M od sila Q i Y u odnosu na nominalnu tačku kontakta

Moment M je u stvari nelinearna funkcija parametara Q , Y i y_{cp} [8]:

$$M = -Q \cdot y_{cp} - Y \cdot z_{cp} \quad (3)$$

Za formiranje modela i naponsko-deformacionu analizu točka od presudnog značaja je da pomenuta linearna veza omogućava da se, za proizvoljno izabran položaj tačke kontakta, ukupna deformacija može izraziti kao zbir komponenti deformacija izazvanih pojedinačnim dejstvom sile Q i sile Y u kontaktu točak-šina. Ovo se matematički može definisati na sledeći način:

$$\varepsilon_t = \varepsilon_t(Q, Y) = \varepsilon_t(Q, 0) + \varepsilon_t(0, Y) \quad (4)$$

Dakle, u formiranom MKE modelu naponi i deformacije točka mogu se analizirati pri individualnim dejstvima Q i Y sile, u različitim položajima tačke kontakta (Sl. 8).

Sl. 8: Posledica linearne relacije između deformacija točka i sila Q i Y

Primarni cilj naponsko-deformacione analize je određivanje lokacija sa najvećom osetljivošću na pojedinačna dejstva parametara koji se mere (vertikalne sile Q , bočne sile Y i položaja tačke kontakta y_{cp}), ali na kojima nema mešanja njihovog uticaja u vrednostima deformacija točka odnosno izlaznih signala sa mernih mostova. Postavljanjem mernih traka na radijalna rastojanja sa visokom osetljivošću i bez mešanja uticaja omogućava se uspostavljanje veoma jednostavne matematičke zavisnosti između izlaznog mernog signala i nepoznate sile koja ga izaziva. Ta zavisnost se utvrđuje kalibracijom mernog sistema koja se može realizovati na posebnoj probnici ili korišćenjem rezultata dobijenih pomoću MKE modela točka. U ovakvom slučaju, algoritam inverzne identifikacije se pojednostavljuje i podrazumeva da se na osnovu vrednosti jednog mernog signala sa radijalnog rastojanja koje je najosetljivije na dejstvo date sile, odredi vrednost te sile. Međutim, ukoliko za datu geometriju točka ne postoje takve lokacije, odnosno ukoliko je izlazni signal dobijen sa mernog mosta postavljenog na radijalnom rastojanju sa najvećom osetljivošću na određeni parametar pomešan usled uticaja i drugih parametara koji se mere, rešavanje problema se značajno komplikuje. Veoma je značajno naglasiti da ukoliko se ovaj problem ne identifikuje, merenje će biti realizovano sa velikom greškom.

U cilju postizanja visoke tačnosti merenja, jedno od rešenja je kompenzacija ili neutralisanje uticaja mešanja odgovarajućim načinom povezivanja mernih traka u Vitstonove mostove. Pri tome, treba imati u vidu da se mešanje nikada ne može u potpunosti neutralisati. Drugi pristup podrazumeva primenu neke od metoda koje omogućavaju određivanje pojedinačnih uticaja parametara koji se mere na osnovu vrednosti pomešanih izlaznih signala sa Vitstonivih mostova. U tom slučaju, biraju se radijalna rastojanja sa najvećom osetljivošću, bez obzira na stepen mešanja uticaja parametara koji se mere.

Prema tome, način rešavanja svih ovih problema zavisi od rezultata naponsko-deformacione analize dobijenih pomoću modela konkretnog tipa točka standardnog osovinskog sklopa koji je izabran kao platforma za razvoj instrumentalizovanog osovinskog sklopa. Dobijene rezultate naponsko-deformacione analize odnosno dati model točka potrebno je verifikovati eksperimentalnim ispitivanjima na realnom objektu, odnosno točku izabranog osovinskog sklopa.

4. ZAKLJUČAK

Eksperimentalna ispitivanja su najpouzdaniji način za određivanje parametara dinamičkog ponašanja železničkih vozila, naročito onih najvažnijih – sila u kontaktu točak-šina. Ne postoji univerzalni način niti univerzalno tehničko rešenje za merenje ovih sila. Takođe, ne postoji univerzalno tehničko rešenje instrumentalizovanog osovinskog sklopa koje se može okarakterisati kao najbolje. Svaka metoda i svako tehničko rešenje, u zavisnosti od namene i karakteristika, ima određene prednosti i nedostatke u odnosu na ostale. U tom smislu, cilj ovog rada bio je da definiše osnove za rešavanje problema merenja sila u kontaktu točak-šina i položaja tačke kontakta pomoću instrumentalizovanih osovinskih sklopova. Identifikovani su ključni problemi u razvoju instrumentalizovanih osovinskih sklopova. Oni su

povezani sa određivanjem optimalnog rasporeda, broja i načina povezivanja mernih traka, kao i sa razvojem algoritma inverzne identifikacije. Posebna pažnja posvećena je značaju razvoja MKE modela točka koji predstavlja osnovu za rešavanje svih ovih problema. Rezultati ovog rada daju veoma značajne smernice za optimalno rešavanje pomenutih problema, što predstavlja osnovni preduslov za razvoj instrumentalizovanih osovinskih sklopova visoke tačnosti.

ZAHVALNICA

Autori izražavaju zahvalnost Ministarstvu prosvete, nauke i tehnološkog razvoja Republike Srbije za podršku ovom istraživanju kroz projekat TR35038.

LITERATURA

- [1] V.K. Garg, R.V. Dukkipati, "Dynamics of Railway Vehicle Systems", Academic Press, Toronto, (1984)
- [2] A.H. Wickens, "Fundamentals of Rail Vehicle Dynamics – Guidance and Stability", Swets & Zeitlinger Publishers, Lisse, (2003)
- [3] S.D. Iwnicki, "Handbook of Railway Vehicle Dynamics", CRC Press, Taylor & Francis Group, Boca Raton, (2006)
- [4] E. Andersson, M. Berg, S. Stichel, "Rail Vehicle Dynamics", Railway Group KTH, Stockholm, (2007)
- [5] S.Z. Meymand, A. Keylin, M. Ahmadian, "A survey of wheel-rail contact models for rail vehicles", *Vehicle System Dynamics*, 54(3), pp. 386-428, (2016)
- [6] D. Milković, G. Simić, Ž. Jakovljević, J. Tanasković, V. Lučanin, "Wayside system for wheel-rail contact forces measurements", *Measurement*, 46, pp. 3308-3318, (2013)
- [7] M. Brunera, M. Catenab, D. Cortisa, G. Malavasia, S. Rossib, M. Testab, "Estimation of the wheel-rail lateral contact force through the analysis of the rail web bending strains", *Measurement*, 99, pp. 23-35, (2017)
- [8] M. Bižić, "Istraživanje uticajnih parametara u interakciji točak-šina na stabilnost kretanja železničkih vozila", Doktorska disertacija, Fakultet za mašinstvo i građevinarstvo u Kraljevu, Univerzitet u Kragujevcu, (2015)
- [9] UIC CODE 518 OR, "Testing and approval of Railway vehicles from the point of view of their dynamic behaviour – Safety – Track fatigue – Running behaviour", 4th edition, International Union of Railways – UIC, (2009)
- [10] EN 14363, "Railway applications – Testing for the acceptance of running characteristics of railway vehicles – Testing of running behaviour and stationary tests", European Committee for Standardization – CEN, (2005)
- [11] Y.Q. Sun, C. Cole, M. Spiriyagin, "Monitoring vertical wheel-rail contact forces based on freight wagon inverse modelling", *Advances in Mechanical Engineering*, 7(5), pp. 1-11, (2015)
- [12] J. Zeng, L. Wei, P. Wu, "Safety evaluation for railway vehicles using an improved indirect measurement method of wheel-rail forces", *J. Mod. Transport*, 24(2), pp. 114-123, (2016)

- [13] M. Bizic, M. Tomic, Z. DjinoVIC, D. Petrovic, "Test stand for calibration of measurement railway wheelsets", Proceedings of the 7th International Conference Research and Development of Mechanical Elements and Systems – "IRMES 2011", Zlatibor, Serbia, pp. 419-424, (2011)
- [14] L. Binbin, S. Bruni, "A method for testing railway wheel sets on a full-scale roller rig", Vehicle System Dynamics, 53(9), pp. 1331-1348, (2015)
- [15] M. Bizic, D. Petrovic, "Methodologies of experimental determination of wheel-rail contact forces", Proceedings of the XVI International Scientific-Expert Conference on Railways – "RAILCON 2014", Niš, Serbia, pp. 157-160, (2014)
- [16] ORE B55/RP4, "Two axled wagons subjected to simultaneous stresses due to track distortion and to transverse components of the forces of the automatic coupler; Dynamic effects of track distortions", Office for Research and Experiments, Utrecht, Netherlands, (1970)
- [17] M. Zeilhofer, G. Sühsmuth, G. Piwenitzky, "Ermittlung der Kräfte zwischen Rad und Schiene aus den Biegedehnungen der Radsatzwelle", ZEV - Glasers Annalen, 96(12), pp. 373-385, (1972)
- [18] H.H. Zuck, "Determination of Wheel/Rail Forces by Means of Measuring Wheelsets on Deutsche Bundesbahn", Proceedings of the International Conference on Wheel/Rail Load and Displacement Measurement Techniques, Transportation Systems Center, Cambridge, Massachusetts, pp. 7.1-7.22, (1981)
- [19] H. Berg, G. Gößling, H. Zück, "Radsatzwelle und Radscheibe – die richtige Kombination zur Messung der Kräfte zwischen Rad und Schiene", ZEV - Glasers Annalen, 120(2), pp. 40-47, (1996)
- [20] P.E. Olson, S. Johnsson, "Seit enkräfte zwischen Rad und Schiene", Glasers Annalen, pp. 153-161, (1959)
- [21] A. Bracciali, F. Cavaliere, M. Macherelli, "Review of Instrumented Wheelset Technology and Applications", Proceedings of the Second International Conference on Railway Technology: Research, Development and Maintenance, Civil-Comp Press, Stirlingshire, Scotland, Paper 167, pp. 1-16, (2014)
- [22] A.R. Pocklington, R.A. Allen, "Improved Data from Load-Measuring Wheels", Railway engineering, 2(4), Institute of Mechanical Engineers, pp. 37-43, (1977)
- [23] R.A. Allen, "A Superior Instrumented Wheelset", Wheel/Rail Dynamics Society, (1980)
- [24] Pocklington A.R., "The B. R. Load Measuring Wheel", Proceedings of the International Conference on Wheel/Rail Load and Displacement Measurement Techniques, Transportation Systems Center, Cambridge, Massachusetts, pp. 4.1-4.30, (1981)
- [25] J. Modransky, W.J. Donnelly, S.P. Novak, K.R. Smith, "Instrumented Locomotive Wheels for Continuous Measurement of Vertical and Lateral Loads", ASME, Paper no. 79-RT-8, (1979)
- [26] C.A. Swenson, K.R. Smith, "Development and Use of Instrumented Locomotive Wheelsets", Proceedings of the International Conference on Wheel/Rail Load and Displacement Measurement Techniques, Transportation Systems Center, Cambridge, Massachusetts, pp. 5.1-5.10, (1981)
- [27] P. Boyd, K. Kesler, T.L. Yang, "Measurement Techniques for Onboard Wheel/Rail Loads", Proceedings of the International Conference on Wheel/Rail Load and Displacement Measurement Techniques, Transportation Systems Center, Cambridge, Massachusetts, pp. 1.1-1.36, (1981)
- [28] R. Jovanović, "Naučno-istraživački projekat: Iznalaženje metoda određivanja sila u tački dodira vagonkog točka i šine pomoću tenzometara i računara", ŽTO Sarajevo – Institut za saobraćaj Sarajevo – Zavod za kibernetiku saobraćaja Doboj, Doboj, (1985)
- [29] D.E. Otter, M.A. El-Sibaie, R.L. Higgins, "A design for next generation load measuring wheel sets", Proceedings of the 1991 IEEE/ASME Joint Railroad Conference, St. Louis, Missouri, pp. 37-42, (1991)
- [30] H. Kanehara, T. Fujioka, "Measuring rail/wheel contact points of running railway vehicles", Wear, 253, pp. 275-283, (2002)
- [31] J.C.O. Nielsen, "High-frequency vertical wheel-rail contact forces – Validation of a prediction model by field testing", Wear, 265, pp. 1465-1471, (2008)
- [32] P. Gullers, L. Andersson, R. Lunden, "High-frequency vertical wheel-rail contact forces – Field measurements and influence of track irregularities", Wear, 265, pp. 1472-1478, (2008)
- [33] E. Magel, A. Tajaddini, M. Trosino, J. Kalousek, "Traction, forces, wheel climb and damage in high-speed railway operations", Wear, 265, pp. 1446-1451, (2008)
- [34] Y.S. Ham, D.H. Lee, S.J. Kwon, W.H. You, T.Y. Oh, "Continuous Measurement of Interaction Forces between Wheel and Rail", International Journal of Precision Engineering and Manufacturing, 10(1), pp. 35-39, (2009)

Basics of experimental determination of wheel-rail contact forces by using instrumented wheelsets

Milan Bižić*, Dragan Petrović

Faculty of Mechanical and Civil Engineering in Kraljevo, University of Kragujevac, Serbia

The wheel-rail contact forces are the main influential parameters and indicators of quality of dynamic behaviour of railway vehicles. Their exact determination has a great practical importance in development and testing of railway vehicles. Past experiences have shown that the best way for determination of these forces is experimental testing or measurement that can be stationary (track side systems) and continuous (vehicle side systems). When it comes to the vehicle side systems, which are obligatory in many cases of certification of railway vehicles according to the international standards, there is no universally and prescribed technical solution. Consequently, today there are number of solutions of these measuring systems which are mainly based on using of instrumented wheelsets. The aim of this paper is to analyze the most relevant methods and to define basics of measurement of wheel-rail contact forces and contact point position using instrumented wheelsets. Results of the paper can be an important source of information for scientists and engineers, considering the deficiency of literature and scientific publications in this field.

Keywords: Wheel-rail contact forces, Instrumented wheelset, Experimental testing, Railway vehicles.

0. INTRODUCTION

The derailment mechanism is closely connected with wheel-rail contact forces which cause vibrations, wear, thermal effects, noise, fatigue, failure, and other adverse effects in exploitation of railway vehicles. Of utmost importance are vertical force Q and lateral force Y whose relation Y/Q is crucial for assessment the safety against derailment (Fig. 1).

Fig. 1: Wheel-rail contact forces

Finding ways for more accurately and reliably analytical and experimental determination of these forces is one of the most important tasks in railway vehicle dynamics [1–4]. The analytical approach is based on appropriate models of wheel-rail contact and numerical solution of formed equations [5]. However, the most reliable approach implies the experimental testing or measurement which can be realized from the track-side and from the vehicle-side. The track-side measuring systems are usually based on measurement of strains of the rail [6, 7]. On the other hand, the vehicle-side measuring systems (instrumented wheelsets) are usually based on measurement of strains of the wheel [8]. Instrumented wheelsets are equipped with sensors, usually strain gauges, and can be placed on the railway vehicles to be tested (Fig. 2). Their application is obligatory in many cases of the

certification of railway vehicles according to the international standards UIC 518 and EN14363 [9, 10].

Fig. 2: Instrumented wheelset

The main objective in the development of instrumented wheelsets is to achieve high measurement accuracy. The degree of fulfilment of this goal depends on the success of solving of more mutually coupled problems related to the strain gauges locations, inverse identification method, way of calibration, etc. [11–14]. Over the years, many researchers are dealt with solving of these problems, which are still in trend in scientific and professional public. It is important to note that today there is no universal method for measurement of wheel-rail contact forces using the instrumented wheelset. Although the mentioned international standards prescribe using the instrumented wheelsets in certain phases of certification of railway vehicles, they do not define the technical solution and the required accuracy of measurement system. That is why there are many different approaches and methods, while each of them has certain advantages and disadvantages compared to the other [15]. In this sense, the main objective of this paper is to analyze the most relevant methods and to define basics of measurement of wheel-rail contact forces and contact point position using the instrumented wheelsets.

1. METHODS OF MEASUREMENT OF WHEEL-RAIL CONTACT FORCES

All methods of experimental determination of wheel-rail contact forces are based on two approaches: measurement from the track side and measurement from

*Corresponding author: Dositejeva 19, 36000 Kraljevo, Serbia, bizic.m@mfkv.kg.ac.rs

the vehicle side. These approaches are stemmed from the impossibility to measure these forces directly in place of their existence – wheel-rail contact. The problem solving lies in the fact that forces causing certain deformations of structures in its vicinity during the running. By measurement deformations of these structures (elements of track or vehicle), forces in wheel-rail contact can be determined in an indirect way.

The track-side measurement is usually based on checkpoints placed at certain points along the track. They are equipped with sensors (usually strain gauges) placed on the track elements (usually rails), which measure strains during the train passing. First steps in introduction of track-side measurement have been made by ORE (Office for Research and Experiments) – later ERRI (European Rail Research Institute). In report published 1970. ORE has identified the key problems and gave general guidelines for their solution, but without defining of unique measurement method [16]. Since then, different technical solutions of such measurement systems are developed. The most of them are based on measurement of rail strains using the strain gauges [6, 7]. Determination of strain gauges positions is usually based on the FEM (Finite element method) analysis of rail strains. The key problem is to find locations with the highest sensitivity on Q and Y forces, as well as minimal crosstalk. Calibration of measurement system can be based on the FEM results or can be done using special tools and equipment in near-real conditions. The main advantage of track-side method is that measurement is performed for each wheelset of any train that passes through the checkpoint. The main disadvantage of this method is that it does not allow continuous measurement during the train running. Measurements are carried out only at discrete points on the line which are estimated as critical from the point of quality of dynamic behaviour of railway vehicles. However, the process of certification of railway vehicles in accordance with mentioned international standards involves the continuous measurement of parameters of dynamic behaviour along the certain track sections. Therefore, application of track-side measurements is limited on the field of monitoring of vehicles that are already in exploitation.

The vehicle-side measurements of wheel-rail contact forces are usually based on instrumented wheelsets. They are equipped with sensors (usually strain gauges) which measure certain strains during the running of tested vehicle, on the basis of which wheel-rail contact forces can be determined in an indirect way. Generally, all technical solutions of instrumented wheelsets are based on two approaches: measurement over the axle and measurement over the wheel. First solutions of measurement over the axle appeared in early seventies of the 20th century. Although they are in the meantime significantly improved, their main characteristic is based on measurement of bending and torsion moments in certain sections of the axle [17–19]. The solution in the Fig. 3 is based on measurement of bending and torsion moments in six different sections of the axle. In this way it is possible to determine the approximate values of the six wheel-rail contact forces. Moments are measured using the strain gauges connected in the proper configurations of Wheatstone bridges. Advantages of these solutions are

based in relative simple measurement system and in possibility for changing wheels of instrumented wheelset. The more important are their disadvantages which are primarily reflected in the impossibility to compensate measurement error due to changing the contact point position. Measurement over the axle was used a long time in German Railways. Because the mentioned disadvantages, this method is replaced with the modern solutions.

Fig. 3: Instrumented wheelset based on measurement over the axle [19]

First concrete solutions of measurement over the wheel of instrumented wheelset emerged in the fifties of the 20th century when method of Olson and Johnsson appeared [20]. From that time until today, the large number of technical solutions of measurement over the wheel of instrumented wheelset is developed [21]. All solutions are based on two approaches: measurement over the wheel with spokes and measurement over the standard monoblock wheel. The largest contribution to the development of instrumented wheelsets with spoked wheels gave the British Railways during the seventies and eighties of the 20th century [22–24]. The solution is based on measurement of strains using the strain gauges placed on the certain sensitive locations of spokes (Fig. 4). The strain gauges are in certain configurations connected into the Wheatstone bridges in order to obtain high sensitivity and measurement accuracy. The advantage of this method is in better sensitivity on the effects of Q force due to the higher elasticity in the vertical direction. The main drawback is a very complex and expensive machining of spokes that require high precision. This method is rarely used today, although it has long been in use in the UK and Switzerland.

Fig. 4: Instrumented wheelset based on wheels with spokes [23]

Instrumented wheelsets with measurement over the standard monoblock wheels appeared in the fifties of the 20th century. After the occurrence of method of Olson and

Johnsson, the development of such instrumented wheelsets flowed upward with the increasing of sensitivity and accuracy of measurement [25–27]. In the eighties of the 20th century in this area a significant step forward is made in region of former Yugoslavia. At that time, Jovanovic and colleagues developed instrumented wheelset based on the application of strain gauges placed on the standard monoblock wheels [28]. Measurement of wheel-rail contact forces using the instrumented wheelsets based on the standard monoblock wheels is today most common method that is widely used [29–34].

The key advantage of vehicle-side measurement is that it allows continuous measurement. The main disadvantage is that the measuring system is connected with one wheelset. Since the design of wheelsets for different types of railway vehicles can vary significantly, the instrumented wheelsets must be adapted to the specific types of vehicles or bogies. This causes the high costs of their development and production.

2. FORMULATION OF PROBLEM OF CONTINUOUS MEASUREMENT OF WHEEL-RAIL CONTACT FORCES AND CONTACT POINT POSITION

The basic problem in measuring of wheel-rail contact forces consists in the fact that these forces cannot be measured directly in the contact surface between wheel and rail. Consequently, these forces are determined indirectly based on measurement of strains of structures which are located in the vicinity of the contact surface. In the measuring systems from the vehicle side, measurement is usually carried out through the wheel as an element of railway vehicles that is exposed to the greatest loads due to the effect of given forces. Measurement of wheel strains using strain gauges enables indirectly determination of wheel-rail contact forces using an algorithm. The main problem of all indirect methods comes from the fact that the wheel strains are not arise only as a result of actions of lateral and vertical forces to be measured, but they are at the same time affected by the various other parameters. Taking into account and the proper understanding of the effects of these parameters is a key prerequisite for development of high-quality method for experimental determination of wheel-rail contact forces and achieving a high measurement accuracy.

The wheel strains during running are caused by the following forces in the wheel-rail contact: vertical force Q , lateral force Y and longitudinal force X . In addition, these strains are affected with: contact point position y_{cp} , wear of wheel profile w , angular velocity of the wheel ω and

temperature field T . The dependence of wheel strain in point j from the mentioned parameters can be expressed as follows [8]:

$$\varepsilon_j = f(Q, Y, X, y_{cp}, w, \omega, T) \quad (1)$$

Thus, on the basis of wheel strains or signals from Wheatstone bridges, which are mixed due to the influence of all mentioned parameters, it is necessary to determine indirectly the values of unknown parameters Q , Y and y_{cp} . This problem belongs to the group of inverse identification problems and it can be schematically represented as shown in Fig. 5.

Due to the high stiffness of the wheel, strains which are registered by strain gauges have very low values, particularly at the effect of Q force. There is very important problem how to obtain the highest possible values of the signals from Wheatstone bridges and increase signal-to-noise ratio. Bearing in mind that strains are changeable along the wheel body, it is extremely important to determine locations or radial distances with highest sensitivity to the effects of parameters to be measured. Placing the strain gauges on such locations provides greater sensitivity of the measuring system or higher values of output signals from Wheatstone bridges. If the strain gauges are placed at locations with insufficient sensitivity, small values of the output signals will be obtained, which will lead to the great signal-to-noise ratio and large measurement error. In addition, very important problem is determination of optimal layout, number and way of connection of strain gauges, also in order to obtain the highest possible values of output signals, or with the aim of compensating of influence of the certain parameters from expression (1). So, the main prerequisite for obtaining the high measurement accuracy is interactive and quality solving of defined problems as well as the problem of development of inverse identification algorithm.

3. PRINCIPLES FOR SOLVING OF FORMULATED PROBLEM

The basis for solving of formulated problems should be the FEM model of the wheel of wheelset which is selected as platform for development of the instrumented wheelset. A key task of the model is to provide accurate determination of the stress-strain state of the wheel at actions of given parameters defined in expression (1). This allows the identification of influence of given parameters on the wheel strains or signals from Wheatstone bridges, which is of crucial importance for quality solution of the problem and obtaining high

Figure 5: Inverse identification problem in measurement of wheel-rail contact forces and contact point position

measurement accuracy. The model should enable accurate identification of optimal locations of strain gauges, as well as their optimal layout, number and way of connection. In addition, it should enable testing and verification of developed algorithm of inverse identification. In this way, the costs of development of instrumented wheelset are significantly reduced. An example of stress-strain state of the wheel obtained with the FEM calculation is shown in Fig. 6.

Fig. 6: Example of stress-strain state of the wheel obtained with the FEM calculation [8]

Of all parameters in expression (1), only the influence of longitudinal force X can be neglected. The reasons lie in the facts that instrumented wheelsets are primarily intended for testing of hauled vehicles in which this force has no significant values, and that measurement of this force is not prescribed in the certification process according to the mentioned international standards. It is significant to point out that standards do not require measurement of the contact point position in certification process of railway vehicles. However, this parameter has a certain influence on wheel strains and must be taken into

account in order to achieve high measurement accuracy of Q and Y forces. The influence of parameter w is manifested by changing of wheel profile during a certain period of exploitation of instrumented wheelset. In order to achieve a high measurement accuracy, influence of this parameter should be taken into account in inverse identification algorithm [8]. Finally, influences of parameters ω and T on output signals from Wheatstone bridges should be compensated via appropriate way of connection of strain gauges [8]. In this way, the signal from Wheatstone bridge which is placed at certain radial distance becomes the following function:

$$S_m = f(Q, Y, y_{cp}) \quad (2)$$

Therefore, based on output signals from Wheatstone bridges, three unknown parameters Q , Y and y_{cp} should be determined. Bearing in mind that each strain gauge registers the relative strain ε , and the fact that the wheel is in zone of elasticity, according to the Hooke's law there will be a linear relationship between stress or wheel-rail contact force and the registered strain. The same is true for Wheatstone bridge that is composed of multiple strain gauges. Since the relationship between registered strain of every individual strain gauge and applied force is linear, correlation between the signal from Wheatstone bridge and applied wheel-rail contact force will be also linear. On this basis, the dependence of signal S_m from Q force and Y force is linear in expression (2). However, the key problem arise from the fact that, due to the complex non-linear geometry of the wheel profile, the dependence of the signal S_m from the contact point position y_{cp} is nonlinear. This non-linear relationship can be transformed into linear by introduction of moment M of Q and Y forces with respect to the nominal contact point (Fig. 7).

Fig. 7: The moment M of Q and Y forces with respect to the nominal contact point position

Moment M is in fact a non-linear function of parameters Q , Y and y_{cp} [8]:

$$M = -Q \cdot y_{cp} - Y \cdot z_{cp} \quad (3)$$

For development of FEM model and stress-strain analysis of the wheel, of crucial importance is that mentioned linear relationships allow that, for arbitrary chosen contact point position, the total strain can be expressed as sum of individual strains caused by the individual actions of Q and Y forces. Mathematically, this can be expressed as follows:

$$\varepsilon_t = \varepsilon_t(Q, Y) = \varepsilon_t(Q, 0) + \varepsilon_t(0, Y) \quad (4)$$

Thus, in formed FEM model, stresses and strains of the wheel can be analysed at individual actions of Q and Y forces in different contact point positions (Fig. 8).

The primary objective of stress-strain analysis is to determine locations with the greatest sensitivity to the individual actions of parameters to be measured (vertical force Q , lateral force Y and contact point position y_{cp}),

where there is no mixing of their influences in the values of the wheel strains or output signals from Wheatstone bridges. Placing the strain gauges on radial distances with high sensitivity and without mixing of influence provide the establishment of a very simple mathematical dependence between the output measuring signal and unknown force that caused it. This dependence is determined by the calibration of the measuring system which can be realized on special test stand or by using the results obtained with the FEM model of the wheel. In this case, the inverse identification algorithm is relatively simple. Based on the value of a measuring signal from radial distance that is the most sensitive to the effect of given force, its value is determined. However, if for a given wheel geometry there are no such locations, or if the output signal obtained from the Wheatstone bridge (placed on the radial distance with the greatest sensitivity to the certain parameter) is mixed due to the influence of other parameters to be measured, troubleshooting is significantly complicated. It is very important to emphasize that if this problem is not identified, measurement will be carried out with a large error.

Fig. 8: The consequence of linear relationships between wheel strains and forces Q and Y

In order to achieve high measurement accuracy, one of the solutions is compensation or neutralization the influence of mixing with the appropriate way of connecting of strain gauges into Wheatstone bridges. Thereby, it should bear in mind that mixing can never be completely neutralized. The second approach involves using some of the methods that allow determination of individual influences of parameters to be measured, based on the values of mixed output signals from Wheatstone bridges. In this case, the radial distances with the highest sensitivity should be selected, regardless of the degree of mixing of the influence of parameters to be measured.

So, the way of solution of all these problems depends on the results of stress-strain analysis obtained from the model of specific type of wheel of standard wheelset which is chosen as a platform for development of instrumented wheelset. The results of the stress-strain analysis and FEM model should be verified with the experimental tests on real object, or wheel of the selected wheelset.

4. CONCLUSION

The experimental testing is the most reliable way to determine the parameters of dynamic behaviour of railway vehicles, especially those most important – wheel-rail contact forces. There is no universal method or technical solution for measurement of these forces. Also, there is no universal technical solution of instrumented wheelset which can be characterized as the best. Every method and

technical solution, depending on a purpose and technical characteristics, have certain advantages and disadvantages compared to the others. In that sense, the aim of this paper was to define the basics for solution of problem of measurement of wheel-rail contact forces and contact point position using instrumented wheelsets. The key problems in development of instrumented wheelsets are identified. They are related to the determination of optimal layout, number and way of connection of strain gauges, as well as the development of inverse identification algorithm. The special attention is dedicated to the importance of development of the FEM model of the wheel, which is basis for solving all these problems. The results of this paper give very important guidelines for optimal solving of formulated problems, which is main prerequisite for development of instrumented wheelsets of high accuracy.

ACKNOWLEDGEMENTS

The authors wish to express their gratitude to Serbian Ministry of Education, Science and Technology for supporting this paper through project TR35038.

REFERENCES

- [1] V.K. Garg, R.V. Dukkipati, "Dynamics of Railway Vehicle Systems", Academic Press, Toronto, (1984)
- [2] A.H. Wickens, "Fundamentals of Rail Vehicle Dynamics – Guidance and Stability", Swets & Zeitlinger Publishers, Lisse, (2003)
- [3] S.D. Iwnicki, "Handbook of Railway Vehicle Dynamics", CRC Press, Taylor & Francis Group, Boca Raton, (2006)
- [4] E. Andersson, M. Berg, S. Stichel, "Rail Vehicle Dynamics", Railway Group KTH, Stockholm, (2007)
- [5] S.Z. Meymand, A. Keylin, M. Ahmadian, "A survey of wheel-rail contact models for rail vehicles", *Vehicle System Dynamics*, 54(3), pp. 386-428, (2016)
- [6] D. Milković, G. Simić, Ž. Jakovljević, J. Tanasković, V. Lučanin, "Wayside system for wheel-rail contact forces measurements", *Measurement*, 46, pp. 3308-3318, (2013)
- [7] M. Brunera, M. Catenab, D. Cortisa, G. Malavasia, S. Rossib, M. Testab, "Estimation of the wheel-rail lateral contact force through the analysis of the rail web bending strains", *Measurement*, 99, pp. 23-35, (2017)
- [8] M. Bizic, "Research of influential parameters in wheel-rail interaction on running stability of railway vehicles", PhD Thesis, Faculty of Mechanical and Civil Engineering in Kraljevo, University of Kragujevac, Serbia, (2015), (in Serbian)
- [9] UIC CODE 518 OR, "Testing and approval of Railway vehicles from the point of view of their dynamic behaviour – Safety – Track fatigue – Running behaviour", 4th edition, International Union of Railways – UIC, (2009)
- [10] EN 14363, "Railway applications – Testing for the acceptance of running characteristics of railway vehicles – Testing of running behaviour and stationary tests", European Committee for Standardization – CEN, (2005)

- [11] Y.Q. Sun, C. Cole, M. Spiriyagin, "Monitoring vertical wheel-rail contact forces based on freight wagon inverse modelling", *Advances in Mechanical Engineering*, 7(5), pp. 1-11, (2015)
- [12] J. Zeng, L. Wei, P. Wu, "Safety evaluation for railway vehicles using an improved indirect measurement method of wheel-rail forces", *J. Mod. Transport*, 24(2), pp. 114-123, (2016)
- [13] M. Bizic, M. Tomic, Z. DjinoVIC, D. Petrovic, "Test stand for calibration of measurement railway wheelsets", *Proceedings of the 7th International Conference Research and Development of Mechanical Elements and Systems – "IRMES 2011"*, Zlatibor, Serbia, pp. 419-424, (2011)
- [14] L. Binbin, S. Bruni, "A method for testing railway wheel sets on a full-scale roller rig", *Vehicle System Dynamics*, 53(9), pp. 1331-1348, (2015)
- [15] M. Bizic, D. Petrovic, "Methodologies of experimental determination of wheel-rail contact forces", *Proceedings of the XVI International Scientific-Expert Conference on Railways – "RAILCON 2014"*, Niš, Serbia, pp. 157-160, (2014)
- [16] ORE B55/RP4, "Two axled wagons subjected to simultaneous stresses due to track distortion and to transverse components of the forces of the automatic coupler; Dynamic effects of track distortions", Office for Research and Experiments, Utrecht, Netherlands, (1970)
- [17] M. Zeilhofer, G. Sühsmuth, G. Piwenitzky, "Ermittlung der Kräfte zwischen Rad und Schiene aus den Biegedehnungen der Radsatzwelle", *ZEV - Glasers Annalen*, 96(12), pp. 373-385, (1972)
- [18] H.H. Zuck, "Determination of Wheel/Rail Forces by Means of Measuring Wheelsets on Deutsche Bundesbahn", *Proceedings of the International Conference on Wheel/Rail Load and Displacement Measurement Techniques*, Transportation Systems Center, Cambridge, Massachusetts, pp. 7.1-7.22, (1981)
- [19] H. Berg, G. Gößling, H. Zück, "Radsatzwelle und Radscheibe – die richtige Kombination zur Messung der Kräfte zwischen Rad und Schiene", *ZEV - Glasers Annalen*, 120(2), pp. 40-47, (1996)
- [20] P.E. Olson, S. Johnsson, "Seit enkräfte zwischen Rad und Schiene", *Glasers Annalen*, pp. 153-161, (1959)
- [21] A. Bracciali, F. Cavaliere, M. Macherelli, "Review of Instrumented Wheelset Technology and Applications", *Proceedings of the Second International Conference on Railway Technology: Research, Development and Maintenance*, Civil-Comp Press, Stirlingshire, Scotland, Paper 167, pp. 1-16, (2014)
- [22] A.R. Pocklington, R.A. Allen, "Improved Data from Load-Measuring Wheels", *Railway engineering*, 2(4), Institute of Mechanical Engineers, pp. 37-43, (1977)
- [23] R.A. Allen, "A Superior Instrumented Wheelset", *Wheel/Rail Dynamics Society*, (1980)
- [24] Pocklington A.R., "The B. R. Load Measuring Wheel", *Proceedings of the International Conference on Wheel/Rail Load and Displacement Measurement Techniques*, Transportation Systems Center, Cambridge, Massachusetts, pp. 4.1-4.30, (1981)
- [25] J. Modransky, W.J. Donnelly, S.P. Novak, K.R. Smith, "Instrumented Locomotive Wheels for Continuous Measurement of Vertical and Lateral Loads", *ASME, Paper no. 79-RT-8*, (1979)
- [26] C.A. Swenson, K.R. Smith, "Development and Use of Instrumented Locomotive Wheelsets", *Proceedings of the International Conference on Wheel/Rail Load and Displacement Measurement Techniques*, Transportation Systems Center, Cambridge, Massachusetts, pp. 5.1-5.10, (1981)
- [27] P. Boyd, K. Kesler, T.L. Yang, "Measurement Techniques for Onboard Wheel/Rail Loads", *Proceedings of the International Conference on Wheel/Rail Load and Displacement Measurement Techniques*, Transportation Systems Center, Cambridge, Massachusetts, pp. 1.1-1.36, (1981)
- [28] R. Jovanović, "Naučno-istraživački projekat: Iznalaženje metoda određivanja sila u tački dodira vagonkog točka i šine pomoću tenzometara i računara", *ŽTO Sarajevo – Institut za saobraćaj Sarajevo – Zavod za kibernetiku saobraćaja Doboj, Doboj*, (1985)
- [29] D.E. Otter, M.A. El-Sibaie, R.L. Higgins, "A design for next generation load measuring wheel sets", *Proceedings of the 1991 IEEE/ASME Joint Railroad Conference*, St. Louis, Missouri, pp. 37-42, (1991)
- [30] H. Kanehara, T. Fujioka, "Measuring rail/wheel contact points of running railway vehicles", *Wear*, 253, pp. 275-283, (2002)
- [31] J.C.O. Nielsen, "High-frequency vertical wheel-rail contact forces – Validation of a prediction model by field testing", *Wear*, 265, pp. 1465-1471, (2008)
- [32] P. Gullers, L. Andersson, R. Lunden, "High-frequency vertical wheel-rail contact forces – Field measurements and influence of track irregularities", *Wear*, 265, pp. 1472-1478, (2008)
- [33] E. Magel, A. Tajaddini, M. Trosino, J. Kalousek, "Traction, forces, wheel climb and damage in high-speed railway operations", *Wear*, 265, pp. 1446-1451, (2008)
- [34] Y.S. Ham, D.H. Lee, S.J. Kwon, W.H. You, T.Y. Oh, "Continuous Measurement of Interaction Forces between Wheel and Rail", *International Journal of Precision Engineering and Manufacturing*, 10(1), pp. 35-39, (2009)