Metaheuristički algoritmi za rešavanje fleksibilnog problema raspoređivanja radnih mesta

Aleksandar Stanković¹, Goran Petrović¹, Danijel Marković¹, Žarko Čojbašić¹, Nikola Simić²

¹Mašinski fakultet u Nišu, Univerzitet u Niš, Srbija

²Fakultet inženjerskih nauka, Univerzitet u Kragujevcu, Srbija

Problem fleksibilnog planiranja radnih mesta (FJSP) je modifikacija klasičnog problema zakazivanja radnih mesta. Rad se bavi problemom fleksibilnog raspoređivanja radnih mesta i obrade operacija na jednoj mašini iz skupa alternativnih mašina. Problem raspoređivanja fleksibilnih radnih mesta u realnom vremenu spada u grupi teških NP-problema (Nedeterminisano polinomno vreme). Motiv rada je prikazati primenu meta-heurističkih algoritama na primeru fleksibilnog zakazivanja radnih mesta i predstaviti budućim studijama odgovarajuću metodu. Da bi se rešio ovaj problem korišćena su dva meta-heuristička algoritma i to: Optimizacija rojem čestica (PSO) i Veštačka pčelinja kolonija (ABC). Cilj rada je povećati produktivnost proizvodnje a smanjiti ukupno vreme završetka svih poslova. Parametri koji pokazuju uspešnost metode su: brzina konvergacionog rešenja u nizu iteracija, minimizacija ukupnog vremena raspoređivanja na alternativnom setu mašina i minimizacija ukupnog vremena zakazivanja. Problem raspoređivanja fleksibilnih radnih mesta ima veliku primenu, a ovim testom predlažemo algoritam za rešavanje ovakvog problema.

Ključne reči: Fleksibilni poslovi, Meta-heuristički algoritmi, Planiranje i zakazovanje, Pregled literature

1. UVOD

Planiranje proizvodnje i proizvodnih procesa ima veoma važnu ulogu u poboljšanju i uspešnom radu proizvodnje. Takođe, sve veći broj istraživača se bavi problemom planiranja i zakazivanja resursa. Ranije su istraživači koristili metode linearnog programiranja, ali zbog ograničenja da se bave obimnim problemima raspoređivanja došlo se do metoda koje spadaju u grupu veštačke inteligencije kao i metoda simulacija koje se danas veoma često koriste pri rešavanju problema planiranja i zakazivanja resursa. Ključni razlog raspoređivanja resursa je optimizacija ukupnog vremena raspoređivanja i maksimalna produktivnost proizvodnje. Problem raspoređivanja resursa i metode koje se koriste za rešavanje ove vrste problema dobijaju sve veću primenu u mnogim oblastima logistike, planiranja, pretraživanja kao i u oblasti rutiranja gde je ova metodologija veoma značajna [1]. Cilj rada se ogleda u uspešnoj primeni meta-heurističkih algoritama na primeru raspoređivanja poslova na dostupnom skupu mašina. U istraživačkoj literaturi mogu se videti mnogi primeri FJS problema sa jednim meta heurističkim algoritmom. Na osnovu toga dolazi se do motiva primene više meta-heurističkih algoritama na primeru Job Shop problema za različite probleme optimizacije počevši od brzine konvergacionog rešenja kroz niz iteracija pa do testiranja istih, počevši od problema malih dimenzija pa sve do robusnih FJS problema sa velikim setom podataka [2]. Takođe, potrebno je napomenuti da problem FJS predstavlja jedan od najtežih NP problema u kombinatornoj optimizaciji. Problem raspoređivanja radnih mesta ima veliku primenu u proizvodnom okruženju pa samim tim predloženom optimizacijom problema, na osnovu više meta-heurističkih algoritama predlaže se jedan od nekoliko algoritama za buduće studije prilikom rešavanja problema raspoređivanja.

2. PREGLED LITERATURE

Problem planiranja i raspoređivanja resursa moguće je rešavati uz pomoć mnogih metoda koje daju dovoljno dobro optimalno rešenje. Kao i što se moglo videti u prethodnom delu rada govori se o tome da većina problema raspoređivanja spada u grupu NP- teških problema, mogućim metodama rešavanja problema planiranja resursa. Prema tome načini rešavanja ovakve vrste problema dele se na nekoliko metoda, što se može videti na slici 1:

Slika 1: Metode rešavanja problema raspoređivanja i zakazivanja

2.1. Veštačka inteligencija

Ovakav pristup rešavanja problema spada u grupu težih NP- problema i karakteriše ga programiranje ograničenja prilikom rešavanja realnih problema u industrijskim sistemima planiranja i zakazivanja. U ovoj kategoriji rešavanja problema koristi se veliki broj različitih softvera uz kojih je moguće programiranje ograničenja pri rešavanju problema zakazivanja, a ovakav pristup rešavanja nastao je u oblasti veštačke inteligencije.

Programski jezici koji se danas najčešće koriste za rešavanje problema planiranja i zakazivanja u oblasti veštačke inteligencije su: MatLab, Python, C, C++, C#, Java i mnogi drugi. Kada govorimo o programiranju ograničenja prilikom rešavanja problema planiranja i zakazivanja u velikoj meri su zastupljene meta-heurističke metode. Najpoznatiji algoritmi koji spadaju u grupu meta-

heurističkih metoda a u velikoj meri se koriste za rešavanje problema planiranja i zakazivanja resursa su: Genetic Algorithm (GA), Ant Colony Optimization (ACO), Simulated Annealing (SA), Tabu Search (TS) i Particle Swarm Optimization (PSO).

Tehnike programiranja ograničenja mogu se primeniti na problemu planiranja i zakazivanja resursa na različitim primerima u zavisnosti od funkcije cilja. Programiranje ograničenja sa funkcijom cilja označava vremenski trenutak završetka poslednjeg proizvoda koji se obrađuje i obeležava se sa C_{max} što predstavlja ukupnu kriterijumsku vrednost funkcije.

2.1.1 Fleksibilni problem raspoređivanja

Problem FJSP predstavlja proširenje klasičnog problema Job Shop na problem u kojem postoji mogućnost fleksibilnosti izvršavanja operacija na setu alternativnih mašina. Osnovna razlika od klasičnog problema Job Shop u kome su operacije fiksirane po redosledu mašina i unapred definisane, kod problema FJSP postoji fleksibilnost jer, raspored operacija mašina nije unapred određen, već set mašina ima mogućnost izvršavanja više operacija na jednoj mašini. Problem se sastoji od dodeljivanja skupa operacija u okviru posla na skupu alternativnih mašina tako da je maksimalno vreme dodeljivanja operacija stroju mašina svedeno na minimum. FJSP se dodatno može razvrstati prema stepenu fleksibilnosti u pogledu zakazivanja operacija na skupu mašina [3]:

- Totalni FJSP gde svaka od operacija ima mogućnost potpune fleksibilnosti tokom zakazivanja na skupu alternativnih mašina.
- Delimični FJSP predstavlja problem zakazivanja gde neke od operacija se mogu izvršiti samo jednom delu raspoloživih mašina.

U daljem delu rada je prikazana detaljna analiza radova i pregled literature na razmatranom Flexible Job-Shop Problem-u.

U radu [4] Haojie Ding i Xingsheng Gu su predstavili primenu poboljšanog algoritma optimizacije putem rojem čestica iz grupe meta-heurističkih algoritama za rešavanje problema fleksibilnog planiranja poslova. Poboljšanje navedenog algoritma se sastoji u boljoj komunikaciji između čestica prilikom pretraživanja lokanog prostora mogućih rešenja. Eksperimentalni rezultati algoritma optimizacije putem rojem čestica u poređenju sa drugim meta-heurističkim algoritmima na problemu zakazivanja pokazuju uspešnost prilikom rešavanja problema fleksibilnog planiranja poslova. Autori rada izlaze parametre u obliku rezultata prikazuju putem Gant karte. Takođe treba napomenuti da autori u radu navode da prilikom optimizacije problema, putem algoritma optimizacije rojem čestica treba voditi računa o podešavanju parametra i donošenja odluka u vidu pretraživanja. Stoga u daljim istraživanju problema zakazivanja navode dalje proširenje algoritma i proširenje problema fleksibilnog planiranja poslova.

Ahmad Ebrahimi i saradnici u radu [5] razmatraju problem minimizacije ukupnih troškova energije i kašnjenja za problem fleksibilnog zakazivanja posla. U radu je predstavljena međuzavisnost između zakazivanje poslova i rasporeda mašina, a međusobno su povezani u poboljšanju energije i mera produktivnosti. Međuzavisnost

se ogleda u vidu vremena transporta između zakazivanja operacija i optimizacije posla na mašini. Autori predlažu model optimizacije koji uključuje zavisnost energije implementorana zajedno sa rasporedom zakazivanja. Definisana ciljna funkcija minimizuje troškove energije u vidu kazne tokom kašnjenja posla, koji se kontroliše u fleksibilnom sistemu radnih mesta. Predloženi integrisani model smanjuje ukupne troškove energije u proseku za oko 0,16 %, a vreme kašnjenja za oko 5,34% u proseku. Sumirani rezultati pokazuju uspešnost predloženog integrisanog modela u odnosu na druge algoritme za oko 5,17%. Takođe u radu možemo videti i neintegrisani model koji je u suprotnosti sa integrisanom metodom, a osnovni cilj neintegrisane metode je da kontroliše samo zakazivanje operacija kako bi se smanjila ciljna funkcija C_{max} . Treba napomenuti da integrisana metoda i njena efikasnost je potvrđena samo za slučajeve malih dimenzija. Autori zbog složenosti problema optimizacije predlažu četiri hibridna meta-heuristička algoritma. Efikasnost i performanse predloženih meta-heuristika ocenjene su u smislu vrednosti ciljne funkcije i ukupnog vremena potrebnog računaru. Kombinacijom dva meta-heuristička algoritma, optimizacija kolonijom mrava i simularnog kaljenja, autori dolaze do optimalnih rezultata za probleme zakazivanja velikih dimenzija. Eksperimentalni rezultati optimizacijom kolonijom mrava i simularnog kaljenja pokazuju da su prosečne vrednosti ciljne funkcije dobijene integrisanim modelom za 5% bolje od one dobijene neintegrisanom metodom.

Rylan H. Caldeira i A. Gnanavelbabu su u radu [6] predložili Java algoritam za rešavanja problema fleksibilnog planiranja poslova. Rešavani problem je testiran kao varijanta sa vremenskim ograničenjem operacija i minimizaciji ukupnog vremena zakazivanja. Predloženi Java algoritam autori upoređuju sa drugim poznatim meta-heuristikama na 203 referentna slučaja i zaključuje se efikasnost algoritma za probleme zakazivanja. U prvom delu rada autori daju pregled literature kao i implementaciju Java algoritma kroz niz koraka, a nakon toga je predstavljena formulacija problema sa svim potrebnim parametrima. Rad se bavi razmatranjem problema zakazivanja u stvarnom svetu, na konkretnom primeru izrada komponenti spojnice u vidu operacija koje je potrebno rasporediti na dostupnim mašinama. Vremena obrade operacija prikazana su u Tabelama. Takođe, treba napomenuti da se vremena obrade operacija razlikuju na sličnim mašinama. Studija slučaja se sastoji od ulaznih naloga za posao i to od 9 poslova, 7 mašina i 30 operacija. Rezultati predloženog Java algoritma pokazuju efikasnost algoritma, a optimalna vrednost dobijena algoritmom na osnovu kriterijumske funkcije C_{max} u vidu Gantovog grafikona iznosi 35 jedinica. U zaključku rada autori navode prednosti algoritma i optimalnost algoritma za druge probleme u vidu proizvodnog zakazivanja.

Guohui Zhang i sardnici u radu [7] predstavljaju poboljšani genetski algoritam za rešavanje problema fleksibilnog planiranja poslova sa višestrukim vremenskim ograničenjima. Autori rada navode jedan veoma bitan segment u okviru vremenskih ograničenja tokom raspoređivanja koji ukazuje na vremenska ograničenja tokom transporta do druge mašine, kao i pripremu mašine za izvršavanje drugog posla. U prvom delu rada

predstavljen je problem dok u drugom delu rada možemo videti predloženi algoritam i cilj optimizacije u vidu minimizacije vremena izrade, ukupnog vremena kao i minimizacija ukupnog vremena transporta operacija između mašina. Poboľšani algoritma ostvaruje se kroz nekoliko faza u vidu početne populacije, usvojenih dobrih rešenja sa veštačkom inteligencijom i mehanizmom sa dinamičkom izmenom mutacije i raspona pretraživanja mogućih rešenja. U poređenju sa drugim publikovanim algoritimima predloženi algoritam daje odlične rezultate i pokazuje relevantnost dobijenih rezultata za rešavanje problema zakazivanja.

Bilel Marzoukia sa radnicima u radu [8] opisuje problem zakazivanja i planiranja poslova na skupu mašinama sa skupom operacija gde svaka od definisanih operacija jednog posla ima ograničeno procesno vreme izvršavanja na mašini. Cilj rada je pravilno rasporediti poslove na dostupnim mašinama kako bi ukupno procečno vreme bilo minimalno, na osnovu kriterijumske funkcije C_{max} . Sličan način rešavanja ovakve vrste problema sa ograničenjima u vidu fleksibilnosti planiranja poslova i uslova mogućnosti izvršavanja datih operacija sa predviđenim vremnom obrade na mašinama može se videti u radu [9] gde autor sa svojim saradnicima koristi programski jezik python i detaljno objašnjava problem planiranja i raspoređivanja poslova u dva slučaja: prvi deo u ovom radu se sastoji od parcijalne fleksibilnosti poslova, dok se drugi deo odnosi na potpunu fleksibilnost. Cilj ovoga rada je minimizacija ukupnom vremene obrade svih operacija i završetak svih poslova u što kraćem roku na osnovu kriterijumske funkcije C_{max} . Kompleksnost ovoga problema se odnosi u vidu dodavanja ograničenja i otežavanja rešavanja problema.

3. ALGORITMI ZA REŠAVANJE FJSP

Tačne i heurističke metode koriste se za rešavanje problema planiranja i raspoređivanja. Primena tačnih metoda ograničena je na jednostavne probleme, dok se složenije metaheurističke metode koriste za složene realne probleme. Termin metaheuristika prvi je predložio Fred Glover 1986.godine, dok je isti autor mnogo godina kasnije definisao metaheuristiku kao skup algoritamskih koncepata koji se koriste za definisanje heurističkih metoda primenljivih na širok spektar problema [10]. Metaheuristika je dizajnirana za rešavanje složenih optimizacionih problema kada druge metode optimizacije ne uspevaju efikasno da reše problem optimizacije.

Ove metode su danas prepoznatljive kao jedan od najvažnijih praktičnih pristupa u rešavanju mnogih složenih problema, a to je posebno važno za rešavanje mnogih stvarnih problema kombinatorne optimizacije, pa samim tim i primena na problemu FJSP-a. Generalno, za metaheuristiku se može reći da je heuristika višeg nivoa. U nastavku, predstavljamo dve metaheurističke metode koje su primenjene u rešavanju problema alokacije i rasporeda operacija FJSP-a.

3.1 Optimizacija rojem čestica

Algoritam za optimizaciju roja čestica (PSO) razvijen je već 1995.godine, a razvili su ga poznati naučnici Kennedy i Eberhart [11], na osnovu ponašanja roja (roj riba u prirodi).

Za razliku od ostalih metaheurističkih algoritama, rad PSO algoritma se zasniva na česticama, a konvergencija rešenja zasniva se na orijentaciji čestica. PSO je poslednjih godina našao veliku upotrebu u naučnoj literaturi i pokazao se jednim od korisnih algoritama koji pružaju optimalno rešenje pri rešavanju problema sa ograničenjima kao što je ova studija slučaja. Karakteriše ga jedna faza tokom traženja rešenja, ali i dva ključna faktora prilikom traženja rešenja, a to su: brzina roja čestica i položaj čestica.

PSO algoritam predstavlja proces pronalaženja optimalnog rešenja koje se odvija na osnovu ulaznih parametara kroz niz definisanih iteracija. Na kraju svake iteracije, svaka čestica u svoje sećanje unosi sledeće dve vrednosti; (a) najbolja vrednost kriterijumske funkcije koju je čestica ikada postigla; (b) najbolja vrednost kriterijumske funkcije koju je bilo koja čestica ikada postigla. Na taj način, čestica brine i o svojim dostignućima i o dostignućima ostalih čestica sa kojima je u gomili [12]. Određivanjem svojih najboljih vrednosti (do te tačke) i najbolje otkrivene vrednosti celog roja, sve čestice menjaju brzinu kojom lete kroz svemir na svoje položaje u prostoru dozvoljenih rešenja.

Osnovni parametri koji karakterišu PSO algoritam su:

Pozicija $X_i = (x_{i1}, x_{i2}, \dots, x_{iD})$ i brzina $V_i = (v_{i1}, v_{i2}, \dots, v_{iD})$ pojedinačne čestice koje predstavljaju vektore. Pozicija X_{k+1}^i i čestica u iteraciji $k+1$ izračunava se na sledeći način:

$$X_{k+1}^i = x_i + v_{k+1}^i \Delta t, \quad (1)$$

Pri čemu je V_{k+1}^i brzina i -ih čestica u iteraciji $k+1$, a Δt je jedinični vremenski interval. Brzina V_{k+1}^i je jednaka:

$$V_{k+1}^i = \omega V_k^i + c_1 r_1 * (P_{Bi} - X_{ik}) / \Delta t + c_2 r_2 * (P_{gi} - X_{ik}) / \Delta t \quad (2)$$

gde je:

ω - "inertnost" čestice.

r_1, r_2 - slučajni brojevi (nezavisno jedan od drugog) iz jedinice intervala $[0,1]$,

c_1, c_2 - parametri "poverenja" (parametar c_1 pokazuje koliko čestica veruje sebi, a parametar c_2 koliko čestica veruje grupi čestica),

Δt - vremenski interval jedinice,

P_{Bi} - najbolji ikad otkriveni položaj i čestice,

P_{gi} - najbolja ikada otkrivena pozicija bilo koje čestice.

Parametri c_1 i c_2 se takođe mogu primeniti kao parametri za učenje, jer svaka čestica neprestano uči rezultate svojih odluka, kao i najbolje rezultate postignute u grupi čestica. Na taj način čestice uče kako donositi dobre odluke u budućnosti.

Početni parametri PSO algoritma postavljaju se nezavisno u zavisnosti od broja iteracija i kvaliteta dobijenog rešenja. Pseudo-kod PSO algoritma predstavljen je u Tabeli 1 [13].

Tabela 1: Pseudo kod PSO algoritma

Pseudo kod Optimizacije Rojem Čestica
Funkcija cilja $f(x)$, $x = (x_1, \dots, x_p)^T$
Inicijalizujte lokacije x_i i brzinu v_i od n čestica.
Pronadj g^* od $\min \{f(x_1), \dots, f(x_n)\}$ (at $t = 0$)

```

While (kriterijum)
t = t+1 (pseudo vreme ili broj iteracija)
  for petlju preko svih n čestica i svih p dimenzija
  Generišite novu brzinu  $v^{t+1}_i$  koristeći jednačinu
  Izračunajte nove lokacije  $x^{t+1}_i = x^t_i + v^{t+1}_i$ 
  Procenite ciljne funkcije na novim lokacijama  $x^{t+1}_i$ 
  Nađite trenutno najbolje rešenje za svaku česticu  $x^*_i$ 
  end for
  Završite trenutno najbolji globalni  $g^*$ 
end while
Iznesite konačne rezultate  $x^*_i$  i  $g^*$ 

```

3.1 Optimizacija kolonijom pčela

Algoritam veštačkih pčelinih kolonija (ABC) je razvio Karaboga 2005.godine. Od tada su Karaboga i Basturk sistematski proučavali učinak ABC algoritma koji se odnosi na neograničene probleme optimizacije i njegovo proširenje na neograničene optimizacije.

U algoritmu ABC, pčele u koloniji su podeljene u tri grupe: zaposlene pčele - (pčele koje traže hranu), pčele posmatrači - (pčele posmatrači) i izviđači. Za svaki izvor hrane postoji samo jedna zaposlena pčela. To će reći, broj zaposlenih pčela jednak je broju izvora hrane. Zaposlena pčela na mestu odbačene hrane primorana je da postane izviđač za nasumično traženje novih izvora hrane [13].

Zaposlene pčele razmenjuju informacije sa pčelama promatračima u košnici kako bi pčele promatračice mogle da biraju izvor hrane za ishranu. Za razliku od algoritma medonosnih pčela koji ima dve grupe pčela (pčele tragači hrane i pčele posmatrače), pčele u ABC algoritmu su više specijalizovane. Ciljna funkcija $f(x)$ može se kodirati kao $F(x)$ i predstavlja količinu nektara na lokaciji x , pa verovatnoća P_i promatračke pčele odabere da ide do željenog izvora hrane na x_i , a može se definisati sa:

$$P_i = \frac{F(x_i)}{\sum_{j=1}^S F(x_j)} \quad (3)$$

gde je S broj izvora hrane. Za određeni izvor hrane, efikasnost unosa određuje se F/τ gde je F količina nektara, a τ vreme provedeno na izvoru hrane.

Ako se izvor hrane proba na određenom broju istraživanja bez poboljšanja, on se napušta i pčela na ovom mestu će nasumično krenuti u istraživanje novih lokacija. The pseudo-code of the ABC algorithm is presented in Table 2 [13].

Table 1: Pseudo kod of ABC algoritma

```

Veštačka Optimizacija Pčelinih Kolonija
Funkcija cilja  $f(x)$ ,  $x = (x_1, \dots, x_n)^T$  ograničenja
Kodirajte  $f(x)$  u nivou virtualnog nektara
Definišite plesnu rutinu (snagu, pravac) ili protokol
While (kriterijum)
  for petlju sa svih n dimenzija
  (ili čvorove za probleme usmeravanja i raspoređivanja)
  Generišite nova rešenja
  end for
  Komunicirajte i azurirajte optimilni skup rešenja
end while
Dekodirajte i ispišite najbolje rezultate

```

4. MATEMATIČKA FORMULACIJA PROBLEMA FLEKSIBILNE POSLOVNE RADNJE

Studija slučaja pokriva planiranje i raspoređivanje proizvodnih ciklusa povezanih sa rešenjem FJSP. Osnovna struktura problema koji se rešava, odnosi se na skup poslova koje treba obaviti na mašinama, a svaki posao se dodeljuje listi aktivnosti koje se obrađuju u redosledu. Suština problema i definisane aktivnosti je da sveukupno vreme završetka bude što je moguće niže u skladu sa planiranim operacijama sa definisanim vremenom svake operacije pojedinačno. Skup svih izvršenih operacija čine jedan proizvod (posao) gotovim, a samim tim i gotov proizvod. Matematički model FJSP može se predstaviti na sledeći način.

Potrebno je zakazati n proizvoda (poslova) $J = \{J_1, J_2, \dots, J_n\}$, pri čemu svaki posao J_j ($j = 1, 2, \dots, n$) ima unapred određeni sekventni raspored operacija n_j ($O_{1,j}, O_{2,j}, \dots, O_{n_j,j}$), skup svih operacija čine jedan gotov proizvod, potrebno je rasporediti sve operacije na alternativnom skupu mašina kako bi se postigla maksimalna produktivnost za minimalno vreme, $M = \{M_1, M_2, \dots, M_k\}$ [9].

Za potpuno fleksibilan problem, svaka mašina može istovremeno da izvede samo jednu operaciju, a vreme obrade svake operacije zavisi od dostupnih mašina i predstavljamo je sa $t_{i,j,k}$ (prosečno vreme izvršavanja operacije $O_{i,j}$ na mašini M_k). Cilj uočenog problema je dodeliti svaku operaciju odgovarajućoj mašini, a zatim odrediti optimalan raspored svih mašina dodeljenim operacijama kako bi se povećala produktivnost a minimiziralo ukupno vreme ciljne funkcije C_{max} , u ovoj studiji slučaja koritićemo dva meta-heuristička algoritma i to: PSO i ABC algoritam.

Korišćena je sledeća notacija za definisanje matematičke formulacije FJSP [14]:

4.1 Predstavljanje modela

$p_{(i)}$ – planovi procesa posla i ($p_{(i)} \in P_i$),

P_i – skup alternativnih planova procesa za posao i ,

$O_{ip(i)}$ – uređeni skup operacija u procesnom planu $p_{(i)}$ za posao i ($O_{ip(i)} \subseteq O$), gde je $O_{ip(i)ff(i)}$ prvi, a $O_{ip(i)ll(i)}$ poslednji element $O_{ip(i)}$,

O_i – skup operacija u svim procesnim planovima posla i , ($O_i = \bigcup_{p_{(i)} \in P_i} O_{ip(i)}$),

Parametri:

$t_{ip(i)jk}$ – vreme trajanja operacije $O_{ip(i)j}$ na mašini k ,

L – veliki broj,

Promenljive:

$Z_{ip(i)}$ – 1, ako je odabran procesni plan $p_{(i)}$ posao i je izabran, u suprotnom 0,

$X_{ip(i)jk}$ – 1, ako je mašina k izabrana za rad $O_{ip(i)j}$; u suprotnom 0,

$S_{ip(i)jk}$ – vreme početka rada $O_{ip(i)j}$ na mašini k ,

$C_{ip(i)jk}$ – vreme završetka operacije $O_{ip(i)j}$ na mašini k ,

$Y_{iji'j'k}$ – 1, ako operacija O_{ij} prethodi operaciji $O_{i'j'}$ na mašini k ; 0, u suprotnom,

C_i – vreme završetka posla i ,

C_{max} – maksimalno vreme završetka svih poslova (vremenski raspon)

Predloženi matematički model definisan je na sledeći način:

Cilj funkcije: Minimalizirati C_{max}

sa ograničenjima:

$$\sum_{k \in M_j} x_{ip(i)jk} = z_{ip(i)} \quad \forall i \in J, \forall p(i) \in P_i, \forall j \in O_{ip(i)}, \quad (4)$$

$$\sum_{p(i) \in P_i} z_{ip(i)} = 1 \quad \forall i \in J, \quad (5)$$

$$s_{ip(i)jk} + c_{ip(i)jk} \leq (x_{ip(i)jk}) * L \quad \forall i \in J, \forall p(i) \in O_i, \forall j \in O_{ip(i)} \quad (6)$$

$$c_{ip(i)jk} \geq s_{ip(i)jk} + t_{ip(i)jk} - (1 - x_{ip(i)jk}) * L \quad \forall i \in J, \quad (7)$$

$$\sum_{p(i) \in P_i} s_{ip(i)jk} \geq \sum_{p'(i) \in P_i} c_{ip'(i)jk} - (Y_{ij'j'k}) * L \quad (8)$$

$$\sum_{p'(i) \in P_i} s_{ip'(i)jk} \geq \sum_{p(i) \in P_i} c_{ip(i)jk} - (1 - Y_{ij'j'k}) * L \quad (9)$$

$$\sum_{k \in M_j} s_{ip(i)jk} \geq \sum_{k \in M_j} c_{ip(i)jk} \quad \forall i \in J, \forall p(i) \in P_i, \forall j \in O_{ip(i)} \quad (10)$$

$$c_i \geq \sum_{k \in M_j} c_{ip(i), O_{ip(i)}, t_{ip(i), k}} \quad \forall i \in J, \forall p(i) \in P_i \quad (11)$$

$$c_{\max} \geq c_i \quad \forall i \in J, \quad (12)$$

and

$$z_{ip(i)} \in \{0, 1\} \quad \forall i \in J, \forall p(i) \in P_i$$

$$x_{ip(i)jk} \in \{0, 1\} \quad \forall i \in J, \forall p(i) \in P_i, \forall j \in O_{ip(i)} \quad \forall k \in M_j,$$

$$s_{ip(i)jk} \geq 0 \quad \forall i \in J, \forall p(i) \in P_i, \forall j \in O_{ip(i)} \quad \forall k \in M_j,$$

$$c_{ip(i)jk} \geq 0 \quad \forall i \in J, \forall p(i) \in P_i, \forall j \in O_{ip(i)} \quad \forall k \in M_j,$$

$$Y_{ij'j'k} \in \{0, 1\} \quad \forall i < i', \forall j \in O_i, \forall j' \in O_{i'}, \forall k \in M_j \cap M_{j'},$$

$$c_i \geq 0 \quad \forall i \in J.$$

Ograničenja (4) i (5) osiguravaju da je usvojen samo jedan plan procesa i da je operacija $O_{ip(i)j}$ dodeljena samo jednoj mašini. Ako operacija $O_{ip(i)j}$ nije dodeljena mašini k , ograničenja (6) postavljaju njeno vreme početka i završetka na mašini k jednaku nuli. Ako je dodeljena, ograničenja (7) garantuju da je razlika između vremena početka i završetka najmanje vreme obrade na mašini k . Ograničenja (8) i (9) vode računa o zahtevu da se rad O_{ij} operacije $O_{ij'}$ njihovi usvojeni planovi procesa ne mogu istovremeno izvršiti na bilo kojoj mašini u skupu $M_j \cap M_{j'}$. Ograničenja (10) osiguravaju da odnosi prvenstva između operacija posla ne budu narušeni. Ograničenja (11) određuju vremena završetka poslova, a ograničenja (12) određuju raspon izrade [14]

5. STUDIJA SLUČAJA

Osnovni motiv studije slučaja je primena meta-heuristike u rešavanju problema planiranja i zakazivanja resursa sa različitim ograničenjima tokom optimizacije. Težina problema se ogleda u primeni predstavljenih ograničenja u matematičkom modelu na konkretnom primeru u proizvodnom okruženju. Cilj rada je povećati produktivnost proizvodnje.

Povećanje produktivnosti proizvodnje se ogleda u optimalnom zakazivanju operacija na setu mašina.

Problem raspoređivanja resursa u proizvodnom okruženju predstavlja jedan od teških NP problema. U literaturi mogu se naći različiti primeri raspoređivanja resursa na osnovu meta-heurističkih algoritama. U radu, za rešavanje predstavljenog matematičkog modela, korišćena su dva meta-heuristička algoritma i to: ABC i PSO. Motiv primene ova dva algoritma je međusobno poredjenje algoritama u rešavanju problema manjih obima pa sve do problema sa većim obimom podataka.

Ulazni parametri rešavanog problema sastoje se od mašina M i Operacija O . Ono što treba napomenuti je i različita fleksibilnost prilikom zakazivanja operacija. U Tabeli 1 predstavljeni su podmodeli FJSP-a sa različitom strukturom poslova i mašina.

Tabela 1: Definisani problemi

Problemi	Veličina problema (n x m)
PFJS1	5 x 5
PFJS2	10 x 5
PFJS3	10 x 10
PFJS4	15 x 10
PFJS5	20 x 15

Tabela 2: Osnovni pokazatelji ulaznih podataka

Pokazatelj	
Broj poslova (n)	5, 10, 20
Broj mašina (m)	5, 10, 15
Operacija za posao i	Uniformno[m/2, m + 1]
m_j (mašina za j-tu operaciju)	Uniformno[1, m]
t_{ijk} (i * posao j * vreme izvršenja operacije)	t_{ij1} Uniformno[1, 99]
$k \in M_j$	$t_{ij2} \dots$ Uniformno[t_{ij1} , 3 x t_{ij1}]

U tabeli 2 predstavljene su osnovne promenljive koje su jasno definisane u matematičkom modelu.

Tabela 3: Ulazne sekvence testiranih problema

Alternative process plans for jobs		
Jobs	Process plans	Operation sequence
PFJS1	5	2-3-4-5-1
		1-4-3-2-5
		5-3-4-1-2
		3-1-5-4-2
		4-2-1-5-2
PFJS2	10	2-3-1-5-4
		3-2-1-5-4
		3-4-5-1-2
		5-1-3-2-4
		5-1-2-4-3
		5-1-2-3-4
		4-3-1-5-2
		5-2-1-3-4
		5-1-4-3-2
		5-2-1-3-4
PFJS3	10	1-2-3-4-5-6-7-8-9-10
		1-3-5-10-4-2-7-6-8-9
		2-1-4-3-9-6-8-7-10-5
		2-3-1-5-7-9-8-4-10-6
		3-1-2-6-4-5-9-8-10-7
		3-2-6-4-9-10-1-7-5-8
		2-1-4-3-7-6-10-9-8-5
		3-1-2-6-5-7-9-10-8-4
		1-2-4-6-3-1-7-8-5-9
		2-1-3-7-9-10-6-4-5-8

U tabeli 3 možemo videti ulazne sekvence i početni raspored operacija na setu mašina. Primenom meta-heuristike možemo doći do boljeg rasporeda operacija a samim tim i veće produktivnosti proizvodnje.

Tabela 4: Ukupno vreme trajanja svake operacije

Jobs	Operation	M ₁	M ₂	M ₃	M ₄	M ₅					
PFJS1	5	88	-	94	85	-					
		65	35	95	69	55					
		-	45	-	71	75					
		45	-	37	78	80					
		77	68	29	-	83					
Jobs	Operation	M ₁	M ₂	M ₃	M ₄	M ₅					
PFJS2	10	-	85	-	84	-					
		21	29	18	41	50					
		-	54	-	52	-					
		37	54	74	62	57					
		57	81	61	68	30					
		81	-	89	-	11					
		-	20	91	-	66					
		24	84	32	55	-					
		-	7	54	-	39					
		40	83	19	8	-					
Jobs	Operation	M ₁	M ₂	M ₃	M ₄	M ₅	M ₆	M ₇	M ₈	M ₉	M ₁₀
PFJS3	10	-	68	19	55	59	-	62	46	34	61
		33	60	65	81	49	38	66	46	42	70
		41	-	69	44	80	-	82	69	35	-
		71	85	61	49	69	32	-	38	92	63
		24	16	22	61	-	69	21	49	72	53
		-	12	62	8	38	62	27	95	36	65
		36	67	91	63	52	71	92	39	-	45
		81	66	96	44	-	38	49	58	66	69
		96	39	-	71	25	51	50	39	46	-
		75	33	41	-	64	-	77	-	64	58

U tabeli 4 su predstavljena vremena trajanja svake operacije na mašini.

Tabela 5: Rašunski rezultati

Problem Br.	Veličina problema						Rezultati			
	Poslovi	Mašine	PPFL	RFL	Operacije	Iteracije	CPU vreme (s)		C _{max}	
							PSO	ACO	PSO	ACO
PFJS1	5	5	Low	Low	5	1000	68	65	380	380
PFJS2	10	5	Low	High	10	1000	181	185	534	534
PFJS3	10	10	Low	High	10	1000	516	518	897	914
PFJS4	15	10	High	High	15	1000	948	950	1151	1208
PFJS5	20	15	High	High	20	1000	2838	3155	763	814

Slika 2: Optimizacija rojem čestica: veličina problema 5x5

Kao što možemo videti vremena zavise od mašina na kojoj se obrađuju operacije. Potrebno je napomenuti da mašine nemaju mogućnost izvršavanja svake operacije na svakoj mašini što se i može videti u priloženoj tabeli 4.

5.1 Računski rezultati

Nakon detaljnog predstavljanja FJSP-a kroz niz preglednih radova, u drugom delu rada je predstavljen matematički model i primena meta-heurističkih algoritama. Ulazni podaci su predstavljeni u Tabeli 1, Tabeli 3 i Tabeli 4. Cilj rada je prikazati primenu ova dva algoritma za rešavanje problema planiranja i zakazivanja resursa u okviru FJSP-a. Potrebno je napomenuti da ulazne podatke koji su predstavljeni u Tabeli 3 u okviru sekvetnog rasporeda i Tabeli 4 vremena izvršavanja operacija na mašinama možemo primeniti u realnom proizvodnom okruženju.

U tabeli 5 su predstavljeni računski rezultati primenjenih algoritama i predstavljaju izlazne parametre optimizacije. Ključni izlazni parametri tokom testiranja su brzina konvergacionog rešenja CPU time (s) i ukupno jedinica kriterijumske funkcije C_{max}. Primena i testiranje ABC i PSO algoritma na primeru FJSP-a je primenjavana na niz podmodela koji su predstavljeni u Tabeli 1, početi od problema malih dimenzija jednog proizvodnog okruženja sa n = 5 poslova i m = 5 mašina pa sve do obimnih problema gde imamo n = 20 poslova i m = 15 mašina. Svaki posao ima niz operacija O_{ij} koje je potrebno izvršiti i optimalno ih rasporediti na skupu alternativnih mašina kako bi efikasnost bila što veća a vreme zakazivanja što manje u vidu kriterijumske funkcije C_{max}.

Računski rezultati koj su kao izlazni parametri predstavljeni u Tabeli 5 možemo videti i u grafičkom obliku u vidu Gant karte na Slici 2, Slici 3, Slici 4 i Slici 5.

Slika 3: Optimizacija kolonijom pčela: problem 5x5

Slika 4: Optimizacija rojem čestica: problem 20x15

Slika 5: Optimizacija kolonijom pčela: problem 20x15

6. ZAKLJUČAK

Problem rasporedjivanja resursa spada u grupi problema gde su osnovni ciljevi planiranje i zakazivanje resursa, dok u ovom slučaju zakazivanje operacija na dostupnom skupu mašina u okviru FJSP-a. Planiranje i optimizacija proizvodnih procesa predstavlja neophodan dio jednog industrijskog okruženja. Optimizacija i optimalno rasporedjivanje resursa predstavlja proces povećanja produktivnosti u što kraćem vremenskom opsegu. Za jedno proizvodno okruženje posebno je bitno pravilno planiranje i rasporedjivanje resursa. Optimizacija FJSP-a primenom meta-heurističkih algoritama predstavlja jedan od načina rešavanja problema proizvodnog okruženja i predstavljanja mogućnost novih boljih rešenja u okviru rasporedjivanja. Optimalan raspored poslova J i skup operacija O_{ij} koje pripadaju jednom poslu, na skupu mašina M može uštedeti dodatno vreme i minimizirati ukupno vreme potrebno za završetak posla J . Cilj rada je povećati produktivnost a smaniti potrebno vreme za završetak poslova kroz optimalan raspored i pravilno zakazivanje operacija na mašinama. Primenom ABC i PSO algoritma dobili smo maksimalnu produktivnost proizvodnje, optimalan raspored operacija i minimlanu vrednost kriterijumske funkcije C_{max} . Takođe, treba napomenuti bolje optimalne vrednosti PSO algoritma u odnosu na ABC algoritam na osnovu predstavljenih vrednosti u Tabeli 5. Što se tiče budućih istraživanja predlažemo i jedan i drugi algoritam za rešavanje problema planiranja i zakazivanja resursa u proizvodnom okruženju zbog optimalnih rezultata i minornih razlika. U daljim istraživanjima potrebno je proširiti problem, dodati dodatna ograničenja i uočiti ga u realnom vremenu. Takvi problemi biće tema budućih istraživanja koje će sprovesti autori ovog rada.

ZAHVALNOST

Ovaj istraživački rad je finansijski podržalo Ministarstvo prosvete, nauke i tehnološkog razvoja Republike Srbije kroz Ugovor o realizaciji i finansiranju naučno-istraživačkog rada u 2020. godini, čiji je evidencioni broj 451-03-68-/2020-14200109.

LITERATURA

- [1] A. Stanković, D. Marković, G. Petrović, Ž. Čojbašić, "Metaheuristics for the waste collection vehicle routing problem in urban areas", Series: Working and Living Environmental Protection Vol. 17, No1, pp. 1 – 16, (2020).
- [2] D. Marković, G. Petrović, Ž. Čojbašić, A. Stanković, "The vehicle routing problem with stochastic demands in an urban area – a case study", Facta Universitatis, Series: Mechanical Engineering Vol.18, No1, pp. 107-120, (2020).
- [3] I. A. Chaudhry, A. A. Khan, "A research survey: review of flexible job shop scheduling techniques", International Transactions in Operational Research, Vol. 23, No3, pp. 551-59, (2016).
- [4] H. Ding, X. Gu, "Hybrid of human learning optimization algorithm and particle swarm optimization algorithm with scheduling strategies for

the flexible job-shop scheduling problem", Neurocomputing, Vol. 414, No.3, Pages 313-332, (2020).

- [5] A. Ebrahimia, H. Woo, J. S. Lee, C. Wang, "Minimizing total energy cost and tardiness penalty for a scheduling-layout problem in a flexible job shop system: A comparison of four metaheuristic algorithms", Computers & Industrial Engineering, Vol.141,106295, (2020).
- [6] R. H. Caldeira, A.Gnanavelbabu, "Solving the flexible job shop scheduling problem using an improved Jaya algorithm", Computers & Industrial Engineering, Vol. 137, 106064, (2019).
- [7] G. Zhang, Y. F. Hu, J. Sun, W. Zhang, "An improved genetic algorithm for the flexible job shop scheduling problem with multiple time constraints", Swarm and Evolutionary Computation, Vol. 54,100664, (2020).
- [8] B. Marzoukia, O. B. Driss, K. Ghédira, "Solving Distributed and Flexible Job shop Scheduling Problem using a Chemical Reaction Optimization metaheuristic", Procedia Computer Science, Vol. 126, pp. 1424-1433, (2020).
- [9] A. Stanković, G. Petrović, Ž. Čojbašić, D. Marković, "An application of metaheuristic optimization algorithms for solving the flexible job-shopscheduling problem", Operational Research in Engineering Sciences: Theory and Applications, Vol. 3, Issue 3, pp. 13-28, (2020).
- [10] Glover, F. W., Kochenberger, G. A. (Eds.) Handbook of metaheuristics, Vol. 57. Springer Science & Business Media, (2006).
- [11] J. Kennedy, R. Eberhart, "Particle Swarm Optimization", Proceedings of IEEE International Conference on Neural Networks.IV. pp. 1942–1948, doi:10.1109/ICNN.1995.488968, (1995).
- [12] S.A. MirH, N. Abolghasemi, "A particle swarm optimization algorithm for open vehicle routing problem", Expert Systems with Applications, Vol.38, Issue 9, pp. 11547-11551, (2011).
- [13] X. S. Yang, "An introduction with metaheuristic applications", Engineering Optimization, University of Cambridge, United Kingdom, (2010).
- [14] C. Özgüvena, L. Özbakır, Y. Yavuz, "Mathematical models for job-shop scheduling problems with routing and process plan flexibility", Applied Mathematical Modelling, Vol. 34, Issue 6, pp. 1539-1548, (2010).

Metaheuristic Algorithms for the Flexible Job-Shop Scheduling Problem

Aleksandar Stanković¹, Goran Petrović¹, Danijel Marković¹, Žarko Čojbašić¹, Nikola Simić²

¹Faculty of Mechanical Engineering, University of Niš, Serbia

²Faculty of Engineering, University of Kragujevac, Serbia

The problem with flexible job planning (FJSP) is a modification of the classic job booking problem. This paper deals with the problem of flexible job deployment and processing of operations on one machine from a set of alternative machines. The problem of deploying flexible jobs in real time is one of a group of difficult NP problems (Non-deterministic polynomial time). The motive of this paper is to show the application of meta-heuristic algorithms on the example of flexible job schedules and present the appropriate method to future studies. To solve this problem, two meta-heuristic algorithms were used: Particle Swarm Optimization (PSO) and Artificial Bee Colony (ABC). The aim of the paper is to achieve the speed of the conversion solution in a series of iterations, minimizing the total time of deployment of jobs on an alternative set of machines, as well as minimizing the total schedule time. The problem of deploying flexible jobs has great application, and with this test we propose an algorithm for solving this problem.

Keywords: Flexible job-shop, Meta-heuristic algorithms, Planning and scheduling, Literature review

1. INTRODUCTION

Planning production and production processes plays a very important role in its improving and success. Also, a growing number of researchers are dealing with the problem of resource planning and appointments. Previously, researchers used linear programming methods, but because of restrictions on dealing with extensive deployment problems, methods that fall within the artificial intelligence group as well as simulation methods are often used to solve resource planning and appointment problems. A key reason for deploying resources is optimizing the total deployment time and maximum productivity. The problem of resource deployment and the methods used to resolve this type of problem are getting increasingly applied in many areas of logistics, planning, search, and in the area of routing where this methodology is very important [1]. The goal of the work is reflected in the successful application of meta-heuristic algorithms, such as job schedules on an available set of machines. The basic essence of the work is to display optimal and behavior algorithms for different deployment problems in terms of the scope of the problem. In research literature, you can see many examples of the Flexible Job Shop problem with a meta-heuristic algorithm. Based on this, we come up with a motive for applying multiple meta-heuristic algorithms, such as Job Shop problems for various optimization problems, ranging from the speed of the conversion solution through a series of iterations to testing them, ranging from small-dimensional problems to robust Flexible Job Shop problems with large data sets [2]. It should also be noted that the Flexible Job Shop problem is one of the most difficult NP - problems in combined optimization. It is necessary to note that the problem of job deployment has great application in the product environment and therefore the proposed optimization of the problem, based on multiple meta-heuristic algorithms is what we suggest with several algorithms for future studies when solving deployment problems.

2. LITERATURE REVIEW

The problem of planning and deploying resources can be solved with many methods that provide an optimal solution which is good enough. As you can see in the previous part of the work, most of the deployment problems fall into a group of NP-difficult problems, possible methods for solving resource planning problems. Therefore, ways of solving this type of problem are divided into several methods, as can be seen in figure 1:

Figure 1: Methods for solving scheduling and planning problems

2.1. Artificial intelligence

This troubleshooting approach is one of a group of more difficult NP - problems and is characterized by programming constraints when solving real problems in industrial planning and appointment systems. In this troubleshooting category, a number of different software is used to program restrictions on solving the problem of appointments, and this approach to solving has been created in the field of artificial intelligence.

The programming languages most commonly used today to solve planning and appointment problems in the field of artificial intelligence are: MathLab, Python, C, C++, C#, Java, and many others. When it comes to programming restrictions when solving planning and appointment problems, meta-heuristic methods are largely represented. The most famous algorithms that fall into a group of meta-heuristic methods and are widely used to troubleshoot planning and resource appointments are: Genetic Algorithm (GA), Ant Colony Optimization

(ACO), Simulated Annealing (SA), Taboo Search (TS), and Particle Swarm Optimization (PSO).

Restriction programming techniques can be applied to the problem of resource planning and appointment in different examples, depending on the goal function. Programming limitations with the goal function indicates the time frame of completion of the last product that is processed and is marked with $C_{\max}$, which represents the overall criterion value of the function.

2.1.1 Flexible Job-Shop Problem (FJSP)

The problem of FJSP is the extension of the classic Job Shop problem to an issue where there is flexibility to perform operations on a set of alternative machines. The basic difference from the classic job shop problem in which operations are fixed in order of machines and predetermined, in the case of the problem FJSP there is flexibility because the arrangement of machine operations is not predetermined, but the set of machines has the possibility of performing multiple operations on a single machine. The problem consists of assigning a set of operations within the framework of a work on a set of alternative machines so that the maximum allocation time of operations to the machine is minimized. FJSP can be further classified according to the degree of flexibility in scheduling operations on a set of machines [3]:

- Total FJSP where each of the operations has the possibility of complete flexibility during scheduling on a set of alternative machine machines.
- Partial FJSP is a scheduling problem where some of the operations can only be performed with one part of the available machines.

Further work presents a detailed analysis of the papers and a literature review on the considered Flexible Job-Shop Problem.

In the paper [4] Haojie Ding and Xingsheng Gu presented the application of an improved optimization algorithm through a swarm of particles from a group of meta-heuristic algorithms to solve the problem of flexible job planning. The improvement of the specified algorithm consists of better communication between particles when searching the local area of possible solutions. Experimental results of the particle optimization algorithm compared to other meta-heuristic algorithms on the problem of appointment show success in solving flexible job planning problems. The authors display the output parameters as results through the Gant card. It should also be noted that the authors state in the work that when optimizing problems, swarm particle optimization algorithms should be careful about adjusting parameters and making decisions in the form of searches. Therefore, further research into the problem of appointment stipulates further expansion of the algorithm and the expansion of the problem of flexible job planning.

Ahmad Ebrahimi and collaborators [5] are discussing the problem of minimizing total energy costs and delays for the problem of flexible job appointments. The work presents interdependence between scheduling jobs and machine layouts, and is interconnected in improving energy and productivity measures.

Interdependence is reflected in the time of transport between operations appointment and optimization of the machine work. The authors suggest an optimization model

that includes energy dependency implemented in conjunction with the schedule. The defined target function miniatures energy costs in the form of penalties during work delays, which are controlled in a flexible workplace system. The proposed integrated model reduces overall energy costs by an average of about 0.16 per cent and delay times by about 5.34% on average. The summate results show the success of the proposed integrated model compared to other algorithms by about 5.17%. We can also see an unintegrated model that contradicts the integrated method, and the main goal of the unintegrated method is to control only scheduling operations to reduce the $C_{\max}$ target function. It should be noted that the integrated method and its efficiency are confirmed only for small-dimensional cases. Because of the complexity of the optimization problem, the authors suggest four hybrid meta-heuristic algorithms. The efficiency and performance of the proposed meta-heuristics are evaluated in terms of the value of the target function and the total time required for your computer. By combining two meta-heuristic algorithms, optimization with ant colonies and simulated hardening, the authors come up with optimal results for large-scale appointment problems. Experimental results by optimizing the colony of ants and simulating hardening show that the average values of the target function obtained by an integrated model are 5% better than those obtained by an unintegrated method.

Rylan H. Caldeira and A. Gnanavelbabu in the work [6] proposed Java problem-solving algorithm flexible job planning. The problem that's been resolved is tested as a variant with a time limit operations and minimize the total appointment time. The proposed Java algorithm compares the authors to another known meta-heuristics on 203 reference cases and concludes the efficacy of the problem algorithm appointments. In the first part of the work, the authors, literature as well as implementation of Java algorithms through a series of steps, and then the wording of the problems with all necessary parameters. This work considers real-world appointment problems, on specific example of the production of coupling components in the form of operations that need to be deployed on the available Machines. Operation processing times are shown in Tables. It should also be noted that times processing operations vary on similar machines. Study case consists of incoming job orders of 9 jobs, 7 machines and 30 operations. Results of the proposed Java algorithms show the efficiency of the algorithm, and the optimal value derived from an algorithm based on the criteria $C_{\max}$ functions as a Gant chart is 35 units. In the conclusion of the paper, the authors state the advantages of the algorithm and the optimality of the algorithm for other problems in the form of production scheduling.

Guohui Zhang and the associates in the work [7] represent enhanced genetic problem-solving algorithm flexible planning of multi-time jobs constraints. The authors cite a very important segment within time constraints during schedules indicating time limits transport to another machine, as well as the preparation of the machine to perform another job. In the first part of the work the problem is presented while in the second part of the work we can see the proposed algorithm and the goal of optimization in the form of minimizing the time of production, total time as well as minimize the total

transport time of operations between the machines. An improved algorithm is achieved through several phases in the form of the initial population, adopted good solutions with artificial intelligence and mechanism with dynamically modified mutation and search range possible solutions. Compared to other published algorithms the proposed algorithm provides excellent results and shows the relevance of the results obtained to resolve the appointment problems.

Bilel Marzoukia with labours in the work [8] describes the problem of appointment and job planning on the set of machines with a set of operations where each of the defined job operation has a limited process time execution on the machine. The goal of the work is to arrange correctly jobs on available machines in order to minimize the time, based on the criterion function $C_{\max}$. A similar way of solving this type of problem with restrictions in the form of job planning flexibility and conditions of the ability to perform the operations in the predicted processing time on the machines can be seen in the work [9] where the author and his colleagues use the program language python and explains the problem in detail planning and deploying of jobs in two cases: part 1 in this work consists of partial flexibility of jobs, while the second part refers to complete flexibility. The goal of this work is a minimization of the total processing time of all operations and completion of all operations as soon as possible on the basis of the $C_{\max}$ criterion function. The complexity of these problems refer to adding restrictions and difficulty solving problems.

3. ALGORITHMS FOR SOLVING THE FJSP

Accurate and heuristic methods are used to solve planning and scheduling problems. The application of exact methods is limited to simple problems, while more complex meta-heuristic methods are used for complex real systems. The term meta-heuristics was first proposed by Fred Glover in 1986, while the same author defined meta-heuristics many years later as a set of algorithmic concepts used for defining heuristic methods applicable to a wide range of problems [10]. Meta-heuristics are designed to solve complex optimization problems when other optimization methods fail to effectively solve the optimization problem.

These methods are nowadays recognized as one of the most important practical approaches to solving many complex problems, and this is especially important for solving many real combinatorial optimization problems, hence the application for the FJSP problem. In general, meta-heuristics can be said to be higher level heuristics. Below we present three meta-heuristic methods that have been applied in solving the problems of allocation and scheduling of FJSP operations.

3.1 Particle Swarm Optimization

The particle swarm optimization algorithm (PSO) was developed as early as 1995 and was developed by well-known scientists Kennedy and Eberhart [11], based on swarm behaviour (a swarm of fish in natural). Unlike other meta-heuristic algorithms, PSO operation is particle-based and solution convergence is based on particle orientation. PSO has found great use in the scientific literature in recent years and has proven to be one of the

useful algorithms that provide an optimal solution when solving problems with constraints such as this similarity study. It is characterized by one phase during the search for a solution, but also two key factors when searching for the solution, namely: the rate of particle swarm and the location of the particles.

PSO is the process of finding the optimal solution that takes place based on input parameters through a series of defined iterations. At the end of each iteration, each particle innovates in its memory the following two values; (a) the best value of the criterion function the particle has ever achieved; (b) the best value of the criterion function that any particle has ever achieved. In this way, the particle takes care of both its achievements and the achievements of the other particles with which it is in the crowd [12]. By determining their best values (up to that point) and the best-revealed value of the entire swarm, all particles change their speeds through which they fly through space into their positions in space of permissible solutions.

The basic parameters that characterize the PSO algorithm are:

Positions $X_i = (x_{i1}, x_{i2}, \dots, x_{iD})$ and speed $V_i = (v_{i1}, v_{i2}, \dots, v_{iD})$ individual particles represent vectors. Position X_{k+1}^i i particles in iteration $k+1$ is calculated as follows:

$$X_{k+1}^i = x_{ik} + v_{k+1}^i \Delta t, \quad (1)$$

wherein V_{k+1}^i the velocity of the i -th particle in iteration $k+1$, a Δt unit time interval. Speed V_{k+1}^i is equal:

$$V_{k+1}^i = \omega V_k^i + c_1 r_1 * (P_{Bi} - X_{ik}) / \Delta t + c_2 r_2 * (P_g - X_{ik}) / \Delta t \quad (2)$$

wherein:

ω - "inertia" of a particle.

r_1, r_2 - random numbers (independent of each other) from the unit interval $[0, 1]$,

c_1, c_2 - "trust" parameters (parameter c_1 shows how many particles trust themselves, and parameter c_2 how many particles trust a group of particles),

Δt - unit time interval,

P_{Bi} - the best ever detected position of the i particle,

P_g - the best ever detected pose of any particle.

Parameters c_1 and c_2 can also be implemented as learning parameters since each particle is constantly learning the results of its decisions as well as the best results achieved in the particle group. In this way, particles learn how to make good decisions in the future.

The initial parameters of the PSO algorithm are set independently depending on the number of iterations and the quality of the obtained solution. The pseudo-code of the PSO algorithm is presented in Table 1 [13].

Table 1: Pseudo code of Particle Swarm Optimization

Pseudo code of particle swarm optimization
Objective function $f(x)$, $x = (x_1, \dots, x_p)^T$
Initialize locations x_i and velocity v_i of n particles.
Find g^* from $\min\{f(x_1), \dots, f(x_n)\}$ (at $t = 0$)
While (criterion)
$t = t+1$ (pseudo time or iteration counter)
for loop over all n particles and all p dimensions
Generate new velocity v^{t+1}_i using equation

```

Calculate new locations  $x^{t+1}_i = x^t_i + v^{t+1}_i$ 
Evaluate objective functions at new locations  $x^{t+1}_i$ 
Find the current best for each particle  $x^*_i$ 
end for
Find the current global best  $g^*$ 
end while
Output the final results  $x^*_i$  and  $g^*$ 

```

3.1 Artificial Bee Colony Optimization

The Artificial Bee Colonies Algorithm (ABC) is developed by Karaboga in 2005. Since then, Karaboga and Basturk have systematically studied the performance of the ABC algorithm referring to unlimited optimization problems and its expansion to unlimited optimizations. In the ABC algorithm, the bees in the colony are divided into three groups: working bees - (food-seeking bees), bees observers - (bee observers) and scouts. For each source there is only one working bee.

That means, the number of bees is equal to the number of food sources. Busy bees at the site of discarded food are forced to become Scout for random search for new food sources [13]. Working bees exchange information with bees beekeepers in the hive so that the bees can observe to choose a food source for nutrition.

Unlike an algorithm honey bees that have two groups of bees (bees trackers food and bees observers), bees in the ABC algorithm are more specialized. The target function $f(k)$ can be coded as $F(x)$ and represents the amount of nectar at x , so the probability of p_i observing bees choosing to go to food source on x_i , and can be defined with:

$$P_i = \frac{F(x_i)}{\sum_{j=1}^S F(x_j)} \quad (3)$$

where the S number of food sources. For a specific source food efficiency, the efficiency of the intake is determined by F/τ where the F nectar, and τ time spent at the food source

If the food source is tried at a certain number of without improvement, it is also abandoned by bees on this will randomly start exploring new locations. The pseudo-code of the ABC algorithm is presented in Table 2 [13].

Table 1: Pseudo code of Artificial Bee Colony Optimization

```

Artificial Bee Colony Optimization
Objective function  $f(x)$ ,  $x = (x_1, \dots, x_n)^T$  constraints
Encode  $f(x)$  into virtual nectar levels
Define dance routine (strength, direction) or protocol
While (criterion)
    for loop over all  $n$  dimensions
        (or nodes for routing and scheduling problems)
        Generate new solutions
    end for
    Communicate and update the optimal solution set
end while
Decode and output the best results

```

4. MATHEMATICAL FORMULATION OF THE FLEXIBLE JOB SHOP PROBLEM

The case study covers the planning and scheduling of production cycles related to the FJSP solution. The basic structure of the problem being solved relates to a set of jobs that need to be done on the machines, and each job is allocated to a list of activities that are processed in the order.

The essence of the problem and the defined activity is to keep the total completion time as low as possible in accordance with the planned operations with defined time of each operation individually. The set of operations performed to make one job complete and therefore a finished product. The mathematical model of FJSP can be represented as follows.

It is necessary to schedule n products $J = \{J_1, J_2, \dots, J_n\}$, with each job J_j ($j = 1, 2, \dots, n$) having a predetermined order of operations n_j ($O_{1,j}, O_{2,j}, \dots$ They, j), should be realized in the order given in m machines $M = \{M_1, M_2, \dots, M_k\}$ [9].

For a completely flexible problem, each machine can perform only one operation at a time, and the processing time of each operation depends on the machines available and is represented by $t_{i,j,k}$ (processing time of the operation $O_{i,j}$ on the machine M_k). The goal of the problem observed is to assign each operation to a corresponding machine and then determine the arrangement of all the machines assigned to the operations to reduce the target function $C_{\max}$, in this case minimizing the manufacturing process based PSO and ABC.

The following notation was used to define the mathematical formulation of FJSP [14]:

4.1 Presentation of the Model

$p_{(i)}$ - process plans of job i ($p_{(i)} \in P_i$),

P_i - the set of alternative process plans for job i ,

$O_{ip(i)}$ - ordered set of operations in the process plan $p_{(i)}$ of job i ($O_{ip(i)} \subseteq O$), where $O_{ip(i)f(i)}$ is the first and $O_{ip(i)l(i)}$ is the last element of $O_{ip(i)}$,

O_i - the set of operations in all process plans of job i , ($O_i = \bigcup_{p_{(i)} \in P_i} O_{ip(i)}$),

Parameters:

$t_{ip(i)jk}$ - the processing time of operation $O_{ip(i)j}$ on machine k ,

L - a large number,

Decision variables:

$Z_{ip(i)}$ - 1, if process plan $p_{(i)}$ of job i is selected; otherwise,

$X_{ip(i)jk}$ - 1, if machine k is selected for operation $O_{ip(i)j}$; 0, otherwise,

$S_{ip(i)jk}$ - the starting time of operation $O_{ip(i)j}$ on machine k ,

$C_{ip(i)jk}$ - the completion time of operation $O_{ip(i)j}$ on machine k ,

$Y_{iji'j'k}$ - 1, if operation O_{ij} precedes operation $O_{i'j'}$ on machine k ; 0, otherwise,

C_i - the completion time of job i ,

$C_{\max}$ - maximum completion time over all jobs (makespan)

The proposed mathematical model is defined as follows:

Objective function: Minimize $C_{\max}$

with constraints:

$$\sum_{k \in M_j} X_{ip(i)jk} = Z_{ip(i)} \quad \forall i \in J, \forall p(i) \in P_i, \forall j \in O_{ip(i)},$$

$$\sum_{p(i) \in P_i} Z_{ip(i)} = 1 \quad \forall i \in J, \quad (4)$$

$$S_{ip(i)jk} + C_{ip(i)jk} \leq (X_{ip(i)jk} * L) \quad \forall i \in J, \forall p(i) \in O_i, \forall j \in O_{ip(i)}, \forall k \in M_j, \quad (6)$$

$$C_{ip(i)jk} \geq S_{ip(i)jk} + t_{ip(i)jk} - (1 - X_{ip(i)jk}) * L \quad \forall i \in J, \forall p(i) \in P_i, \forall j \in O_{ip(i)}, \forall k \in M_j \quad (7)$$

$$\sum_{p(i) \in P_i} S_{ip(i)jk} \geq \sum_{p'(i) \in P_{i'}} C_{ip'(i)j'k} - (Y_{ij i' j' k}) * L$$

$$\forall i < i', \forall j \in O_{ip(i)}, \forall j' \in O_{ip'(i')}, \forall k \in M_j \cap M_{j'}, \quad (8)$$

$$\sum_{p'(i) \in P_{i'}} S_{ip'(i)j'k} \geq \sum_{p(i) \in P_i} C_{ip(i)jk} - (1 - Y_{ij i' j' k}) * L$$

$$\forall i < i', \forall j \in O_{ip(i)}, \forall j' \in O_{ip'(i')}, \forall k \in M_j \cap M_{j'}, \quad (9)$$

$$\sum_{k \in M_j} S_{ip(i)jk} \geq \sum_{k \in M_j} C_{ip(i)j-1,k} \quad \forall i \in J, \forall p(i) \in P(i), \forall j \in O_{ip(i)} - \{O_{ip(i)f(i)}\}, \quad (10)$$

$$C_i \geq \sum_{k \in M_j} C_{ip(i), O_{ip(i)} t(i), k} \quad \forall i \in J, \forall p(i) \in P_i$$

$$C_{\max} \geq C_i \quad \forall i \in J, \quad (11)$$

and

$$Z_{ip(i)} \in \{0, 1\} \quad \forall i \in J, \forall p(i) \in P_i \quad (12)$$

$$X_{ip(i)jk} \in \{0, 1\} \quad \forall i \in J, \forall p(i) \in P_i, \forall j \in O_{ip(i)}, \forall k \in M_j,$$

$$S_{ip(i)jk} \geq 0 \quad \forall i \in J, \forall p(i) \in P_i, \forall j \in O_{ip(i)}, \forall k \in M_j,$$

$$C_{ip(i)jk} \geq 0 \quad \forall i \in J, \forall p(i) \in P_i, \forall j \in O_{ip(i)}, \forall k \in M_j,$$

$$Y_{ij i' j' k} \in \{0, 1\} \quad \forall i < i', \forall j \in O_i, \forall j' \in O_{i'}, \forall k \in M_j \cap M_{j'},$$

$$C_i \geq 0 \quad \forall i \in J.$$

Constraints (4) and (5) make sure that only one process plan is adopted for job i and that operation $O_{ip(i)j}$ is assigned to only one machine. If operation $O_{ip(i)j}$ is not assigned to machine k , the constraints (6) set the starting and completion times of it on machine k equal to zero. If it is assigned, the constraints (7) guarantee that the difference between the starting and the completion times is at least the processing time on machine k . Constraints (8) and (9) take care of the requirement that operation O_{ij} operation $O_{i'j'}$ their adopted process plans cannot be done at the same time on any machine in the set $M_j \cap M_{j'}$. Constraints (10) ensure that the precedence relationships between the operations of a job are not violated. Constraints (11) determine the completion times of the jobs and constraints (12) determine the makespan [14].

5. CASE STUDY

The main motive for the case study is the application of metaheuristics in troubleshooting planning and appointments resources with different constraints during optimization. The severity of the problem is reflected in the application of the limitations in mathematical models on specific example in a production environment.

The goal of the work is to increase productivity. Increased production is reflected in the optimal surgery on the set of machines. Problem deploying

resources in a production environment is one of the difficult NP problems. In literature different examples of resource allocation can be found based on meta-heuristic algorithms.

In this work two meta-heuristic algorithms were used for resolving the presented mathematical models: ABC and PSO. The motive for applying these two algorithms is to compare algorithms in troubleshooting to problems with a greater data scope.

That's how we propose an algorithm for the next research. Incoming troubleshooting parameters consist of machines M and Operation O . What should be noted is also different flexibility when scheduling operations. In Table 1, FJSP submodels are presented with different structure of jobs and machines.

Table 1. Defined problems

Problems	Problem size (n x m)
PFJS1	5 x 5
PFJS2	10 x 5
PFJS3	10 x 10
PFJS4	15 x 10
PFJS5	20 x 15

Table 2. Basic indicators of input operations

Notation	
Number of jobs (n)	5, 10, 20
Number of machines (m)	5, 10, 15
Operations for job i	Uniform[m/2, m + 1]
m _j (machine for j * operation)	Uniform[1, m]
t _{ijk} (i * job j * operation processing time)	t _{ij1} Uniform[1, 99]
k ∈ M _j	t _{ij2...} Uniform[t _{ij1} , 3 x t _{ij1}]

Table 2 presents the underlying variables clearly defined in the mathematical model.

Table 3. Input sequences of tested problems

Alternative process plans for jobs		
Jobs	Process plans	Operation sequence
PFJS1	5	2-3-4-5-1
		1-4-3-2-5
		5-3-4-1-2
		3-1-5-4-2
		4-2-1-5-2
PFJS2	10	2-3-1-5-4
		3-2-1-5-4
		3-4-5-1-2
		5-1-3-2-4
		5-1-2-4-3
		5-1-2-3-4
		4-3-1-5-2
		5-2-1-3-4
		5-1-4-3-2
		5-2-1-3-4
PFJS3	10	1-2-3-4-5-6-7-8-9-10
		1-3-5-10-4-2-7-6-8-9
		2-1-4-3-9-6-8-7-10-5
		2-3-1-5-7-9-8-4-10-6
		3-1-2-6-4-5-9-8-10-7
		3-2-6-4-9-10-1-7-5-8
		2-1-4-3-7-6-10-9-8-5
		3-1-2-6-5-7-9-10-8-4
		1-2-4-6-3-1-7-8-5-9
		2-1-3-7-9-10-6-4-5-8

In Table 3, we can see input sequences and initial schedule of operations on the set of machines. Application meta-heuristics we can get a better schedule operations and therefore higher productivity.

Table 4. Overall time of each operation

Jobs	Operation	M ₁	M ₂	M ₃	M ₄	M ₅					
PFJS1	5	88	-	94	85	-					
		65	35	95	69	55					
		-	45	-	71	75					
		45	-	37	78	80					
		77	68	29	-	83					
Jobs	Operation	M ₁	M ₂	M ₃	M ₄	M ₅					
PFJS2	10	-	85	-	84	-					
		21	29	18	41	50					
		-	54	-	52	-					
		37	54	74	62	57					
		57	81	61	68	30					
		81	-	89	-	11					
		-	20	91	-	66					
		24	84	32	55	-					
		-	7	54	-	39					
		40	83	19	8	-					
Jobs	Operation	M ₁	M ₂	M ₃	M ₄	M ₅	M ₆	M ₇	M ₈	M ₉	M ₁₀
PFJS3	10	-	68	19	55	59	-	62	46	34	61
		33	60	65	81	49	38	66	46	42	70
		41	-	69	44	80	-	82	69	35	-
		71	85	61	49	69	32	-	38	92	63
		24	16	22	61	-	69	21	49	72	53
		-	12	62	8	38	62	27	95	36	65
		36	67	91	63	52	71	92	39	-	45
		81	66	96	44	-	38	49	58	66	69
		96	39	-	71	25	51	50	39	46	-
		75	33	41	-	64	-	77	-	64	58

Table 4 presents all the times of operations of each machine. As we can see, time depends on the machines on which the operations are processed

Tabela 5. Computational results

Problem No.	Problem size						Result			
	Jobs	Machines	PPFL	RFL	Operations	Iteration	CPU time (s)		C _{max}	
							PSO	ACO	PSO	ACO
PFJS1	5	5	Low	Low	5	1000	68	65	380	380
PFJS2	10	5	Low	High	10	1000	181	185	534	534
PFJS3	10	10	Low	High	10	1000	516	518	897	914
PFJS4	15	10	High	High	15	1000	948	950	1151	1208
PFJS5	20	15	High	High	20	1000	2838	3155	763	814

Figure 2: Particle Swarm Optimization: problem size 5x5

Stanković, A.- Petrović, G.- Marković, D.- Čojbašić, Ž. – Simić, N.

It should be noted that machines do not have the ability to perform every operation on each machine, as can be seen in the attached table 4.

5.1 Computational results

After detailed presentation of FJSP through a series of review papers, the second part of the work presented the mathematical model and application of meta-heuristic algorithms. Input data is represented in Table 1, Table 3, and Table 4. The goal of the work is to display the application of these two algorithms to troubleshoot the planning and schedule of resources within the FJSP. It should be noted that input data represented in Table 3 within the sequential schedule and Table 4 of operations on machines can be applied in a real production environment. Table 5 presents the calculation results applied to algorithms and represents the output parameters of the reprimand.

Key output parameters during testing are the speed of the CPU time conversion solution (s) and the total unit of the C_{max} criterion function. Application and testing of the ABC and PSO algorithms, for example FJSP, is applied to a series of submodels presented in Table 1, starting with problems with small dimensions of one production environment with n = 5 jobs and m = 5 machines to extensive problems where we have n = 20 jobs and m = 15 machines. Each job has a series of operations O_{ij} that need to be performed and optimal deployed on a set of alternative machines in order for efficiency to be as high as possible and the schedule time as little as possible in the form of the C_{max} criterion function. We can also see the calculation results as output parameters presented in Table 5 in graphic form in the form of a Gant card in Figure 2, Figure 3, Figure 4 and Figure 5.

Figure 3: Artificial Bee Colony Optimization: problem size 5x5

Figure 4: Particle Swarm Optimization: problem size 20x15

Figure 5: Artificial Bee Colony Optimization: problem size 20x15

6. CONCLUSION AND DISCUSSION

The resource allocation problem falls into a group of problems where the main goals are planning and scheduling resources, in this case, operations on the available set machine within the FJSP. Scheduling and optimizing production processes is a necessary part of an industrial environment. Optimization and optimal resource allocation is an increased process productivity in as short a time range as possible. For one production environment it is especially important to plan properly and resource allocation. FJSP application of meta-heuristic algorithms means how to solve the problem of the production environment and presents the possibility of new better solutions within the deployments.

Optimal job schedule J and set operation O_{ij} belonging to one job at the gathering machine M can save extra time and minimize the total time it takes to complete the job J . The goal of the work is to increase productivity and to downsize the necessary time for finishing jobs through optimal schedule and correct scheduling operations on machines. By applying the ABC and PSO algorithms we got maximum productivity, optimal schedule of operations and minimal value of the C_{max} criterion function. Also, you should note better optimal value of the PSO algorithm in a ABC algorithm based on the presented values in Table 5. As for future research we propose both algorithms for resolving planning and resource planning problems in the production environment due to optimal results and minor differences. In the further research it is necessary to extend the problem, adding additional restrictions and spot it in real time. Such problems will be the subject of future research to be carried out by the authors of this paper.

ACKNOWLEDGEMENTS

This research was financially supported by the Ministry of Education, Science and Technological Development of the Republic of Serbia through the Contract for the scientific-research activity realization and financing in 2020, ID 451-03-68/2020-14200109.

REFERENCES

- [1] A. Stanković, D. Marković, G. Petrović, Ž. Čojbašić, "Metaheuristics for the waste collection vehicle routing problem in urban areas", Series: Working and Living Environmental Protection Vol. 17, No1, pp. 1 – 16, (2020).
- [2] D. Marković, G. Petrović, Ž. Čojbašić, A. Stanković, "The vehicle routing problem with stochastic demands in an urban area – a case study", Facta Universitatis, Series: Mechanical Engineering Vol.18, No1, pp. 107-120, (2020).
- [3] I. A. Chaudhry, A. A. Khan, "A research survey: review of flexible job shop scheduling techniques", International Transactions in Operational Research, Vol. 23, No3, pp. 551-59, (2016).
- [4] H. Ding, X. Gu, "Hybrid of human learning optimization algorithm and particle swarm optimization algorithm with scheduling strategies for the flexible job-shop scheduling problem", Neurocomputing, Vol. 414, No.3, Pages 313-332, (2020).
- [5] A. Ebrahimia, H. Woo, J. S. Lee, C. Wang, "Minimizing total energy cost and tardiness penalty for a scheduling-layout problem in a flexible job shop system: A comparison of four metaheuristic algorithms", Computers & Industrial Engineering, Vol.141,106295, (2020).
- [6] R. H. Caldeira, A.Gnanavelbabu, "Solving the flexible job shop scheduling problem using an improved Jaya algorithm", Computers & Industrial Engineering, Vol. 137, 106064, (2019).
- [7] G. Zhang, Y. F. Hu, J. Sun, W. Zhang, "An improved genetic algorithm for the flexible job shop scheduling problem with multiple time constraints", Swarm and Evolutionary Computation, Vol. 54,100664, (2020).
- [8] B. Marzoukia, O. B. Driss, K. Ghédira, "Solving Distributed and Flexible Job shop Scheduling Problem using a Chemical Reaction Optimization metaheuristic", Procedia Computer Science, Vol. 126, pp. 1424-1433, (2020).
- [9] A. Stanković, G. Petrović, Ž. Čojbašić, D. Marković, "An application of metaheuristic optimization algorithms for solving the flexible job-shopscheduling problem", Operational Research in Engineering Sciences: Theory and Applications, Vol. 3, Issue 3, pp. 13-28, (2020).
- [10] Glover, F. W., Kochenberger, G. A. (Eds.) Handbook of metaheuristics, Vol. 57. Springer Science & Business Media, (2006).
- [11] J. Kennedy, R. Eberhart, "Particle Swarm Optimization", Proceedings of IEEE International Conference on Neural Networks.IV. pp. 1942–1948, doi:10.1109/ICNN.1995.488968, (1995).
- [12] S.A. MirH, N. Abolghasemi, "A particle swarm optimization algorithm for open vehicle routing problem", Expert Systems with Applications, Vol.38, Issue 9, pp. 11547-11551, (2011).
- [13] X. S. Yang, "An introduction with metaheuristic applications", Engineering Optimization, University of Cambridge, United Kingdom, (2010).
- [14] C. Özgüvena, L. Özbakır, Y. Yavuz, "Mathematical models for job-shop scheduling problems with routing and process plan flexibility", Applied Mathematical Modelling, Vol. 34, Issue 6, pp. 1539-1548, (2010).